

Package ‘RAQSAPI’

March 31, 2021

Type Package

Version 2.0.1

Title A R Interface to the US EPA Air Quality System Data Mart API

Description Retrieve air monitoring data and associated metadata from the US Environmental Protection Agency's Air Quality System service using functions. See <https://aqs.epa.gov/aqsweb/documents/data_api.html> for details about the US EPA Data Mart API.

Encoding UTF-8

URL <<https://github.com/USEPA/RAQSAPI>>,
<https://aqs.epa.gov/aqsweb/documents/data_api.html>

BugReports <https://github.com/USEPA/RAQSAPI/issues>

Depends R (>= 3.6.0)

Imports dplyr,
glue,
gtools,
httr,
jsonlite,
lubridate,
magrittr,
purrr,
stringr,
tibble,
rlang,
lifecycle

Suggests desc,
devtools,
goodpractice,
knitr,
lintr,
roxygen2,
rmarkdown,
testthat (>= 3.0.0),
usethis,
covr

SystemRequirements package manual requires pandoc (>= 1.14) <http://pandoc.org>

RoxygenNote 7.1.1

VignetteBuilder knitr
BuildVignettes true
ByteCompile true
License CC0
License_is_FOSS yes
NeedsCompilation no
License_restricts_use no
Language en-US
Collate 'AQSAPI_helperfunctions.R'
 'bystate.R'
 'bycounty.R'
 'bystate.R'
 'byma.R'
 'bypqao.R'
 'bycbsa.R'
 'bybox.R'
 'RAQSAPIlistfunctions.R'
 'setupfunctions.R'
 'zzz.R'
 'RAQSAPI-package.R'
Copyright United States Environmental Protection Agency
RdMacros lifecycle
Roxygen list(markdown = TRUE)
Config/testthat/edition 3

R topics documented:

aqqs_annualsummary_by_box	4
aqqs_annualsummary_by_cbsa	6
aqqs_annualsummary_by_county	7
aqqs_annualsummary_by_site	9
aqqs_annualsummary_by_state	11
aqqs_cbsas	13
aqqs_classes	13
aqqs_counties_by_state	14
aqqs_credentials	15
aqqs_dailysummary_by_box	15
aqqs_dailysummary_by_cbsa	17
aqqs_dailysummary_by_county	19
aqqs_dailysummary_by_site	21
aqqs_dailysummary_by_state	22
aqqs_fields_by_service	24
aqqs_isavailable	25
aqqs_knownissues	25
aqqs_mas	26
aqqs_monitors_by_box	27
aqqs_monitors_by_cbsa	28
aqqs_monitors_by_county	30

aqs_monitors_by_site	31
aqs_monitors_by_state	33
aqs_parameters_by_class	34
aqs_pqaos	35
aqs_qa_blanks_by_county	36
aqs_qa_blanks_by_MA	37
aqs_qa_blanks_by_pqao	39
aqs_qa_blanks_by_site	41
aqs_qa_blanks_by_state	42
aqs_qa_collocated_assessments_by_county	44
aqs_qa_collocated_assessments_by_MA	46
aqs_qa_collocated_assessments_by_pqao	47
aqs_qa_collocated_assessments_by_site	49
aqs_qa_collocated_assessments_by_state	51
aqs_qa_flowrateaudit_by_county	53
aqs_qa_flowrateaudit_by_MA	54
aqs_qa_flowrateaudit_by_pqao	56
aqs_qa_flowrateaudit_by_site	58
aqs_qa_flowrateaudit_by_state	59
aqs_qa_flowrateverification_by_county	61
aqs_qa_flowrateverification_by_MA	63
aqs_qa_flowrateverification_by_pqao	64
aqs_qa_flowrateverification_by_site	66
aqs_qa_flowrateverification_by_state	68
aqs_qa_one_point_qc_by_county	69
aqs_qa_one_point_qc_by_MA	71
aqs_qa_one_point_qc_by_pqao	73
aqs_qa_one_point_qc_by_site	74
aqs_qa_one_point_qc_by_state	76
aqs_qa_pep_audit_by_county	78
aqs_qa_pep_audit_by_MA	79
aqs_qa_pep_audit_by_pqao	81
aqs_qa_pep_audit_by_site	83
aqs_qa_pep_audit_by_state	84
aqs_removeheader	86
aqs_revisionhistory	87
aqs_sampledata_by_box	87
aqs_sampledata_by_cbsa	89
aqs_sampledata_by_county	91
aqs_sampledata_by_site	93
aqs_sampledata_by_state	95
aqs_services_by_box	96
aqs_services_by_cbsa	98
aqs_services_by_county	99
aqs_services_by_MA	100
aqs_services_by_pqao	101
aqs_services_by_site	102
aqs_services_by_state	103
aqs_sign_up	104
aqs_sites_by_county	105
aqs_states	106
aqs_transactionsample_by_county	106

aqs_transactionsample_by_MA	108
aqs_transactionsample_by_site	109
aqs_transactionsample_by_state	111
RAQSAPI	112

Index 114

aqs_annualsummary_by_box
aqs_annualsummary_by_box

Description

[Stable] Returns multiple years of data where annual data is aggregated at the bounding box level. Returned is an annual summary within the input parameter, latitude/longitude bounding box provided for bdate - edate time frame. The data returned is summarized at the annual level. Variables returned include mean value, maxima, percentiles, and etc. If return_header is FALSE (default) the object returned is a tibble, if TRUE an AQS_API_v2 object.

Usage

```
aqs_annualsummary_by_box(  
  parameter,  
  bdate,  
  edate,  
  minlat,  
  maxlat,  
  minlon,  
  maxlon,  
  cdate = NA_Date_,  
  edate = NA_Date_,  
  return_header = FALSE  
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object which represents the minimum latitude of a geographic box. Decimal latitude with north begin positive. Only data north of this latitude will be returned.
maxlat	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north begin positive. Only data south of this latitude will be returned.
minlon	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.

```
aqs_annualsummary_by_cbsa
      aqs_annualsummary_by_cbsa
```

Description

[Stable] Returns multiple years of data where annual data is aggregated at the Core Based Statistical Area (CBSA) level. Returned is an annual summary matching the input parameter, and cbsa_code provided for bdate - edate time frame. The data returned is summarized at the annual level. Variables returned include mean value, maxima, percentiles, and etc. If return_header is FALSE (default) the object returned is a tibble, if TRUE an AQS_API_v2 object.

Usage

```
aqs_annualsummary_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros)
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object that containing annual summary data for the cbsa_code requested. A AQS_Data Mart_APIv2 is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_cbsa functions: [aq_s_dailysummary_by_cbsa\(\)](#), [aq_s_monitors_by_cbsa\(\)](#), [aq_s_sampledata_by_cbsa\(\)](#)

Examples

```
# returns a tibble of annual summary N02
# data the for Charlotte-Concord-Gastonia, NC cbsa for
# January 01, 2017
## Not run: aqs_annualsummary_by_cbsa(parameter = "42602",
                                     bdate = as.Date("20170101",
                                                       format = "%Y%m%d"
                                                     ),
                                     edate = as.Date("20170101",
                                                       format = "%Y%m%d"
                                                     ),
                                     cbsa_code = "16740"
                                   )

## End(Not run)
```

aq_s_annualsummary_by_county

aq_s_annualsummary_by_county

Description

[Stable] Returns multiple years of data where annual data is aggregated at the county level. Returned is an annual summary matching the input parameter, stateFIPS, and county_code provided for bdate - edate time frame. The data returned is summarized at the annual level. Variables returned include mean value, maxima, percentiles, and etc. If return_header is FALSE (default) the object returned is a tibble, if TRUE an AQS_API_v2 object.

Usage

```

aqs_annualsummary_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object that containing annual summary data for the countycode and stateFIPS requested. A AQS_Data Mart_APIv2 is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each

calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_county functions: [aq_s_dailysummary_by_county\(\)](#), [aq_s_monitors_by_county\(\)](#), [aq_s_qa_blanks_by_county\(\)](#), [aq_s_qa_collocated_assessments_by_county\(\)](#), [aq_s_qa_flowrateaudit_by_county\(\)](#), [aq_s_qa_flowrateverification_by_county\(\)](#), [aq_s_qa_one_point_qc_by_county\(\)](#), [aq_s_qa_pep_audit_by_county\(\)](#), [aq_s_sampledata_by_county\(\)](#), [aq_s_transactionsample_by_county\(\)](#)

Examples

```
# returns an aqs S3 object with annual summary FRM/FEM
# PM2.5 data for Wake County, NC between January
# and February 2016
## Not run: aqs_annualsummary_by_county(parameter = "88101",
                                         bdate = as.Date("20160101",
                                                         format = "%Y%m%d"),
                                         edate = as.Date("20180228",
                                                         format = "%Y%m%d"),
                                         stateFIPS = "37",
                                         countycode = "183"
                                         )

## End(Not run)
```

aq_s_annualsummary_by_site

aq_s_annualsummary_by_site

Description

[Stable] Returns multiple years of data where annual data is aggregated at the site level. Returned is an annual summary matching the input parameter, stateFIPS, county_code, and sitenum provided for bdate - edate time frame. The data returned is summarized at the annual level. Variables returned include mean value, maxima, percentiles, and etc. If return_header is FALSE (default) the object returned is a tibble, if TRUE an AQS_API_v2 object.

Usage

```
aqs_annualsummary_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested as a single tibble. If TRUE returns a list of AQSAPI_v2 objects which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object that containing annual summary data for the Sitenum, countycode and stateFIPS requested. A AQS_Data Mart_APIv2 is a 2 item named list in which the first item ($\$Header$) is a tibble of header information from the AQS API and the second item ($\$Data$) is a tibble of the data returned.

Note

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_site functions: [aq_s_dailysummary_by_site\(\)](#), [aq_s_monitors_by_site\(\)](#), [aq_s_qa_blanks_by_site\(\)](#), [aq_s_qa_collocated_assessments_by_site\(\)](#), [aq_s_qa_flowrateaudit_by_site\(\)](#),

[aqs_qa_flowrateverification_by_site\(\)](#), [aqs_qa_one_point_qc_by_site\(\)](#), [aqs_qa_pep_audit_by_site\(\)](#), [aqs_sampledata_by_site\(\)](#), [aqs_services_by_site\(\)](#), [aqs_transactionsample_by_site\(\)](#)

Examples

```
# Returns a tibble of annual summary ozone
# data for the Millbrook School site (#0014) in Wake County,
# NC for 2017 (Note, for annual data, only the
# year portion of the bdate and edate are used and only whole
# years of data are returned. For example, bdate = 2017-12-31 and
# edate = 2018-01-01 will return full data for 2017 and 2018 )
## Not run:
aqs_annualsummary_by_site(parameter = "44201",
                          bdate = as.Date("20170618",
                                           format="%Y%m%d"),
                          edate = as.Date("20190618",
                                           format="%Y%m%d"),
                          stateFIPS = "37",
                          countycode = "183",
                          sitenum = "0014"
                          )

## End(Not run)
```

```
aqs_annualsummary_by_state
      aqs_annualsummary_by_state
```

Description

[Stable] Returns multiple years of data where annual data is aggregated at the state level. Returned is an annual summary matching the input parameter and stateFIPS provided for bdate - edate time frame. The data returned is summarized at the annual level. Variables returned include mean value, maxima, percentiles, and etc. If return_header is FALSE (default) the object returned is a tibble, if TRUE an AQS_API_v2 object.

Usage

```
aqs_annualsummary_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.

bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object that containing annual summary data for the state-FIPS requested. A AQS_Data Mart_APIv2 is a 2 item named list in which the first item (\backslash \$Header) is a tibble of header information from the AQS API and the second item (\backslash \$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of annualsummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_state functions: [aq_s_dailysummary_by_state\(\)](#), [aq_s_monitors_by_state\(\)](#), [aq_s_qa_blanks_by_state\(\)](#), [aq_s_qa_collocated_assessments_by_state\(\)](#), [aq_s_qa_flowrateaudit_by_state\(\)](#), [aq_s_qa_flowrateverification_by_state\(\)](#), [aq_s_qa_one_point_qc_by_state\(\)](#), [aq_s_qa_pep_audit_by_state\(\)](#), [aq_s_sampledata_by_state\(\)](#)

Examples

```
# returns a tibble of all benzene annually
# summaries from North Carolina collected for 1995
## Not run: aqs_annualsummary_by_state(parameter = "45201",
                                     bdate = as.Date("19950515",
                                     format="%Y%m%d"
                                     ),
```

```

                                edate = as.Date("19950515",
                                                format = "%Y%m%d"
                                                ),
                                stateFIPS = "37"
                                )

## End(Not run)

```

 aq_s_cbsas

aq_s_cbsas

Description

[Stable] Returns a table of all cbsas and their cbsa codes.

Usage

```
aqs_cbsas(return_header = FALSE)
```

Arguments

`return_header` If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object of all cbsas and their cbsa codes for constructing other requests.

Examples

```

#returns a tibble or an AQS_Data Mart_APIv2 S3 object of cbsas
# and their respective cbsa codes
## Not run: aqs_cbsas()

```

 aq_s_classes

aq_s_classes

Description

[Stable] Returns a table of Parameter classes (groups of parameters, i.e. "criteria" or "all"). The information from this function can be used as input to other API calls.

Usage

```
aqs_classes(return_header = FALSE)
```

Arguments

return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object of Parameter classes (groups of parameters, i.e. "criteria" or "all").

Examples

```
#returns a tibble or an AQS_Data Mart_APIv2 S3 object of
# parameter classes (groups of parameters, i.e. "criteria" or
# all")
## Not run: aqs_classes()
```

aq_s_counties_by_state *aq_s_counties_by_state*

Description

[Stable] Returns a table of all counties in within the stateFIPS provided.

Usage

```
aqs_counties_by_state(stateFIPS, return_header = FALSE)
```

Arguments

stateFIPS a R character object which represents the 2 digit state FIPS code (with leading zeros) for the state being requested. @seealso [aq_s_states\(\)](#) for the list of available FIPS codes.

return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object of all counties in the requested state.

Examples

```
#returns an tibble all the counties
# in North Carolina the county FIPS codes (county codes) for
# each.
## Not run: aqs_counties_by_state(stateFIPS = "37")
```

aq_s_credentials *aq_s_credentials*

Description

[Stable] Sets the user credentials for the AQS API. This function needs to be called once and only once every time this library is re-loaded. Users must have a valid username and key which can be obtained through the use of the aq_s_sign_up function, @seealso [aq_s_sign_up\(\)](#) to sign up for AQS data mart credentials.

Usage

```
aqs_credentials(username = NA_character_, key = NA_character_)
```

Arguments

username	a R character object which represents the email account that will be used to connect to the AQS API.
key	the key used in conjunction with the username given to connect to AQS Data Mart.

Value

None

RAQSAPI setup functions

NA

Examples

```
#to authenticate an existing user the email address
# "John.Doe@myemail.com" and key = "MyKey"
# after calling this function please follow the instructions that are sent
# in the verification e-mail before proceeding.
## Not run: aqs_credentials(username = "John.Doe@myemail.com",
                           key = "MyKey")

## End(Not run)
```

aq_s_dailysummary_by_box
aq_s_dailysummary_by_box

Description

[Stable] Returns a tibble or an AQS_Data Mart_APIv2 S3 object containing sample data bounded within a latitude/longitude bounding box

Usage

```

aqs_dailysummary_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object which represents the minimum latitude of a geographic box. Decimal latitude with north begin positive. Only data north of this latitude will be returned.
maxlat	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north begin positive. Only data south of this latitude will be returned.
minlon	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.
maxlon	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east begin positive. Only data west of this longitude will be returned. Note that -80 is less than -70.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object that contains daily summary statistics for the given parameter for an area bounded within a latitude/longitude bounding box. An AQS_Data

Mart_APIv2 is a 2 item named list in which the first item (\backslash \$Header) is a tibble of header information from the AQS API and the second item (\backslash \$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of dailysummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

Examples

```
#returns a tibble of ozone daily summaries in the vicinity of
# central Alabama for the first two days in May 2015

## Not run: aqs_dailysummary_by_box(parameter = "44201",
                                   bdate = as.Date("20140501",
                                                    format = "%Y%m%d"
                                                    ),
                                   edate = as.Date("20160502",
                                                    format = "%Y%m%d"
                                                    ),
                                   mqinlat = "33.3",
                                   maxlat = "33.6",
                                   minlon = "-87.0",
                                   maxlon = "-86.7"
                                   )

## End(Not run)
```

```
aq_s_dailysummary_by_cbsa
  aqs_dailysummary_by_cbsa
```

Description

[Stable] Returns a tibble or an AQS_Data Mart_APIv2 S3 object containing daily summary data aggregated by cbsa (Core Based Statistical Area) code.

Usage

```
aq_s_dailysummary_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```



```

                                format = "%Y%m%d"
                                ),
                                edate = as.Date("20190101",
                                format = "%Y%m%d"
                                ),
                                cbsa_code = "16740"
                                )

## End(Not run)

```

```

aqd_dailysummary_by_county
  aqd_dailysummary_by_county

```

Description

[Stable] Returns a tibble or an AQS_Data Mart_APIv2 S3 object of daily summary data aggregated by county number.

Usage

```

aqd_dailysummary_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aqd_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aqd_counties_by_state() for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.

```
aqs_dailysummary_by_site
    aqs_dailysummary_by_site
```

Description

[Stable] Returns a table of daily summaries with the matching input parameter, stateFIPS, county_code, and sitenum provided for bdate - edate time frame. The data returned is summarized at the daily level. All daily summaries are calculated on midnight to midnight basis in local time. Variables returned include date, mean value, maximum value, etc.

Usage

```
aqs_dailysummary_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

`return_header` If FALSE (default) only returns data requested. If TRUE returns a `AQSAPI_v2` object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an `AQS_Data Mart_APIv2 S3` object that contains daily summary statistics for the given parameter for a single site. An `AQS_Data Mart_APIv2` is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of `dailysummary` to be retrieved at a time. This function conveniently extracts date information from the `bdate` and `edate` parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other `Aggregate_by_site` functions: `aqsummary_by_site()`, `aqmonitors_by_site()`, `aqqa_blanks_by_site()`, `aqqa_collocated_assessments_by_site()`, `aqqa_flowrateaudit_by_site()`, `aqqa_flowrateverification_by_site()`, `aqqa_one_point_qc_by_site()`, `aqqa_pep_audit_by_site()`, `aqsampledata_by_site()`, `aqservices_by_site()`, `aqtransactionssample_by_site()`

Examples

```
#Returns a tibble of daily summary ozone
# data for the Millbrook School site (#0014) in Wake County,
# NC for June 18, 2017.
## Not run:
  aqsummary_by_site(parameter = "44201",
                    bdate = as.Date("20160618",
                                     format = "%Y%m%d"),
                    edate = as.Date("20190618",
                                     format = "%Y%m%d"),
                    stateFIPS = "37",
                    countycode = "183",
                    sitenum = "0014"
                    )
## End(Not run)
```

`aqsummary_by_state`

aqsummary_by_state

Description

[Stable] Returns a tibble or an AQS_Data Mart_APIv2 S3 object containing sample data data aggregated by state FIPS.

Usage

```
aqs_dailysummary_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object that contains daily summary statistics for the given parameter for a single stateFIPS An AQS_Data Mart_APIv2 is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of dailysummary to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar

year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_state functions: `aqs_annualsummary_by_state()`, `aqs_monitors_by_state()`, `aqs_qa_blanks_by_state()`, `aqs_qa_collocated_assessments_by_state()`, `aqs_qa_flowrateaudit_by_state()`, `aqs_qa_flowrateverification_by_state()`, `aqs_qa_one_point_qc_by_state()`, `aqs_qa_pep_audit_by_state()`, `aqs_sampledata_by_state()`

Examples

```
# returns a tibble of all benzene daily
# summaries from North Carolina collected on May 15th, 1995
## Not run: aqs_dailysummary_by_state(parameter = "45201",
                                     bdate = as.Date("19950515",
                                                       format="%Y%m%d"
                                                     ),
                                     edate = as.Date("19970515",
                                                       format = "%Y%m%d"
                                                     ),
                                     stateFIPS = "37"
                                   )

## End(Not run)
```

aq_s_fields_by_service *aq_s_fieldsbyservice*

Description

[Stable] Returns a tibble or an AQS_Data Mart_APIv2 S3 object with the list and definitions of fields in the service requested.

Usage

```
aqs_fields_by_service(service, return_header = FALSE)
```

Arguments

service	a string which represents the services provided by the AQS API. For a list of available services @seealso <a href="https://aq<sub>s</sub>.epa.gov/aq<sub>s</sub>web/documents/data_api.html#services">https://aq_s.epa.gov/aq_sweb/documents/data_api.html#services
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object with containing the list and definitions of fields requested service

Examples

```
# Returns a tibble containing a list and definitions
# of fields in the Sample Data service
## Not run: fields_by_service(service = "list")
```

aq _s _isavailable	<i>aq_s_isavailable</i>
------------------------------	-----------------------------------

Description

[Stable] returns a tibble or an AQS_Data Mart_APIv2 S3 object explaining the status of the AQS API.

Usage

```
aqs_isavailable(return_header = FALSE)
```

Arguments

`return_header` If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object which details the status of the AQS API (The status information is located in the header)

list functions

NA

Examples

```
#check if the AQS API is up, running and accepting requests.
## Not run: aqs_isAvailable()
```

aq _s _knownissues	<i>aq_s_knownissues</i>
------------------------------	-----------------------------------

Description

[Stable] Returns a table of any known issues with system functionality or the data. These are usually issues that have been identified internally and will require some time to correct in Data Mart or the API. This function implements a direct API call to Data Mart and returns data directly from the API. Issues returned via this function do not include any issues from the RAQSAPI R package.

Usage

```
aqs_knownissues(return_header = FALSE)
```

Arguments

return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object that contains information involving known issues with the Data Mart API.

Examples

```
#retrieve the list of known issues directly from the AQS data mart API
## Not run: aqs_knownissues()
```

aqs_mas	<i>aqs_mas</i>
---------	----------------

Description

[Stable] Returns a table of monitoring agencies (MA).

Usage

```
aqs_mas(return_header = FALSE)
```

Arguments

return_header If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object of monitoring agencies and their associated agency code.

Examples

```
#returns a tibble or an AQS_Data Mart_APIv2 S3 object
# of monitoring agencies and their respective
# monitoring agency codes.
## Not run: aqs_mas()
```

 aq_s_monitors_by_box aq_s_monitors_by_box

Description

[Stable] Returns a table of monitors at all sites with the provided parameternum, aggregated by latitude/longitude bounding box (`_by_box`) for `bdate` - `edate` time frame.

Usage

```
aqs_monitors_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  return_header = FALSE
)
```

Arguments

<code>parameter</code>	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
<code>bdate</code>	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
<code>edate</code>	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
<code>minlat</code>	a R character object which represents the minimum latitude of a geographic box. Decimal latitude with north begin positive. Only data north of this latitude will be returned.
<code>maxlat</code>	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north begin positive. Only data south of this latitude will be returned.
<code>minlon</code>	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.
<code>maxlon</code>	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east begin positive. Only data west of this longitude will be returned. Note that -80 is less than -70.
<code>return_header</code>	If FALSE (default) only returns data requested. If TRUE returns a <code>AQSAPI_v2</code> object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an `AQS_Data Mart_APIv2 S3` object of monitors from a latitude/longitude bounding box (`_by_box`).

by_box aggregate functions

NA

See AlsoOther Aggregate_by_box functions: [aq_s_annualsummary_by_box\(\)](#), [aq_s_sampledata_by_box\(\)](#)**Examples**

```
# returns a tibble of all ozone
# monitors in the vicinity of central Alabama that operated in
# 1995
## Not run: aqs_monitors_by_box(parameter="44201",
                                bdate=as.Date("19950101",
                                                format="%Y%m%d"),
                                edate=as.Date("19951231",
                                                format="%Y%m%d"),
                                minlat="33.3",
                                maxlat="33.6",
                                minlon="-87.0",
                                maxlon="-86.7"
                                )

## End(Not run)
```

aq_s_monitors_by_cbsa *aq_s_monitors_by_cbsa*

Description

[Stable] Returns a table of monitors at all sites with the provided parameternum, aggregated by Core Based Statistical Area (CBSA) for bdate - edate time frame.

Usage

```
aqs_monitors_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.

edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros)
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object that is the return value from the AQS API. A AQS_Data Mart_APIv2 object is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

by_cbsa aggregate functions

NA

See Also

Other Aggregate_by_cbsa functions: [aq_s_annualsummary_by_cbsa\(\)](#), [aq_s_dailysummary_by_cbsa\(\)](#), [aq_s_sampledata_by_cbsa\(\)](#)

Examples

```
# returns a tibble of N02 monitors
# for Charlotte-Concord-Gastonia, NC cbsa that were operating
# on January 01, 2017
## Not run: aqs_monitors_by_cbsa(parameter="42602",
                                bdate=as.Date("20170101",
                                                format="%Y%m%d"),
                                edate=as.Date("20170101",
                                                format="%Y%m%d"),
                                cbsa_code="16740"
                                )

## End(Not run)
```

 aq_s_monitors_by_county

aq_s_monitors_by_county

Description

[Stable] Returns a table of monitors at a site with the provided parameternum, stateFIPS and county_code for bdate - edate time frame.

Usage

```
aqs_monitors_by_county(  
  parameter,  
  bdate,  
  edate,  
  stateFIPS,  
  countycode,  
  cbdate = NA_Date_,  
  cedate = NA_Date_,  
  return_header = FALSE  
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object of monitors from a selected county

by_county aggregate functions

NA

See Also

Other Aggregate_by_county functions: [aq_s_annualsummary_by_county\(\)](#), [aq_s_dailysummary_by_county\(\)](#), [aq_s_qa_blanks_by_county\(\)](#), [aq_s_qa_collocated_assessments_by_county\(\)](#), [aq_s_qa_flowrateaudit_by_county\(\)](#), [aq_s_qa_flowrateverification_by_county\(\)](#), [aq_s_qa_one_point_qc_by_county\(\)](#), [aq_s_qa_pep_audit_by_county\(\)](#), [aq_s_sampledata_by_county\(\)](#), [aq_s_transactionsample_by_county\(\)](#)

Examples

```
# returns an aqs_v2 S3 object containing all SO2 monitors in
# Hawaii County, HI that were operating on May 01, 2015.
## Not run: aqs_monitors_by_county(parameter="42401",
                                bdate=as.Date("20150501", format="%Y%m%d"),
                                edate=as.Date("20150502", format="%Y%m%d"),
                                stateFIPS="15",
                                countycode="001"
                                )

## End(Not run)
```

aq_s_monitors_by_site *aq_s_monitors_by_site*

Description

[Stable] Returns a table of monitors at all sites with the provided parameternum, stateFIPS, county_code, and sitenum for bdate - edate time frame.

Usage

```
aqs_monitors_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object of monitors from a selected site

by_site aggregate functions

NA

Note

all monitors that operated between the bdate and edate will be returned

See Also

Other Aggregate_by_site functions: [aq_s_annualsummary_by_site\(\)](#), [aq_s_dailysummary_by_site\(\)](#), [aq_s_qa_blanks_by_site\(\)](#), [aq_s_qa_collocated_assessments_by_site\(\)](#), [aq_s_qa_flowrateaudit_by_site\(\)](#), [aq_s_qa_flowrateverification_by_site\(\)](#), [aq_s_qa_one_point_qc_by_site\(\)](#), [aq_s_qa_pep_audit_by_site\(\)](#), [aq_s_sampledata_by_site\(\)](#), [aq_s_services_by_site\(\)](#), [aq_s_transactionsample_by_site\(\)](#)

Examples

```

#Returns a tibble of the SO2 monitors at Hawaii
# Volcanoes NP site (#0007) in Hawaii County, HI that were operating on
# May 1 , 2015. (Note, all monitors that operated between the bdate and
# edate will be returned)
## Not run:
  aqs_monitors_by_site(parameter = "42401",
                       bdate = as.Date("20150501",
                                       format="%Y%m%d"),
                       edate = as.Date("20150502",
                                       format="%Y%m%d"),
                       stateFIPS = "15",
                       countycode = "001",
                       sitenum = "0007"
                       )

## End(Not run)

```

aq_s_monitors_by_state aq_s_monitors_by_state

Description

[Stable] Returns a table of monitors at all sites with the provided parameternum, stateFIPS and county_code for bdate - edate time frame.

Usage

```

aqs_monitors_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.

cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object of monitors from a selected state

by_state aggregate functions

NA

See Also

Other Aggregate_by_state functions: [aq_s_annualsummary_by_state\(\)](#), [aq_s_dailysummary_by_state\(\)](#), [aq_s_qa_blanks_by_state\(\)](#), [aq_s_qa_collocated_assessments_by_state\(\)](#), [aq_s_qa_flowrateaudit_by_state\(\)](#), [aq_s_qa_flowrateverification_by_state\(\)](#), [aq_s_qa_one_point_qc_by_state\(\)](#), [aq_s_qa_pep_audit_by_state\(\)](#), [aq_s_sampledata_by_state\(\)](#)

Examples

```
# returns a tibble of SO2 monitors in Hawaii
#   that were operating on May 01, 2015
## Not run: aqs_monitors_by_state(parameter="88101",
                                bdate=as.Date("20170101",
                                                format="%Y%m%d"),
                                edate=as.Date("20171231",
                                                format="%Y%m%d"),
                                stateFIPS="01"
                                )

## End(Not run)
```

aq_s_parameters_by_class

aq_s_parameters_by_class

Description

[Stable] Returns parameters associated with the input class.

Usage

```
aqs_parameters_by_class(class, return_header = FALSE)
```

Arguments

- class** a R character object that represents the class requested, @seealso [aq_s_classes\(\)](#) for retrieving available classes. The class R character object must be a valid class as returned from [aq_s_classes\(\)](#). The class must be an exact match to what is returned from [aq_s_classes\(\)](#).
- return_header** If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing the parameters associated with the class requested. NULL is returned for classes not found.

Examples

```
# Returns a tibble of AQS parameters in the criteria class
## Not run: aqs_parameters_by_class(class = "CRITERIA")
```

aq_s_pqaos

aq_s_pqaos

Description

[Stable] Returns a table of primary quality assurance organizations (pqaos).

Usage

```
aqs_pqaos(return_header = FALSE)
```

Arguments

- return_header** If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object of pqaos and their associated pqao code.

Examples

```
#To retrieve a tibble of primary quality assurance
# organizations (pqaos)
## Not run: pqaos <- aqs_pqaos()
```

```
aqs_qa_blanks_by_county
      aqs_qa_blanks_by_county
```

Description

[Stable] Returns a tibble or an AQS_Data Mart_APIv2 S3 object containing blank sample data aggregated by county number.

Usage

```
aqs_qa_blanks_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object that contains quality assurance blank sample data for all monitors within the input stateFIPS and countycode. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of qa_blank data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate _by_county functions: [aq_s_annualsummary_by_county\(\)](#), [aq_s_dailysummary_by_county\(\)](#), [aq_s_monitors_by_county\(\)](#), [aq_s_qa_collocated_assessments_by_county\(\)](#), [aq_s_qa_flowrateaudit_by_county\(\)](#), [aq_s_qa_flowrateverification_by_county\(\)](#), [aq_s_qa_one_point_qc_by_county\(\)](#), [aq_s_qa_pep_audit_by_county\(\)](#), [aq_s_sampledata_by_county\(\)](#), [aq_s_transactionsample_by_county\(\)](#)

Examples

```
# returns an tibble with PM2.5 blank data for
#   Colbert County, AL for January 2018
## Not run: aqs_qa_blanks_by_county(parameter = "88101",
#                                   bdate = as.Date("20170101",
#                                                     format="%Y%m%d"),
#                                   edate = as.Date("20190131",
#                                                  format="%Y%m%d"),
#                                   stateFIPS = "01",
#                                   countycode = "033"
#                                   )

## End(Not run)
```

aq_s_qa_blanks_by_MA *aq_s_qa_blanks_by_MA*

Description

[Stable] Returns a tibble or an AQS_Data_Mart_APIv2 S3 object containing Quality assurance - blanks sample data aggregated by monitoring agency code (_by_MA).

Usage

```
aqs_qa_blanks_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object that contains quality assurance blank sample data for all monitors within the input MA_code. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

by_ma aggregate functions

NA

Note

The AQS API only allows for a single year of qa_blank data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will

take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_MA functions: [aq_s_qa_collocated_assessments_by_MA\(\)](#), [aq_s_qa_flowrateaudit_by_MA\(\)](#), [aq_s_qa_flowrateverification_by_MA\(\)](#), [aq_s_qa_one_point_qc_by_MA\(\)](#), [aq_s_qa_pep_audit_by_MA\(\)](#)

Examples

```
# returns a tibble containing PM2.5 blank data for
# January 2018 where the Monitoring Agency is the Alabama
# Department of Environmental Management (agency 0013)
## Not run: aqs_qa_blanks_by_MA(parameter = "88101",
                                bdate = as.Date("20170101",
                                                  format = "%Y%m%d"),
                                edate = as.Date("20190131",
                                                  format = "%Y%m%d"),
                                MA_code = "0013"
                                )

## End(Not run)
```

aq_s_qa_blanks_by_pqao *aq_s_qa_blanks_by_pqao*

Description

[Stable] Returns a tibble or an AQS_Data Mart_APIv2 S3 object containing Quality assurance data - blanks sample data aggregated by Primary Quality Assurance Organization (PQAO) code.

Usage

```
aqs_qa_blanks_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  cdate = NA_Date_,
  edate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.

pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing quality assurance blank data for monitors within a pqao. An AQS_Data Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

by_pqao aggregate functions

NA

Note

The AQS API only allows for a single year of qa_blank data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_pqao functions: [aq_s_qa_collocated_assessments_by_pqao\(\)](#), [aq_s_qa_flowrateaudit_by_pqao\(\)](#), [aq_s_qa_flowrateverification_by_pqao\(\)](#), [aq_s_qa_one_point_qc_by_pqao\(\)](#), [aq_s_qa_pep_audit_by_pqao\(\)](#)

Examples

```
# returns tibble of PM2.5 blank data for
# January 2018 where the PQA0 is the Alabama Department of
# Environmental Management (agency 0013)
## Not run: aqs_qa_blanks_by_pqao(parameter = "88101",
                                bdate = as.Date("20180101",
                                                  format = "%Y%m%d"),
                                edate = as.Date("20180131",
                                                  format = "%Y%m%d"),
                                pqao_code = "0013"
                                )
```



```
## End(Not run)
```

```
aqs_qa_blanks_by_site  aqs_qa_blanks_by_site
```

Description

[Stable] Aggregates multiple years of qa blank data where the blank data is aggregated at the site level and returns table with a tibble of Quality assurance data - blanks samples. Blanks are unexposed sample collection devices (e.g., filters) that are transported with the exposed sample devices to assess if contamination is occurring during the transport or handling of the samples.

Usage

```
aqs_qa_blanks_by_site(  
  parameter,  
  bdate,  
  edate,  
  stateFIPS,  
  countycode,  
  sitenum,  
  cbdate = NA_Date_,  
  cedate = NA_Date_,  
  return_header = FALSE  
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

`return_header` If FALSE (default) only returns data requested. If TRUE returns a `AQSAPI_v2` object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an `AQS_Data_Mart_APIv2 S3` object that contains quality assurance blank sample data for single monitoring site. An `AQS_Data_Mart_APIv2` is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of qa_blank data to be retrieved at a time. This function conveniently extracts date information from the `bdate` and `edate` parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other `Aggregate_by_site` functions: `aqs_annualsummary_by_site()`, `aqs_dailysummary_by_site()`, `aqs_monitors_by_site()`, `aqs_qa_collocated_assessments_by_site()`, `aqs_qa_flowrateaudit_by_site()`, `aqs_qa_flowrateverification_by_site()`, `aqs_qa_one_point_qc_by_site()`, `aqs_qa_pep_audit_by_site()`, `aqs_sampledata_by_site()`, `aqs_services_by_site()`, `aqs_transactionsample_by_site()`

Examples

```
#Returns a tibble of PM2.5 blank
# data for the Muscle Shoals site (#0014) in Colbert County, AL
# for January 2018
## Not run:
  aqs_qa_blanks_by_site(parameter = "88101",
                        bdate = as.Date("20170101",
                                         format="%Y%m%d"),
                        edate = as.Date("20190131",
                                         format="%Y%m%d"),
                        stateFIPS = "01",
                        countycode = "033",
                        sitenum = "1002"
                        )

## End(Not run)
```

aq_s_qa_blanks_by_state

aq_s_qa_blanks_by_state

Description

[Stable] Returns a tibble or an AQS_Data Mart_APIv2 S3 object containing Quality assurance blank sample data aggregated by state FIPS.

Usage

```
aqs_qa_blanks_by_state(  
  parameter,  
  bdate,  
  edate,  
  stateFIPS,  
  cdate = NA_Date_,  
  edate = NA_Date_,  
  return_header = FALSE  
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object that contains quality assurance blank sample data for all monitors within the input stateFIPS. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of qa_blank data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar

year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_state functions: [aq_s_annualsummary_by_state\(\)](#), [aq_s_dailysummary_by_state\(\)](#), [aq_s_monitors_by_state\(\)](#), [aq_s_qa_collocated_assessments_by_state\(\)](#), [aq_s_qa_flowrateaudit_by_state\(\)](#), [aq_s_qa_flowrateverification_by_state\(\)](#), [aq_s_qa_one_point_qc_by_state\(\)](#), [aq_s_qa_pep_audit_by_state\(\)](#), [aq_s_sampledata_by_state\(\)](#)

Examples

```
# returns a aqs_v2 object which contains PM2.5 blank data
# for Alabama for January 2018
## Not run: aqs_qa_blanks_by_state(parameter = "88101",
                                bdate = as.Date("20180101",
                                                format = "%Y%m%d"
                                                ),
                                edate = as.Date("20180131",
                                                format = "%Y%m%d"),
                                stateFIPS = "01"
                                )

## End(Not run)
```

```
aqs_qa_collocated_assessments_by_county
  aqs_qa_collocated_assessments_by_county
```

Description

[Stable] Returns a table of collocated assessment data aggregated by matching input parameter, stateFIPS and county_code provided for bdate - edate time frame.

Usage

```
aqs_qa_collocated_assessments_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aqsa_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aqsa_counties_by_state() for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing quality assurance collocated assessment data for monitors within a county. An AQS_Data Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of collocated assessments to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_county functions: [aqsa_annualsummary_by_county\(\)](#), [aqsa_dailysummary_by_county\(\)](#), [aqsa_monitors_by_county\(\)](#), [aqsa_qa_blanks_by_county\(\)](#), [aqsa_qa_flowrateaudit_by_county\(\)](#), [aqsa_qa_flowrateverification_by_county\(\)](#), [aqsa_qa_one_point_qc_by_county\(\)](#), [aqsa_qa_pep_audit_by_county\(\)](#), [aqsa_sampledata_by_county\(\)](#), [aqsa_transactionsample_by_county\(\)](#)

Examples

```
# returns a tibble with collocated assessment data
# for FRM PM2.5 in Madison County, AL for January 2013
## Not run: aqs_qa_collocated_assessments_by_county(parameter = "88101",
                                                    bdate = as.Date("20130101",
                                                            format = "%Y%m%d"
                                                            ),
                                                    edate = as.Date("20150131",
                                                            format = "%Y%m%d"
                                                            ),
                                                    stateFIPS = "01",
                                                    countycode = "089"
                                                    )

## End(Not run)
```

```
aqs_qa_collocated_assessments_by_MA
      aqs_qa_collocated_assessments_by_MA
```

Description

[Stable] Returns a table of collocated assessment data aggregated by matching input parameter, and monitoring agency (MA) code provided for bdate - edate time frame.

Usage

```
aqs_qa_collocated_assessments_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.

cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing quality assurance collocated assessment data for monitors within a monitoring agency. An AQS_Data Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of collocated assessments to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_MA functions: [aq_s_qa_blanks_by_MA\(\)](#), [aq_s_qa_flowrateaudit_by_MA\(\)](#), [aq_s_qa_flowrateverification_by_MA\(\)](#), [aq_s_qa_one_point_qc_by_MA\(\)](#), [aq_s_qa_pep_audit_by_MA\(\)](#)

Examples

```
# returns a tibble containing collocated assessment
# data for FRM PM2.5 January 2013 where the Monitoring Agency is
# the Alabama Department of Environmental Management (agency 0013)
## Not run: aqs_qa_collocated_assessments_by_MA(parameter="88101",
                                             bdate = as.Date("20130101",
                                                           format = "%Y%m%d"),
                                             edate = as.Date("20150131",
                                                           format = "%Y%m%d"),
                                             MA_code = "0013"
                                             )

## End(Not run)
```

aq_s_qa_collocated_assessments_by_pqao

aq_s_qa_collocated_assessments_by_pqao

Description

[Stable] Returns a table of collocated assessment data aggregated by matching input parameter, and Primary Quality Assurance Organisation (PQAO) code provided for bdate - edate time frame.

Usage

```
aqs_qa_collocated_assessments_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing quality assurance collocated assessment data for monitors within a pqao. An AQS_Data Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of collocated assessments to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API

calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_pqao functions: [aq_s_qa_blanks_by_pqao\(\)](#), [aq_s_qa_flowrateaudit_by_pqao\(\)](#), [aq_s_qa_flowrateverification_by_pqao\(\)](#), [aq_s_qa_one_point_qc_by_pqao\(\)](#), [aq_s_qa_pep_audit_by_pqao\(\)](#)

Examples

```
# returns a tibble of collocated assessment
# data for FRM PM2.5 January 2013 where the PQAO is the Alabama
# Department of Environmental Management (agency 0013)
## Not run: aqs_qa_collocated_assessments_by_pqao(parameter = "88101",
#                                               bdate = as.Date("20130101",
#                                               format = "%Y%m%d"),
#                                               edate = as.Date("20150131",
#                                               format = "%Y%m%d"),
#                                               pqao_code = "0013"
#                                               )

## End(Not run)
```

```
aqs_qa_collocated_assessments_by_site
  aqs_qa_collocated_assessments_by_site
```

Description

[Stable] Returns a table of collocated assessment data aggregated by matching input parameter, stateFIPS, county_code, and sitenum provided for bdate - edate time frame.

Usage

```
aqs_qa_collocated_assessments_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing quality assurance collocated assessment data for monitors within a site. An AQS_Data Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of collocated assessments to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_site functions: [aq_s_annualsummary_by_site\(\)](#), [aq_s_dailysummary_by_site\(\)](#), [aq_s_monitors_by_site\(\)](#), [aq_s_qa_blanks_by_site\(\)](#), [aq_s_qa_flowrateaudit_by_site\(\)](#), [aq_s_qa_flowrateever](#), [aq_s_qa_one_point_qc_by_site\(\)](#), [aq_s_qa_pep_audit_by_site\(\)](#), [aq_s_sampledata_by_site\(\)](#), [aq_s_services_by_site\(\)](#), [aq_s_transactionsample_by_site\(\)](#)

Examples

```
#returns a tibble of collocated assessment data
# for FRM PM2.5 at the Huntsville Old Airport site (#0014)
# in Madison County, AL for January 2013:
## Not run: aqs_qa_collocated_assessments_by_site(parameter = "88101",
                                                bdate = as.Date("20130101",
                                                                format = "%Y%m%d"
                                                                ),
                                                edate = as.Date("20150131",
                                                                format = "%Y%m%d"
                                                                ),
                                                stateFIPS = "01",
                                                countycode = "089",
                                                sitenum = "0014"
                                                )

## End(Not run)
```

```
aqs_qa_collocated_assessments_by_state
  aqs_qa_collocated_assessments_by_state
```

Description

[Stable] Returns a table of collocated assessment data aggregated by matching input parameter and stateFIPS provided for bdate - edate time frame.

Usage

```
aqs_qa_collocated_assessments_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aqs_states() for the list of available FIPS codes.

cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing quality assurance collocated assessment data for monitors within a state. An AQS_Data Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of collocated assessments to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_state functions: [aqs_annualsummary_by_state\(\)](#), [aqs_dailysummary_by_state\(\)](#), [aqs_monitors_by_state\(\)](#), [aqs_qa_blanks_by_state\(\)](#), [aqs_qa_flowrateaudit_by_state\(\)](#), [aqs_qa_flowrateverification_by_state\(\)](#), [aqs_qa_one_point_qc_by_state\(\)](#), [aqs_qa_pep_audit_by_state\(\)](#), [aqs_sampledata_by_state\(\)](#)

Examples

```
# returns a tibble of collocated
# assessment data for FRM2.5 for January 2013
## Not run: aqs_qa_collocated_assessments_by_state(parameter="88101",
#           bdate = as.Date("20130101",
#                           format = "%Y%m%d"
#                           ),
#           edate = as.Date("20150131",
#                           format = "%Y%m%d"
#                           ),
#           stateFIPS = "01"
#           )

## End(Not run)
```

```
aqs_qa_flowrateaudit_by_county
      aqs_qa_flowrateaudit_by_county
```

Description

[Stable] Returns a table containing flow rate audit data aggregated by parameter code, stateFIPS and countycode for bdate - edate time frame.

Usage

```
aqs_qa_flowrateaudit_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aqs_counties_by_state() for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing flow rate audit data for the requested countycode and stateFIPS. An AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\\$Header) is a tibble of header information from the AQS API and the second item (\\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_county functions: [aqs_annualsummary_by_county\(\)](#), [aqs_dailysummary_by_county\(\)](#), [aqs_monitors_by_county\(\)](#), [aqs_qa_blanks_by_county\(\)](#), [aqs_qa_collocated_assessments_by_county\(\)](#), [aqs_qa_flowrateverification_by_county\(\)](#), [aqs_qa_one_point_qc_by_county\(\)](#), [aqs_qa_pep_audit_by_county\(\)](#), [aqs_sampledata_by_county\(\)](#), [aqs_transactionsample_by_county\(\)](#)

Examples

```
#Returns a tibble of flow rate audit data for
# Jefferson County, AL for January 2018
## Not run: aqs_qa_flowrateaudit_by_county(parameter = "88101",
                                         bdate = as.Date("20170101",
                                                         format="%Y%m%d"),
                                         edate = as.Date("20190131",
                                                         format = "%Y%m%d"),
                                         stateFIPS = "01",
                                         countycode = "073"
                                         )

## End(Not run)
```

```
aqs_qa_flowrateaudit_by_MA
      aqs_qa_flowrateaudit_by_MA
```

Description

[Stable] Returns a table containing flow rate audit data aggregated by parameter code and monitoring agency code (*_by_MA*) for bdate - edate time frame.

Usage

```
aqs_qa_flowrateaudit_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing flow rate audit data for the requested MA_code. An AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_MA functions: [aq_s_qa_blanks_by_MA\(\)](#), [aq_s_qa_collocated_assessments_by_MA\(\)](#), [aq_s_qa_flowrateverification_by_MA\(\)](#), [aq_s_qa_one_point_qc_by_MA\(\)](#), [aq_s_qa_pep_audit_by_MA\(\)](#)

Examples

```
# returns a tibble of flow rate audit data
# for FRM PM2.5 January 2016 - Januray 2018 where the Monitoring Agency is
# the Jefferson County, AL Department of Health (agency 0550)
## Not run: aqs_qa_flowrateaudit_by_MA(parameter = "88101",
                                     bdate = as.Date("20160101",
                                                       format = "%Y%m%d"),
                                     edate = as.Date("20180131",
                                                       format = "%Y%m%d"),
                                     MA_code = "0550"
                                     )

## End(Not run)
```

```
aqs_qa_flowrateaudit_by_pqao
      aqs_qa_flowrateaudit_by_pqao
```

Description

[Stable] Returns a table containing flow rate audit data aggregated by parameter code and Primary Quality Assurance Organization (PQAO) code for bdate - edate time frame.

Usage

```
aqs_qa_flowrateaudit_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).

```
aqs_qa_flowrateaudit_by_site
      aqs_qa_flowrate audit_by_site
```

Description

[Stable] Returns a table containing flow rate audit data aggregated by parameter code, stateFIPS, countycode and site number for bdate - edate time frame.

Usage

```
aqs_qa_flowrateaudit_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aqs_counties_by_state() for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing flow rate audit data for the requested sitenum, countycode and stateFIPS. An AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item ($\$Header$) is a tibble of header information from the AQS API and the second item ($\$Data$) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_site functions: [aq_s_annualsummary_by_site\(\)](#), [aq_s_dailysummary_by_site\(\)](#), [aq_s_monitors_by_site\(\)](#), [aq_s_qa_blanks_by_site\(\)](#), [aq_s_qa_collocated_assessments_by_site\(\)](#), [aq_s_qa_flowrateverification_by_site\(\)](#), [aq_s_qa_one_point_qc_by_site\(\)](#), [aq_s_qa_pep_audit_by_site\(\)](#), [aq_s_sampledata_by_site\(\)](#), [aq_s_services_by_site\(\)](#), [aq_s_transactionsample_by_site\(\)](#)

Examples

```
# returns a tibble of flow rate audit data
# for the Wylam site (#2003) in Jefferson County, AL
# for January 2018:
## Not run: aqs_qa_flowrateaudit_by_site(parameter = "88101",
                                         bdate = as.Date("20150101",
                                                           format="%Y%m%d"),
                                         edate = as.Date("20180131",
                                                           format="%Y%m%d"),
                                         stateFIPS = "01",
                                         countycode = "073",
                                         sitenum = "2003"
                                         )

## End(Not run)
```

```
aqs_qa_flowrateaudit_by_state
      aqs_qa_flowrateaudit_by_state
```

Description

[Stable] Returns a table containing flow rate audit data aggregated by parameter code and stateFIPS for bdate - edate time frame.

Usage

```

aqs_qa_flowrateaudit_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object containing flow rate audit data for the requested stateFIPS. An AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (`Header`) is a tibble of header information from the AQS API and the second item (`Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other `Aggregate_by_state` functions: `aqs_annualsummary_by_state()`, `aqs_dailysummary_by_state()`, `aqs_monitors_by_state()`, `aqs_qa_blanks_by_state()`, `aqs_qa_collocated_assessments_by_state()`, `aqs_qa_flowrateverification_by_state()`, `aqs_qa_one_point_qc_by_state()`, `aqs_qa_pep_audit_by_state()`, `aqs_sampledata_by_state()`

Examples

```
# returns a tibble of flow rate audit
# data for Alabama in January 2018
## Not run: aqs_qa_flowrateaudit_by_state(parameter = "88101",
                                         b date = as.Date("20170101",
                                                         format = "%Y%m%d"
                                                         ),
                                         edate = as.Date("20180131",
                                                         format = "%Y%m%d"
                                                         ),
                                         stateFIPS = "01"
                                         )

## End(Not run)
```

```
aqs_qa_flowrateverification_by_county
      aqs_qa_flowrateverification_by_county
```

Description

[Stable] Returns a table containing flow rate Verification data for a parameter code aggregated matching input parameter, stateFIPS, and county_code, provided for bdate - edate time frame.

Usage

```
aqs_qa_flowrateverification_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.


```

    ),
    stateFIPS = "01",
    countycode = "033"
  )

## End(Not run)

```

```

aqs_qa_flowrateverification_by_MA
  aqs_qa_flowrateverification_by_MA

```

Description

[Stable] Returns a table containing flow rate Verification data for a parameter code aggregated by matching input parameter, and monitoring agency (MA) code provided for bdate - edate time frame.

Usage

```

aqs_qa_flowrateverification_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing quality assurance flow rate verification data for monitors within a Monitoring agency. An AQS_Data Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate verifications to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_MA functions: [aq_s_qa_blanks_by_MA\(\)](#), [aq_s_qa_collocated_assessments_by_MA\(\)](#), [aq_s_qa_flowrateaudit_by_MA\(\)](#), [aq_s_qa_one_point_qc_by_MA\(\)](#), [aq_s_qa_pep_audit_by_MA\(\)](#)

Examples

```
# returns a tibble containing collocated assessment
# data for FRM PM2.5 January 2013 where the Monitoring Agency is
# the Alabama Department of Environmental Management (agency 0013)
## Not run: aqs_qa_flowrateverification_by_MA(parameter = "88101",
                                             bdate = as.Date("20130101",
                                                             format = "%Y%m%d"
                                                             ),
                                             edate = as.Date("20150131",
                                                             format = "%Y%m%d"
                                                             ),
                                             MA_code = "0013"
                                             )

## End(Not run)
```

aq_s_qa_flowrateverification_by_pqao

aq_s_qa_flowrateverification_by_pqao

Description

[Stable] Returns a table containing flow rate Verification data for a parameter code aggregated by matching input parameter, and Primary Quality Assurance Organization (PQAO) code provided for bdate - edate time.

Usage

```
aqs_qa_flowrateverification_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing quality assurance flow rate verification data for monitors within a pqao. An AQS_Data Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate verifications to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_pqao functions: [aqs_qa_blanks_by_pqao\(\)](#), [aqs_qa_collocated_assessments_by_pqao\(\)](#), [aqs_qa_flowrateaudit_by_pqao\(\)](#), [aqs_qa_one_point_qc_by_pqao\(\)](#), [aqs_qa_pep_audit_by_pqao\(\)](#)

Examples

```
# returns a tibble of flow rate verification
# data for January 2018 where the PQA0 is the Alabama Department
# of Environmental Management (agency 0013)
## Not run: aqs_qa_flowrateverification_by_pqao(parameter = "88101",
                                             bdate = as.Date("20170101",
                                                           format = "%Y%m%d"
                                                           ),
                                             edate = as.Date("20190131",
                                                           format = "%Y%m%d"
                                                           ),
                                             pqao_code = "0013"
                                             )

## End(Not run)
```

aqs_qa_flowrateverification_by_site

aqs_qa_flowrateverification_by_site

Description

[Stable] Returns a table containing flow rate Verification data for a parameter code aggregated matching input parameter, stateFIPS, county_code, and sitenum provided for bdate - edate time frame.

Usage

```
aqs_qa_flowrateverification_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.

edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing quality assurance flow rate verification data for monitors at a site. An AQS_Data Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate verifications to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_site functions: [aq_s_annualsummary_by_site\(\)](#), [aq_s_dailysummary_by_site\(\)](#), [aq_s_monitors_by_site\(\)](#), [aq_s_qa_blanks_by_site\(\)](#), [aq_s_qa_collocated_assessments_by_site\(\)](#), [aq_s_qa_flowrateaudit_by_site\(\)](#), [aq_s_qa_one_point_qc_by_site\(\)](#), [aq_s_qa_pep_audit_by_site\(\)](#), [aq_s_sampledata_by_site\(\)](#), [aq_s_services_by_site\(\)](#), [aq_s_transactionsample_by_site\(\)](#)

Examples

```
# returns a tibble of flow rate verification
# data for the Muscle Shoals site (#0014) in Colbert County, AL
# for January 2018:
```

```
## Not run: aqs_qa_flowrateverification_by_site(parameter = "88101",
                                             bdate = as.Date("20170101",
                                                             format = "%Y%m%d"),
                                             edate = as.Date("20180131",
                                                             format = "%Y%m%d"),
                                             stateFIPS = "01",
                                             countycode = "033",
                                             sitenum = "1002"
                                             )

## End(Not run)
```

```
aqs_qa_flowrateverification_by_state
      aqs_qa_flowrateverification_by_state
```

Description

[Stable] Returns a table containing flow rate Verification data for a parameter code aggregated matching input parameter, and stateFIPS, provided for bdate - edate time frame.

Usage

```
aqs_qa_flowrateverification_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aqs_states() for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

`return_header` If FALSE (default) only returns data requested. If TRUE returns a `AQSAPI_v2` object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an `AQS_Data Mart_APIv2 S3` object containing quality assurance flow rate verification data for monitors within a state. An `AQS_Data Mart_APIv2` is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of flow rate verifications to be retrieved at a time. This function conveniently extracts date information from the `bdate` and `edate` parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other `Aggregate_by_state` functions: `aqs_annualsummary_by_state()`, `aqs_dailysummary_by_state()`, `aqs_monitors_by_state()`, `aqs_qa_blanks_by_state()`, `aqs_qa_collocated_assessments_by_state()`, `aqs_qa_flowrateaudit_by_state()`, `aqs_qa_one_point_qc_by_state()`, `aqs_qa_pep_audit_by_state()`, `aqs_sampledata_by_state()`

Examples

```
# returns a tibble of flow rate verification
# data for Alabama 2018
## Not run: aqs_qa_flowrateverification_by_state(parameter = "88101",
                                                bdate = as.Date("20170101",
                                                                format = "%Y%m%d"
                                                                ),
                                                edate = as.Date("20190131",
                                                                format = "%Y%m%d"
                                                                ),
                                                stateFIPS = "01"
                                                )

## End(Not run)
```

```
aqs_qa_one_point_qc_by_county
      aqs_qa_one_point_qc_by_county_
```

Description

[Stable] Returns a tibble or an `AQS_Data Mart_APIv2 S3` object containing one point QC check data aggregated by `county_code`.

Usage

```

aqs_qa_one_point_qc_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing one point qc data within a county. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of one point qc data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API

calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_county functions: [aq_s_annualsummary_by_county\(\)](#), [aq_s_dailysummary_by_county\(\)](#), [aq_s_monitors_by_county\(\)](#), [aq_s_qa_blanks_by_county\(\)](#), [aq_s_qa_collocated_assessments_by_county\(\)](#), [aq_s_qa_flowrateaudit_by_county\(\)](#), [aq_s_qa_flowrateverification_by_county\(\)](#), [aq_s_qa_pep_audit_by_county\(\)](#), [aq_s_sampledata_by_county\(\)](#), [aq_s_transactionsample_by_county\(\)](#)

Examples

```
#returns a tibble of One Point QC data for ozone
# in Barnstable County, MA for January 2018
## Not run: aqs_qa_one_point_qc_by_county(parameter= "44201",
                                         bdate = as.Date("20170101",
                                                         format = "%Y%m%d"),
                                         edate = a s.Date("20180131",
                                                         format = "%Y%m%d"),
                                         stateFIPS = "25",
                                         countycode = "001"
                                         )

## End(Not run)
```

```
aqs_qa_one_point_qc_by_MA
      aqs_qa_one_point_qc_by_MA
```

Description

[Stable] Returns a tibble or an AQS_Data Mart_APIv2 S3 object containing Quality assurance data - collocated assessment raw data aggregated by monitoring agency code (_by_MA).

Usage

```
aqs_qa_one_point_qc_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing one point qc data for a single monitoring agency. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item ($\$Header$) is a tibble of header information from the AQS API and the second item ($\$Data$) is a tibble of the data returned.

Note

The AQS API only allows for a single year of one point qc data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_MA functions: [aq_s_qa_blanks_by_MA\(\)](#), [aq_s_qa_collocated_assessments_by_MA\(\)](#), [aq_s_qa_flowrateaudit_by_MA\(\)](#), [aq_s_qa_flowrateverification_by_MA\(\)](#), [aq_s_qa_pep_audit_by_MA\(\)](#)

Examples

```
# returns a tibble of ozone One Point QC data
# for January 2018 where the Monitoring Agency is the
# Massachusetts Department of Environmental Protection
# (agency 0660)
## Not run: aqs_qa_one_point_qc_by_MA(parameter = "44201",
```



```

        bdate = as.Date("20170101",
                        format = "%Y%m%d"),
        edate = as.Date("20180131",
                        format = "%Y%m%d"),
        MA_code = "0660"
    )

## End(Not run)

```

```

aqs_qa_one_point_qc_by_pqao
    aqs_qa_one_point_qc_by_pqao

```

Description

[Stable] Returns a tibble or an AQS_Data Mart_APIv2 S3 object containing Quality assurance data - collocated assessment raw data aggregated by Primary Quality Assurance Organization (PQAO) code.

Usage

```

aqs_qa_one_point_qc_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing one point qc data within a pqao. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item

Note

The AQS API only allows for a single year of one point qc data to be retrieved at a time. This function conveniently extracts date information from the `bdate` and `edate` parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_pqao functions: [aq_s_qa_blanks_by_pqao\(\)](#), [aq_s_qa_collocated_assessments_by_pqao\(\)](#), [aq_s_qa_flowrateaudit_by_pqao\(\)](#), [aq_s_qa_flowrateverification_by_pqao\(\)](#), [aq_s_qa_pep_audit_by_pqao\(\)](#)

Examples

```
# returns a tibble of ozone One Point QC
# data for Jan 2017 - January 2018 where the PQAO is the Massachusetts
# Department of Environmental Protection (agency 0660)
## Not run: aqs_qa_one_point_qc_by_pqao(parameter = "88101",
                                     bdate = as.Date("20170101",
                                                     format = "%Y%m%d"),
                                     edate = as.Date("20180131",
                                                     format = "%Y%m%d"),
                                     pqao_code = "0660"
                                     )

## End(Not run)
```

```
aqs_qa_one_point_qc_by_site
      aqs_qa_one_point_qc_by_site
```

Description

[Stable] Returns a table of one point QC raw data aggregated by parameter code, stateFIPS, countycode and site number.

Usage

```
aqs_qa_one_point_qc_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
```

```

    countycode,
    sitenum,
    cbdate = NA_Date_,
    cedate = NA_Date_,
    return_header = FALSE
  )

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing one point qc data for the requested site. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of one point qc data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other `Aggregate_by_site` functions: `aqs_annualsummary_by_site()`, `aqs_dailysummary_by_site()`, `aqs_monitors_by_site()`, `aqs_qa_blanks_by_site()`, `aqs_qa_collocated_assessments_by_site()`, `aqs_qa_flowrateaudit_by_site()`, `aqs_qa_flowrateverification_by_site()`, `aqs_qa_pep_audit_by_site()`, `aqs_sampledata_by_site()`, `aqs_services_by_site()`, `aqs_transactionsample_by_site()`

Examples

```
# returns a tibble of One Point QC data for
# ozone at the Truro National Seashore site (#0002) in
# Barnstable County, MA for January 2018:
## Not run: aqs_qa_one_point_qc_by_site_multiyear(parameter = "44201",
#                                               bdate = as.Date("20180101",
#                                                             format = "%Y%m%d"),
#                                               edate = as.Date("20180131",
#                                                             format = "%Y%m%d"),
#                                               stateFIPS = "25",
#                                               countycode = "001",
#                                               sitenum = "0002"
#                                               )

## End(Not run)
```

```
aqs_qa_one_point_qc_by_state
      aqs_qa_one_point_qc_by_state
```

Description

[Stable] Returns a tibble or an `AQS_Data Mart_APIv2 S3` object containing Quality assurance data - flow rate audit raw data aggregated by state FIPS.

Usage

```
aqs_qa_one_point_qc_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

<code>parameter</code>	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
<code>bdate</code>	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
<code>edate</code>	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.

```
aqs_qa_pep_audit_by_county
      aqs_qa_pep_audit_by_county
```

Description

[Stable] Returns a table of Performance Evaluation Program (PEP) audit data aggregated by parameter code, stateFIPS and countycode for the time frame between bdate and edate.

Usage

```
aqs_qa_pep_audit_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aqs_counties_by_state() for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object containing quality assurance PEP audit data within a county. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (\backslash \$Header) is a tibble of header information from the AQS API and the second item (\backslash \$Data) is a tibble of the data returned.

Note

The AQS API only allows for a single year of one point pep audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_county functions: [aqs_annualsummary_by_county\(\)](#), [aqs_dailysummary_by_county\(\)](#), [aqs_monitors_by_county\(\)](#), [aqs_qa_blanks_by_county\(\)](#), [aqs_qa_collocated_assessments_by_county\(\)](#), [aqs_qa_flowrateaudit_by_county\(\)](#), [aqs_qa_flowrateverification_by_county\(\)](#), [aqs_qa_one_point_qc_by_county\(\)](#), [aqs_sampledata_by_county\(\)](#), [aqs_transactionsample_by_county\(\)](#)

Examples

```
# returns a tibble with PEP Audit data for FRM
# PM2.5 in Madison County, AL for 2017
## Not run: aqs_qa_pep_audit_by_county_multiyear(parameter = "88101",
                                             bdate = as.Date("20150101",
                                                           format = "%Y%m%d"
                                                           ),
                                             edate = as.Date("20171231",
                                                           format = "%Y%m%d"
                                                           ),
                                             stateFIPS = "01",
                                             countycode = "089"
                                             )

## End(Not run)
```

aqs_qa_pep_audit_by_MA

aqs_qa_pep_audit_by_MA

Description

[Stable] Returns a table of Performance Evaluation Program (PEP) audit data aggregated by monitoring agency code ($_by_MA$) for the time frame between bdate and edate.

Usage

```
aqs_qa_pep_audit_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing quality assurance PEP audit data for a monitoring agency. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of one point pep audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_MA functions: [aq_s_qa_blanks_by_MA\(\)](#), [aq_s_qa_collocated_assessments_by_MA\(\)](#), [aq_s_qa_flowrateaudit_by_MA\(\)](#), [aq_s_qa_flowrateverification_by_MA\(\)](#), [aq_s_qa_one_point_qc_by_MA\(\)](#)

Examples

```
# returns a tibble of PEP audit data for
# June 2017 where the Monitoring Agency is the Alabama Department
# of Environmental Management (agency 0013)
## Not run: aqs_qa_pep_audit_by_MA(parameter = "88101",
                                bdate = as.Date("20170601",
                                                  format = "%Y%m%d"),
                                edate = as.Date("20170630",
                                                  format = "%Y%m%d"),
                                MA_code = "0013"
                                )

## End(Not run)
```

```
aqs_qa_pep_audit_by_pqao
      aqs_qa_pep_audit_by_pqao
```

Description

[Stable] Returns a table of Performance Evaluation Program (PEP) audit data aggregated by Primary Quality Assurance Organization (PQAO) code for the time frame between bdate and edate.

Usage

```
aqs_qa_pep_audit_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
pqao_code	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).

cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object containing quality assurance PEP audit data for a Primary Quality Assurance Organization. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item ($\$Header$) is a tibble of header information from the AQS API and the second item ($\$Data$) is a tibble of the data returned.

Note

The AQS API only allows for a single year of one point pep audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_pqao functions: [aq_s_qa_blanks_by_pqao\(\)](#), [aq_s_qa_collocated_assessments_by_pqao\(\)](#), [aq_s_qa_flowrateaudit_by_pqao\(\)](#), [aq_s_qa_flowrateverification_by_pqao\(\)](#), [aq_s_qa_one_point_qc_by_pqao\(\)](#)

Examples

```
# returns a tibble of PEP audit data for
# June 2017 where the pqao is the Alabama Department of
# Environmental Management (agency 0013)
## Not run: aqs_qa_pep_audit_by_pqao(parameter = "88101",
                                bdate = as.Date("20170601",
                                                format = "%Y%m%d"
                                                ),
                                edate = as.Date("20190630",
                                                format = "%Y%m%d"),
                                pqao_code = "0013"
                                )

## End(Not run)
```

```
aqs_qa_pep_audit_by_site
      aqs_qa_pep_audit_by_site
```

Description

[Stable] Returns a table of Performance Evaluation Program (PEP) audit data aggregated by parameter code, stateFIPS, countycode and site number for the time frame between bdate and edate.

Usage

```
aqs_qa_pep_audit_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aqs_counties_by_state() for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object containing quality assurance PEP audit data within a site. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (`\$Header`) is a tibble of header information from the AQS API and the second item (`\$Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of one point pep audit data to be retrieved at a time. This function conveniently extracts date information from the `bdate` and `edate` parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other `Aggregate_by_site` functions: [aqs_annualsummary_by_site\(\)](#), [aqs_dailysummary_by_site\(\)](#), [aqs_monitors_by_site\(\)](#), [aqs_qa_blanks_by_site\(\)](#), [aqs_qa_collocated_assessments_by_site\(\)](#), [aqs_qa_flowrateaudit_by_site\(\)](#), [aqs_qa_flowrateverification_by_site\(\)](#), [aqs_qa_one_point_qc_by_site\(\)](#), [aqs_sampledata_by_site\(\)](#), [aqs_services_by_site\(\)](#), [aqs_transactionsample_by_site\(\)](#)

Examples

```
# returns a aqs_v2 S3 object of pep Audit data for FRM PM2.5
# at the Huntsville Old Airport site (#0014) in Madison County,
# AL for 2017
## Not run: aqs_qa_pep_audit_by_site(parameter = "88101",
                                   bdate = as.Date("20150101",
                                                  format = "%Y%m%d"),
                                   edate = as.Date("20171231",
                                                  format = "%Y%m%d"),
                                   stateFIPS = "01",
                                   countycode = "089",
                                   sitenum = "0014"
                                   )

## End(Not run)
```

aqs_qa_pep_audit_by_state

aqs_qa_pep_audit_by_state

Description

[Stable] Returns a table of Performance Evaluation Program (PEP) audit data aggregated by parameter code, and stateFIPS for the time frame between `bdate` and `edate`.

Usage

```

aqs_qa_pep_audit_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object containing quality assurance PEP audit data within a state. A AQS_Data_Mart_APIv2 object is a 2 item named list in which the first item (`Header`) is a tibble of header information from the AQS API and the second item (`Data`) is a tibble of the data returned.

Note

The AQS API only allows for a single year of one point pep audit data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other `Aggregate_by_state` functions: `aq_annualsummary_by_state()`, `aq_dailysummary_by_state()`, `aq_monitors_by_state()`, `aq_qa_blanks_by_state()`, `aq_qa_collocated_assessments_by_state()`, `aq_qa_flowrateaudit_by_state()`, `aq_qa_flowrateverification_by_state()`, `aq_qa_one_point_qc_by_state()`, `aq_sampledata_by_state()`

Examples

```
# returns a tibble of PEP audit data for PM2.5 in Alabama 2017
## Not run: aq_qa_pep_audit_by_state_multiyear(parameter="88101",
                                             bdate=as.Date("20160101",
                                                           format="%Y%m%d"),
                                             edate=as.Date("20171231",
                                                           format="%Y%m%d"),
                                             stateFIPS="01"
                                             )

## End(Not run)
```

aq_removeheader

aq_removeheader

Description

[Stable] Coerces a single `AQS_Data_Mart_APIv2 S3` object or a list of `AQS_Data_Mart_APIv2 S3` objects into a single tibble object. This function decouples the `$Data` from the `AQSAPI_v2` object and returns only the `$Data` portion as a tibble. If the input is a list of `AQSAPI_v2` objects combines the `$Data` portion of each `AQS_Data_Mart_APIv2 S3` object into a single tibble with `$Header` information discarded. Else returns the input with no changes.

Usage

```
aq_removeheader(AQSobject)
```

Arguments

`AQSobject` An object of `AQSAPI_v2` or a list of `AQSAPI_v2` objects.

Value

a tibble of the combined `$data` portions of the input `AQS_Data_Mart_APIv2 S3` object with the `$Header` portion discarded.

Note

Since this function returns only the `$Data` portion of `RAQSAPI_v2` objects this means that the `$Header` information will not be present in the object being returned.

Examples

```
## Not run: AQSobject <- aq_removeheader(AQSobject)
```

```
aqs_revisionhistory  aqs_revisionhistory
```

Description

[Stable] Returns the change history to the AQS Data Mart API.

Usage

```
aqs_revisionhistory(return_header = FALSE)
```

Arguments

`return_header` If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object that is the return value from the AQS API. A AQS_Data Mart_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

Examples

```
# read the Data Mart API revision history
# \dontrun{aqs_revisionHistory()}
```

```
aqs_sampledata_by_box  aqs_sampledata_by_box
```

Description

[Stable] Returns sample data where the data is aggregated by latitude/longitude bounding box (`_by_box`). If `return_header` is FALSE (default) this function returns a single dataframe with the requested data. If `return_header` is TRUE returns a list of AQSAPI_v2 objects where each index of the list is an individual RAQSAPI_v2 object returned from each successive call to the AQS API. RAQSAPI_v2 objects are two item list where the \$Data portion contains data that contains sample air monitoring data at a site with the input parameter and `cbsa_code` provided for `bdate` - `edate` time frame. The \$Header is a tibble of header information from the API call //(useful for debugging/). This function returns NULL is `bdate` > `edate`.

Usage

```
aqs_sampledata_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
```

```

    minlon,
    maxlon,
    cbdate = NA_Date_,
    cedate = NA_Date_,
    return_header = FALSE
  )

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object which represents the minimum latitude of a geographic box. Decimal latitude with north begin positive. Only data north of this latitude will be returned.
maxlat	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north begin positive. Only data south of this latitude will be returned.
minlon	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.
maxlon	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east begin positive. Only data west of this longitude will be returned. Note that -80 is less than -70.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object containing sample data for all monitors within the input latitude/longitude bounding box for a single parameter. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item `/(Header/)` is a tibble of header information from the AQS API and the second item `/(Data/)` is a tibble of the data returned.

Note

The AQS API only allows for a single year of sampledata to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated

calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. Fortunately this operation has a linear run time (Big O notation: $O(n + 5 \text{ seconds})$).

See Also

Other Aggregate `_by_box` functions: `aq_sannualsummary_by_box()`, `aq_monitors_by_box()`

Examples

```
# returns a aqs_v2 S3 object containing all ozone samples
# in the vicinity of central Alabama for
# May 1, 2015 - May 2, 2017
## Not run: aq_sampladata_by_box(parameter = "44201",
                                bdate = as.Date("20150501",
                                                  format = "%Y%m%d"),
                                edate = as.Date("20170502",
                                                  format = "%Y%m%d"),
                                minlat = "33.3",
                                maxlat = "33.6",
                                minlon = "-87.0",
                                maxlon = "-86.7"
                                )

## End(Not run)
```

aq_sampladata_by_cbsa

aq_sampladata_by_cbsa

Description

[Stable] Returns sample data where the data is aggregated at the Core Based Statistical Area (cbsa) level. If `return_header` is `FALSE` (default) this function returns a single dataframe with the requested data. If `return_header` is `TRUE` returns a list of `AQSAPI_v2` objects where each index of the list is an individual `RAQSAPI_v2` object returned from each successive call to the AQS API. `RAQSAPI_v2` objects are two item list where the `$Data` portion contains data that contains sample air monitoring data at a site with the input parameter and `cbsa_code` provided for `bdate - edate` time frame. The `$Header` is a tibble of header information from the API call (useful for debugging/). This function returns `NULL` is `bdate > edate`.

Usage

```
aq_sampladata_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  cbdate = NA_Date_,
```

```

cedate = NA_Date_,
return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros)
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object containing sample data for all monitors matching cbsa_code for the given parameter. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item */(Header/)* is a tibble of header information from the AQS API and the second item */(Data/)* is a tibble of the data returned.

Note

The AQS API only allows for a single year of sampledata to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. Fortunately this operation has a linear run time */(Big O notation: O/(n + 5 seconds)/)*

See Also

Other Aggregate_by_cbsa functions: [aq_s_annualsummary_by_cbsa\(\)](#), [aq_s_dailysummary_by_cbsa\(\)](#), [aq_s_monitors_by_cbsa\(\)](#)

Examples

```
# returns an aqs_v2 s3 object which contains NO2 data
# for Charlotte-Concord-Gastonia, NC cbsa for
# January 1, 2015 - January 01, 2017
## Not run: aqs_sampladata_by_cbsa(parameter = "42602",
                                bdate = as.Date("20150101",
                                                format = "%Y%m%d"),
                                edate = as.Date("20170101",
                                                format = "%Y%m%d"),
                                cbsa_code = "16740"
                                )

## End(Not run)
```

aq_sampladata_by_county

aq_sampladata_by_county

Description

[Stable] Returns a single tibble with the requested data. If return_header is TRUE returns a list of AQSAPI_v2 objects where each index of the list is an individual RAQSAPI_v2 object returned from each successive call to the AQS API. RAQSAPI_v2 objects are two item list where the \$Data portion contains data that contains sample air monitoring data at a site with the input parameter, stateFIPS and county_code provided for bdate - edate time frame. The \$Header is a tibble of header information from the API call /(useful for debugging/). This function returns NULL is bdate > edate.

Usage

```
aq_sampladata_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.

stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_counties_by_state() for the list of available county codes for each state.
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object containing sample data for all monitors matching stateFIPS and county_code for the given parameter. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item */(Header/)* is a tibble of header information from the AQS API and the second item */(Data/)* is a tibble of the data returned.

Note

The AQS API only allows for a single year of sampledata to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. Fortunately this operation has a linear run time */(Big O notation: O/(n + 5 seconds)/)*.

See Also

Other Aggregate_by_county functions: [aq_annualsummary_by_county\(\)](#), [aq_dailysummary_by_county\(\)](#), [aq_monitors_by_county\(\)](#), [aq_qa_blanks_by_county\(\)](#), [aq_qa_collocated_assessments_by_county\(\)](#), [aq_qa_flowrateaudit_by_county\(\)](#), [aq_qa_flowrateverification_by_county\(\)](#), [aq_qa_one_point_qc_by_county\(\)](#), [aq_qa_pep_audit_by_county\(\)](#), [aq_transactionsample_by_county\(\)](#)

Examples

```
# returns all FRM/FEM PM2.5 data for Wake County, NC between
# January 1, 2015 - February 28, 2016
## Not run: aq_sampladata_by_county(parameter = "88101",
                                bdate = as.Date("20150101",
                                                format = "%Y%m%d"),
                                edate=as.Date("20160228",
                                                format = "%Y%m%d"),
                                stateFIPS = "37",
```

```

                                countycode = "183"
                                )

## End(Not run)

```

```

aqs_sampledata_by_site
    aqs_sampledata_by_site

```

Description

[Stable] Returns multiple years of data where sample data is aggregated at the site level. If `return_header` is `FALSE` (default) returns a single data frame with the requested data. If `return_header` is `TRUE` returns a list of `AQSAPI_v2` objects where each index of the list is an individual `RAQS-API_v2` object returned from each successive calls to the AQS API. `RAQSAPI_v2` objects are two item list where the `$Data` portion contains data that contains sample air monitoring data at a site with the input parameter, `stateFIPS` and `county_code` provided for `bdate` - `edate` time frame. The `$Header` is a tibble of header information from the API call `/`(useful for debugging/). Returns `NULL` is `bdate > edate`.

Usage

```

aqs_sampledata_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

Arguments

<code>parameter</code>	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
<code>bdate</code>	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
<code>edate</code>	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
<code>stateFIPS</code>	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
<code>countycode</code>	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
<code>sitenum</code>	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.

cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) returns a single data frame with the data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested. This is mostly useful for debugging purposes, in case the user wishes to see the header information from each api call.

Value

a tibble or an AQS_Data_Mart_APIv2 S3 object containing sample data for a single site with the input parameter. An AQS_Data_Mart_APIv2 is a 2 item named list in which the first item `/(($Header/)` is a tibble of header information from the AQS API and the second item `/(/$Data/)` is a tibble of the data returned.

Note

The AQS API only allows for a single year of sampledata to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_site functions: [aq_sannualsummary_by_site\(\)](#), [aq_sdailysummary_by_site\(\)](#), [aq_smonitors_by_site\(\)](#), [aq_sqa_blanks_by_site\(\)](#), [aq_sqa_collocated_assessments_by_site\(\)](#), [aq_sqa_flowrateaudit_by_site\(\)](#), [aq_sqa_flowrateverification_by_site\(\)](#), [aq_sqa_one_point_qc_by_site\(\)](#), [aq_sqa_pep_audit_by_site\(\)](#), [aq_services_by_site\(\)](#), [aq_transactionsample_by_site\(\)](#)

Examples

```
#Returns a AQS_Data_Mart_APIv2 S3 object of ozone monitoring
# data for the Millbrook School site (#0014) in
# Wake County, NC for June 18, 2017.
## Not run:
aq_sampladata_by_site(parameter = "44201",
                      bdate = as.Date("20170618",
                                       format = "%Y%m%d"),
                      edate = as.Date("20190618",
                                       format = "%Y%m%d"),
                      stateFIPS = "37",
                      countycode = "183",
                      sitenum = "0014"
                      )
```

```
## End(Not run)
```

```
aq_sampladata_by_state
  aq_sampladata_by_state
```

Description

[Stable] Returns sample data where the data is aggregated at the state level. If `return_header` is `FALSE` (default) this function returns a single dataframe with the requested data. If `return_header` is `TRUE` returns a list of `AQSAPI_v2` objects where each index of the list is an individual `RAQS-API_v2` object returned from each successive call to the AQS API. `RAQSAPI_v2` objects are two item list where the `$Data` portion contains data that contains sample air monitoring data at a site with the input parameter and stateFIPS provided for `bdate` - `edate` time frame. The `$Header` is a tibble of header information from the API call (useful for debugging/). This function returns `NULL` is `bdate > edate`.

Usage

```
aq_sampladata_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)
```

Arguments

<code>parameter</code>	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
<code>bdate</code>	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
<code>edate</code>	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
<code>stateFIPS</code>	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_states() for the list of available FIPS codes.
<code>cbdate</code>	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. <code>cbdate</code> is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to <code>NA_Date_</code> .
<code>cedate</code>	a R date object which represents an "end date of last change" that indicates when the data was last updated. <code>cedate</code> is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to <code>NA_Date_</code> .

`return_header` If FALSE (default) only returns data requested. If TRUE returns a `AQSAPI_v2` object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an `AQS_Data_Mart_APIv2` S3 object containing sample data for all monitors matching `stateFIPS` for the given parameter. An `AQS_Data_Mart_APIv2` is a 2 item named list in which the first item `/(($Header/)` is a tibble of header information from the AQS API and the second item `/(($Data/)` is a tibble of the data returned.

Note

The AQS API only allows for a single year of sampled data to be retrieved at a time. This function conveniently extracts date information from the `bdate` and `edate` parameters then makes repeated calls to the AQS API retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. Fortunately this operation has a linear run time `/(Big O notation: O/(n + 5 seconds/)/)`

See Also

Other `Aggregate_by_state` functions: `aqannualsummary_by_state()`, `aqdailysummary_by_state()`, `aqmonitors_by_state()`, `aqqa_blanks_by_state()`, `aqqa_collocated_assessments_by_state()`, `aqqa_flowrateaudit_by_state()`, `aqqa_flowrateverification_by_state()`, `aqqa_one_point_qc_by_state()`, `aqqa_pep_audit_by_state()`

Examples

```
# returns an aqs_v2 S3 object with all benzene samples from
# North Carolina collected from May 15th, 1995 - May 15, 1999
## Not run: aqs_sampledata_by_state(parameter = "45201",
                                bdate = as.Date("19950515",
                                                format="%Y%m%d"
                                                ),
                                edate = as.Date("19990515",
                                                format = "%Y%m%d"),
                                stateFIPS = "37"
                                )

## End(Not run)
```

`aqservices_by_box` `aqservices_by_box`

Description

a helper function that abstracts the formatting of the inputs for a call to `aq` away from the calling function for aggregations by a box formed by minimum/maximum latitude/longitude coordinates then calls the `aq` and returns the result. This helper function is not meant to be called directly from external functions.

Usage

```

aqsvservices_by_box(
  parameter,
  bdate,
  edate,
  minlat,
  maxlat,
  minlon,
  maxlon,
  service,
  cbdate = NA_Date_,
  cedate = NA_Date_
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
minlat	a R character object which represents the minimum latitude of a geographic box. Decimal latitude with north begin positive. Only data north of this latitude will be returned.
maxlat	a R character object which represents the maximum latitude of a geographic box. Decimal latitude with north begin positive. Only data south of this latitude will be returned.
minlon	a R character object which represents the minimum longitude of a geographic box. Decimal longitude with east begin positive. Only data east of this longitude will be returned.
maxlon	a R character object which represents the maximum longitude of a geographic box. Decimal longitude with east begin positive. Only data west of this longitude will be returned. Note that -80 is less than -70.
service	a string which represents the services provided by the AQS API. For a list of available services @seealso https://aqsv.eva.gov/aqsvweb/documents/data_api.html#services
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

Value

a AQS_DATAMART_APIv2 S3 object that is the return value from the AQS API. A AQS_DATAMART_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

 aq_s_services_by_cbsa aq_s_services_by_cbsa

Description

a helper function that abstracts the formatting of the inputs for a call to aq_s away from the calling function for aggregations by cbsa then calls the aq_s and returns the result. This helper function is not meant to be called directly from external functions.

Usage

```
aqs_services_by_cbsa(
  parameter,
  bdate,
  edate,
  cbsa_code,
  service,
  cbdate = NA_Date_,
  cedate = NA_Date_
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
cbsa_code	a R character object which represents the 5 digit AQS Core Based Statistical Area code (the same as the census code, with leading zeros)
service	a string which represents the services provided by the AQS API For a list of available services @seealso <a href="https://aq<sub>s</sub>.epa.gov/aq<sub>s</sub>web/documents/data_api.html#services">https://aq_s.epa.gov/aq_sweb/documents/data_api.html#services
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

Value

a AQS_DATAMART_APIv2 S3 object that is the return value from the AQS API. A AQS_DATAMART_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

```
aqs_services_by_county
      aqs_services_by_county
```

Description

a helper function that abstracts the formatting of the inputs for a call to aq_s away from the calling function for aggregations by county then calls the aq_s and returns the result. This helper function is not meant to be called directly from external functions.

Usage

```
aqs_services_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  service,
  cbdate = NA_Date_,
  cedate = NA_Date_
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
service	a string which represents the services provided by the AQS API For a list of available services @seealso <a href="https://aq<sub>s</sub>.epa.gov/aq<sub>s</sub>web/documents/data_
api.html#services">https://aq_s.epa.gov/aq_sweb/documents/data_ api.html#services
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

Value

a `AQS_DATAMART_APIv2` S3 object that is the return value from the AQS API. A `AQS_DATAMART_APIv2` is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

<code>aqservices_by_MA</code>	<code>aqservices_by_MA</code>
-------------------------------	-------------------------------

Description

a helper function that abstracts the formatting of the inputs for a call to `aqservices` away from the calling function for aggregations by Monitoring Agency (MA) then calls the `aqservices` and returns the result. This helper function is not meant to be called directly from external functions.

Usage

```
aqservices_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  service,
  cbdate = NA_Date_,
  cedate = NA_Date_
)
```

Arguments

<code>parameter</code>	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
<code>bdate</code>	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
<code>edate</code>	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
<code>MA_code</code>	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
<code>service</code>	a string which represents the services provided by the AQS API For a list of available services @seealso https://aqservices.epa.gov/aqservicesweb/documents/data_api.html#services
<code>cbdate</code>	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. <code>cbdate</code> is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to <code>NA_Date_</code> .
<code>cedate</code>	a R date object which represents an "end date of last change" that indicates when the data was last updated. <code>cedate</code> is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to <code>NA_Date_</code> .

Value

a `AQS_DATAMART_APIv2` S3 object that is the return value from the AQS API. A `AQS_DATAMART_APIv2` is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

`aqs_services_by_pqao` *aq_s_services_by_pqao*

Description

a helper function that abstracts the formatting of the inputs for a call to `aqs` away from the calling function for aggregations by Primary Quality Assurance Organization (pqao) then calls the `aqs` and returns the result. This helper function is not meant to be called directly from external functions.

Usage

```
aqs_services_by_pqao(
  parameter,
  bdate,
  edate,
  pqao_code,
  service,
  cbdate = NA_Date_,
  cedate = NA_Date_
)
```

Arguments

<code>parameter</code>	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
<code>bdate</code>	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
<code>edate</code>	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
<code>pqao_code</code>	a R character object which represents the 4 digit AQS Primary Quality Assurance Organization code (with leading zeroes).
<code>service</code>	a string which represents the services provided by the AQS API. For a list of available services @seealso <a href="https://aq<sub>s</sub>.epa.gov/aq<sub>s</sub>web/documents/data_
api.html#services">https://aq_s.epa.gov/aq_sweb/documents/data_ api.html#services
<code>cbdate</code>	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. <code>cbdate</code> is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to <code>NA_Date_</code> .
<code>cedate</code>	a R date object which represents an "end date of last change" that indicates when the data was last updated. <code>cedate</code> is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to <code>NA_Date_</code> .

Value

a `AQS_DATAMART_APIv2` S3 object that is the return value from the AQS API. A `AQS_DATAMART_APIv2` is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

`aqs_services_by_site` *aq_s_services_by_site*

Description

a helper function that abstracts the formatting of the inputs for a call to `aqs` away from the calling function for aggregations by site then calls the `aqs` and returns the result. This helper function is not meant to be called directly from external functions.

Usage

```
aqs_services_by_site(  
  parameter,  
  bdate,  
  edate,  
  stateFIPS,  
  countycode,  
  sitenum,  
  service,  
  cdate = NA_Date_,  
  edate = NA_Date_  
)
```

Arguments

<code>parameter</code>	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
<code>bdate</code>	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
<code>edate</code>	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
<code>stateFIPS</code>	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
<code>countycode</code>	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
<code>sitenum</code>	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
<code>service</code>	a string which represents the services provided by the AQS API. For a list of available services @seealso <a href="https://aq<sub>s</sub>.epa.gov/aq<sub>s</sub>web/documents/data_apis.html#services">https://aq_s.epa.gov/aq_sweb/documents/data_apis.html#services

cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

Value

a AQS_DATAMART_APIv2 S3 object that is the return value from the AQS API. A AQS_DATAMART_APIv2 is a 2 item named list in which the first item (\$Header) is a tibble of header information from the AQS API and the second item (\$Data) is a tibble of the data returned.

See Also

Other Aggregate_by_site functions: [aq_s_annualsummary_by_site\(\)](#), [aq_s_dailysummary_by_site\(\)](#), [aq_s_monitors_by_site\(\)](#), [aq_s_qa_blanks_by_site\(\)](#), [aq_s_qa_collocated_assessments_by_site\(\)](#), [aq_s_qa_flowrateaudit_by_site\(\)](#), [aq_s_qa_flowrateverification_by_site\(\)](#), [aq_s_qa_one_point_qc_by_site\(\)](#), [aq_s_qa_pep_audit_by_site\(\)](#), [aq_s_sampledata_by_site\(\)](#), [aq_s_transactionsample_by_site\(\)](#)

aq_s_services_by_state *aq_s_services_by_state*

Description

a helper function that abstracts the formatting of the inputs for a call to aq_s away from the calling function for aggregations by State then calls the aq_s and returns the result. This helper function is not meant to be called directly from external functions.

Usage

```
aqs_services_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  service,
  cbdate = NA_Date_,
  cedate = NA_Date_
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.

stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aqstates() for the list of available FIPS codes.
service	a string which represents the services provided by the AQS API. For a list of available services @seealso https://aqsepa.gov/aqsweb/documents/data_api.html#services
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.

Value

a `AQS_DATAMART_APIv2 S3` object that is the return value from the AQS API. A `AQS_DATAMART_APIv2` is a 2 item named list in which the first item (`$Header`) is a tibble of header information from the AQS API and the second item (`$Data`) is a tibble of the data returned.

aqsign_up	<i>aqsign_up</i>
-----------	------------------

Description

[Stable] Use this service to register as a new user or to reset an existing user's key. A verification email will be sent to the email account specified. To reset a password: If the request is made with an email that is already registered, a new key will be issued for that account and emailed to the listed address. Usage is the same in either case. Refer to the email message for further instructions before continuing.

Usage

```
aqsign_up(email)
```

Arguments

email	a R character object which represents the email account that will be used to register with the AQS API or change an existing user's key. A verification email will be sent to the account specified. Follow the instructions in the verification e-mail before proceeding to use any other functionality of the AQS API. Register your credential with the @3 aqcredentials() before using the other functions in this library.
-------	---

Value

None

Note

The '@' character needs to be escaped with the '/' character.

aq _s _states	<i>aq_s_states</i>
-------------------------	------------------------------

Description

[Stable] Returns a table of US states, US territories, and the district of Columbia with their respective FIPS codes used for constructing other requests

Usage

```
aqs_states(return_header = FALSE)
```

Arguments

`return_header` If FALSE (default) only returns data requested. If TRUE returns an AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object of states and their FIPS codes used for constructing other requests.

Examples

```
#returns a tibble of states and their FIPS codes
## Not run: aqs_states()
```

aq _s _transaction _{sample} _by_ _{county}	<i>aq_s_transaction_{sample}_by__{county}</i>
---	---

Description

[Stable] Returns transaction_{sample} data - aggregated by county in the AQS Submission Transaction Format (RD) sample (raw) data for a parameter code aggregated by matching input parameter, stateFIPS and countycode provided for bdate - edate time frame. Includes data both in submitted and standard units

Usage

```
aqs_transactionsample_by_county(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aq_s_counties_by_state() for the list of available county codes for each state.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object of transaction sample (raw) data in the AQS submission transaction format (RD) corresponding to the inputs provided.

Note

The AQS API only allows for a single year of transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_county functions: [aq_s_annualsummary_by_county\(\)](#), [aq_s_dailysummary_by_county\(\)](#), [aq_s_monitors_by_county\(\)](#), [aq_s_qa_blanks_by_county\(\)](#), [aq_s_qa_collocated_assessments_by_county\(\)](#), [aq_s_qa_flowrateaudit_by_county\(\)](#), [aq_s_qa_flowrateverification_by_county\(\)](#), [aq_s_qa_one_point_qc_by_county\(\)](#), [aq_s_qa_pep_audit_by_county\(\)](#), [aq_s_sampledata_by_county\(\)](#)

Examples

```
#Returns a AQS_Data Mart_APIv2 S3 object of the returns
## Not run: # returns all FRM/FEM transaction data for
# Wake County, NC between January and February 2016
aqs_transactionsample_by_county(parameter = "88101",
                                bdate = as.Date("20160228",
                                                  format = "%Y%m%d"),
                                edate = as.Date("20160228",
                                                  format = "%Y%m%d"),
                                stateFIPS = "37",
                                countycode = "183")
```

```

)

## End(Not run)

```

```

aq_transactionsample_by_MA
  aq_transactionsample_MA

```

Description

[Stable] Returns transactionsample data - aggregated by Monitoring agency (MA) in the AQS Submission Transaction Format (RD) sample (raw) data for a parameter code aggregated by matching input parameter, and monitoring agency (MA) code provided for bdate - edate time frame. Includes data both in submitted and standard units

Usage

```

aq_transactionsample_by_MA(
  parameter,
  bdate,
  edate,
  MA_code,
  cbdate = NA_Date_,
  cedate = NA_Date_,
  return_header = FALSE
)

```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
MA_code	a R character object which represents the 4 digit AQS Monitoring Agency code (with leading zeroes).
cbdate	a R date object which represents a "beginning date of last change" that indicates when the data was last updated. cbdate is used to filter data based on the change date. Only data that changed on or after this date will be returned. This is an optional variable which defaults to NA_Date_.
cedate	a R date object which represents an "end date of last change" that indicates when the data was last updated. cedate is used to filter data based on the change date. Only data that changed on or before this date will be returned. This is an optional variable which defaults to NA_Date_.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object of transaction sample (raw) data in the AQS submission transaction format (RD) corresponding to the inputs provided.

Note

The AQS API only allows for a single year of transaction data to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQS API retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate `_by_state` functions: [aq_transactionsample_by_state\(\)](#)

Examples

```
#Returns a AQS_Data Mart_APIv2 S3 object of
## Not run: # all ozone transaction sample data for all monitors
# operated by South Coast Air Quality Management
# District collected on May 15, 2015
# North Carolina on May 15, 1995
aq_transactionsample_by_MA(parameter = "44201",
                           bdate = as.Date("20150515",
                                             format = "%Y%m%d"),
                           edate = as.Date("20150515",
                                             format = "%Y%m%d"),
                           MA_code = "0972"
                           )

## End(Not run)
```

aq_transactionsample_by_site

aq_transactionsample_by_site

Description

[Stable] Returns transactionsample data - aggregated by site in the AQS Submission Transaction Format (RD) sample (raw) data for a parameter code aggregated by matching input parameter, sitenum, countycode and stateFIPS provided for bdate - edate time frame. Includes data both in submitted and standard units

Usage

```
aqs_transactionsample_by_site(
  parameter,
  bdate,
  edate,
  stateFIPS,
  countycode,
  sitenum,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aqs_states() for the list of available FIPS codes.
countycode	a R character object which represents the 3 digit state FIPS code for the county being requested (with leading zero(s)). @seealso aqs_counties_by_state() for the list of available county codes for each state.
sitenum	a R character object which represents the 4 digit site number (with leading zeros) within the county and state being requested.
return_header	If FALSE (default) only returns data requested. If TRUE returns a AQSAPI_v2 object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an AQS_Data Mart_APIv2 S3 object of transaction sample (raw) data in the AQS submission transaction format (RD) corresponding to the inputs provided.

Note

The AQS API only allows for a single year of transactiondata to be retrieved at a time. This function conveniently extracts date information from the bdate and edate parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate_by_site functions: [aqs_annualsummary_by_site\(\)](#), [aqs_dailysummary_by_site\(\)](#), [aqs_monitors_by_site\(\)](#), [aqs_qa_blanks_by_site\(\)](#), [aqs_qa_collocated_assessments_by_site\(\)](#),

[aq_s_qa_flowrateaudit_by_site\(\)](#), [aq_s_qa_flowrateverification_by_site\(\)](#), [aq_s_qa_one_point_qc_by_site\(\)](#), [aq_s_qa_pep_audit_by_site\(\)](#), [aq_s_sampledata_by_site\(\)](#), [aq_s_services_by_site\(\)](#)

Examples

```
#Returns a AQS_Data Mart_APIv2 S3 object of the returns
## Not run: # returns all ozone transaction data for the
# Millbrook School site (#0014) in Wake County, NC for
# June 18, 2017
aqs_transactionsample_by_site(parameter = "44201",
                              bdate = as.Date("20170618",
                                                format = "%Y%m%d"),
                              edate = as.Date("20170618",
                                                format = "%Y%m%d"),
                              stateFIPS = "37",
                              countycode = "183",
                              sitemum = "0014"
                              )

## End(Not run)
```

aq_s_transactionsample_by_state

aq_s_transactionsample_by_state

Description

[Stable] Returns transactionsample data - aggregated by state in the AQS Submission Transaction Format (RD) sample (raw) data for a parameter code aggregated by matching input parameter, and stateFIPS provided for bdate - edate time frame. Includes data both in submitted and standard units

Usage

```
aqs_transactionsample_by_state(
  parameter,
  bdate,
  edate,
  stateFIPS,
  return_header = FALSE
)
```

Arguments

parameter	a character list or a single character string which represents the parameter code of the air pollutant related to the data being requested.
bdate	a R date object which represents that begin date of the data selection. Only data on or after this date will be returned.
edate	a R date object which represents that end date of the data selection. Only data on or before this date will be returned.
stateFIPS	a R character object which represents the 2 digit state FIPS code (with leading zero) for the state being requested. @seealso aq_s_states() for the list of available FIPS codes.

`return_header` If FALSE (default) only returns data requested. If TRUE returns a `AQSAPI_v2` object which is a two item list that contains header information returned from the API server mostly used for debugging purposes in addition to the data requested.

Value

a tibble or an `AQS_Data Mart_APIv2 S3` object of transaction sample (raw) data in the AQS submission transaction format (RD) corresponding to the inputs provided.

Note

The AQS API only allows for a single year of transaction data to be retrieved at a time. This function conveniently extracts date information from the `bdate` and `edate` parameters then makes repeated calls to the AQSAPI retrieving a maximum of one calendar year of data at a time. Each calendar year of data requires a separate API call so multiple years of data will require multiple API calls. As the number of years of data being requested increases so does the length of time that it will take to retrieve results. There is also a 5 second wait time inserted between successive API calls to prevent overloading the API server. This operation has a linear run time of $O(n + 5 \text{ seconds})$.

See Also

Other Aggregate `_by_state` functions: [aq_transactionsample_by_MA\(\)](#)

Examples

```
#Returns a AQS_Data Mart_APIv2 S3 object of
## Not run: # all benzene transaction sample data for
# North Carolina on May 15, 1995
aq_transactionsample_by_state(parameter = "45201",
                              bdate = as.Date("19950515",
                                                format = "%Y%m%d"),
                              edate = as.Date("19950515",
                                                format = "%Y%m%d"),
                              stateFIPS = "37"
                              )

## End(Not run)
```

RAQSAPI

RAQSAPI: A R Interface to The United States Environmental Protection Agency's Air Quality System Data Mart RESTful API server.

Description

RAQSAPI is a package for R that connects the R programming environment to the United State's Environmental protection agency's Air Quality System (AQS) Data Mart API for retrieval of air monitoring data.

There are two things that you must do before using this package.

1. If you have not done so yet register your username with Data Mart
2. Every time this library is reloaded `AQS_API_credentials()` function must be called before continuing.

please use vignette(RAQSAPI) for more details about this package.

EPA Disclaimer: This software/application was developed by the U.S. Environmental Protection Agency (USEPA). No warranty expressed or implied is made regarding the accuracy or utility of the system, nor shall the act of distribution constitute any such warranty. The USEPA has relinquished control of the information and no longer has responsibility to protect the integrity, confidentiality or availability of the information. Any reference to specific commercial products, processes, or services by service mark, trademark, manufacturer, or otherwise, does not constitute or imply their endorsement, recommendation or favoring by the USEPA. The USEPA seal and logo shall not be used in any manner to imply endorsement of any commercial product or activity by the USEPA or the United States Government.

Index

- * **Aggregate_by_MA functions**
 - aqs_qa_blanks_by_MA, [37](#)
 - aqs_qa_collocated_assessments_by_MA, [46](#)
 - aqs_qa_flowrateaudit_by_MA, [54](#)
 - aqs_qa_flowrateverification_by_MA, [63](#)
 - aqs_qa_one_point_qc_by_MA, [71](#)
 - aqs_qa_pep_audit_by_MA, [79](#)
- * **Aggregate_by_box functions**
 - aqs_annualsummary_by_box, [4](#)
 - aqs_monitors_by_box, [27](#)
 - aqs_sampledata_by_box, [87](#)
- * **Aggregate_by_cbsa functions**
 - aqs_annualsummary_by_cbsa, [6](#)
 - aqs_dailysummary_by_cbsa, [17](#)
 - aqs_monitors_by_cbsa, [28](#)
 - aqs_sampledata_by_cbsa, [89](#)
- * **Aggregate_by_county functions**
 - aqs_annualsummary_by_county, [7](#)
 - aqs_dailysummary_by_county, [19](#)
 - aqs_monitors_by_county, [30](#)
 - aqs_qa_blanks_by_county, [36](#)
 - aqs_qa_collocated_assessments_by_county, [44](#)
 - aqs_qa_flowrateaudit_by_county, [53](#)
 - aqs_qa_flowrateverification_by_county, [61](#)
 - aqs_qa_one_point_qc_by_county, [69](#)
 - aqs_qa_pep_audit_by_county, [78](#)
 - aqs_sampledata_by_county, [91](#)
 - aqs_transactionsample_by_county, [106](#)
- * **Aggregate_by_pqao functions**
 - aqs_qa_blanks_by_pqao, [39](#)
 - aqs_qa_collocated_assessments_by_pqao, [47](#)
 - aqs_qa_flowrateaudit_by_pqao, [56](#)
 - aqs_qa_flowrateverification_by_pqao, [64](#)
 - aqs_qa_one_point_qc_by_pqao, [73](#)
 - aqs_qa_pep_audit_by_pqao, [81](#)
- * **Aggregate_by_site functions**
 - aqs_annualsummary_by_site, [9](#)
 - aqs_dailysummary_by_site, [21](#)
 - aqs_monitors_by_site, [31](#)
 - aqs_qa_blanks_by_site, [41](#)
 - aqs_qa_collocated_assessments_by_site, [49](#)
 - aqs_qa_flowrateaudit_by_site, [58](#)
 - aqs_qa_flowrateverification_by_site, [66](#)
 - aqs_qa_one_point_qc_by_site, [74](#)
 - aqs_qa_pep_audit_by_site, [83](#)
 - aqs_sampledata_by_site, [93](#)
 - aqs_services_by_site, [102](#)
 - aqs_transactionsample_by_site, [109](#)
- * **Aggregate_by_state functions**
 - aqs_transactionsample_by_MA, [108](#)
 - aqs_transactionsample_by_state, [111](#)
- * **Aggregate_by_box functions**
 - aqs_dailysummary_by_box, [15](#)
- * **Aggregate_by_state functions**
 - aqs_annualsummary_by_state, [11](#)
 - aqs_dailysummary_by_state, [22](#)
 - aqs_monitors_by_state, [33](#)
 - aqs_qa_blanks_by_state, [42](#)
 - aqs_qa_collocated_assessments_by_state, [51](#)
 - aqs_qa_flowrateaudit_by_state, [59](#)
 - aqs_qa_flowrateverification_by_state, [68](#)
 - aqs_qa_one_point_qc_by_state, [76](#)
 - aqs_qa_pep_audit_by_state, [84](#)
 - aqs_sampledata_by_state, [95](#)
- aqs_annualsummary_by_box, [4, 28, 89](#)
- aqs_annualsummary_by_cbsa, [6, 18, 29, 90](#)
- aqs_annualsummary_by_county, [7, 20, 31, 37, 45, 54, 62, 71, 79, 92, 107](#)
- aqs_annualsummary_by_site, [9, 22, 32, 42, 50, 59, 67, 76, 84, 94, 103, 110](#)
- aqs_annualsummary_by_state, [11, 24, 34, 44, 52, 61, 69, 77, 86, 96](#)
- aqs_cbsas, [13](#)
- aqs_classes, [13](#)

- aqs_classes(), 35
- aqs_counties_by_state, 14
- aqs_counties_by_state(), 8, 10, 19, 21, 30, 32, 36, 41, 45, 50, 53, 58, 62, 67, 70, 75, 78, 83, 92, 93, 99, 102, 105, 107, 110
- aqs_credentials, 15
- aqs_credentials(), 104
- aqs_dailysummary_by_box, 15
- aqs_dailysummary_by_cbsa, 7, 17, 29, 90
- aqs_dailysummary_by_county, 9, 19, 31, 37, 45, 54, 62, 71, 79, 92, 107
- aqs_dailysummary_by_site, 10, 21, 32, 42, 50, 59, 67, 76, 84, 94, 103, 110
- aqs_dailysummary_by_state, 12, 22, 34, 44, 52, 61, 69, 77, 86, 96
- aqs_fields_by_service, 24
- aqs_isavailable, 25
- aqs_knownissues, 25
- aqs_mas, 26
- aqs_monitors_by_box, 5, 27, 89
- aqs_monitors_by_cbsa, 7, 18, 28, 90
- aqs_monitors_by_county, 9, 20, 30, 37, 45, 54, 62, 71, 79, 92, 107
- aqs_monitors_by_site, 10, 22, 31, 42, 50, 59, 67, 76, 84, 94, 103, 110
- aqs_monitors_by_state, 12, 24, 33, 44, 52, 61, 69, 77, 86, 96
- aqs_parameters_by_class, 34
- aqs_pqaos, 35
- aqs_qa_blanks_by_county, 9, 20, 31, 36, 45, 54, 62, 71, 79, 92, 107
- aqs_qa_blanks_by_MA, 37, 47, 56, 64, 72, 81
- aqs_qa_blanks_by_pqao, 39, 49, 57, 66, 74, 82
- aqs_qa_blanks_by_site, 10, 22, 32, 41, 50, 59, 67, 76, 84, 94, 103, 110
- aqs_qa_blanks_by_state, 12, 24, 34, 42, 52, 61, 69, 77, 86, 96
- aqs_qa_collocated_assessments_by_county, 9, 20, 31, 37, 44, 54, 62, 71, 79, 92, 107
- aqs_qa_collocated_assessments_by_MA, 39, 46, 56, 64, 72, 81
- aqs_qa_collocated_assessments_by_pqao, 40, 47, 57, 66, 74, 82
- aqs_qa_collocated_assessments_by_site, 10, 22, 32, 42, 49, 59, 67, 76, 84, 94, 103, 110
- aqs_qa_collocated_assessments_by_state, 12, 24, 34, 44, 51, 61, 69, 77, 86, 96
- aqs_qa_flowrateaudit_by_county, 9, 20, 31, 37, 45, 53, 62, 71, 79, 92, 107
- aqs_qa_flowrateaudit_by_MA, 39, 47, 54, 64, 72, 81
- aqs_qa_flowrateaudit_by_pqao, 40, 49, 56, 66, 74, 82
- aqs_qa_flowrateaudit_by_site, 10, 22, 32, 42, 50, 58, 67, 76, 84, 94, 103, 111
- aqs_qa_flowrateaudit_by_state, 12, 24, 34, 44, 52, 59, 69, 77, 86, 96
- aqs_qa_flowrateverification_by_county, 9, 20, 31, 37, 45, 54, 61, 71, 79, 92, 107
- aqs_qa_flowrateverification_by_MA, 39, 47, 56, 63, 72, 81
- aqs_qa_flowrateverification_by_pqao, 40, 49, 57, 64, 74, 82
- aqs_qa_flowrateverification_by_site, 11, 22, 32, 42, 50, 59, 66, 76, 84, 94, 103, 111
- aqs_qa_flowrateverification_by_state, 12, 24, 34, 44, 52, 61, 68, 77, 86, 96
- aqs_qa_one_point_qc_by_county, 9, 20, 31, 37, 45, 54, 62, 69, 79, 92, 107
- aqs_qa_one_point_qc_by_MA, 39, 47, 56, 64, 71, 81
- aqs_qa_one_point_qc_by_pqao, 40, 49, 57, 66, 73, 82
- aqs_qa_one_point_qc_by_site, 11, 22, 32, 42, 50, 59, 67, 74, 84, 94, 103, 111
- aqs_qa_one_point_qc_by_state, 12, 24, 34, 44, 52, 61, 69, 76, 86, 96
- aqs_qa_pep_audit_by_county, 9, 20, 31, 37, 45, 54, 62, 71, 78, 92, 107
- aqs_qa_pep_audit_by_MA, 39, 47, 56, 64, 72, 79
- aqs_qa_pep_audit_by_pqao, 40, 49, 57, 66, 74, 81
- aqs_qa_pep_audit_by_site, 11, 22, 32, 42, 50, 59, 67, 76, 83, 94, 103, 111
- aqs_qa_pep_audit_by_state, 12, 24, 34, 44, 52, 61, 69, 77, 84, 96
- aqs_removeheader, 86
- aqs_revisionhistory, 87
- aqs_sampledata_by_box, 5, 28, 87
- aqs_sampledata_by_cbsa, 7, 18, 29, 89
- aqs_sampledata_by_county, 9, 20, 31, 37, 45, 54, 62, 71, 79, 91, 107
- aqs_sampledata_by_site, 11, 22, 32, 42, 50, 59, 67, 76, 84, 93, 103, 111
- aqs_sampledata_by_state, 12, 24, 34, 44, 52, 61, 69, 77, 86, 95
- aqs_services_by_box, 96

aqservices_by_cbsa, 98
aqservices_by_county, 99
aqservices_by_MA, 100
aqservices_by_pqao, 101
aqservices_by_site, 11, 22, 32, 42, 50,
59, 67, 76, 84, 94, 102, 111
aqservices_by_state, 103
aqsign_up, 104
aqsign_up(), 15
aqsites_by_county, 105
aqstates, 106
aqstates(), 8, 10, 12, 14, 19, 21, 23, 30,
32, 33, 36, 41, 43, 45, 50, 51, 53, 58,
60, 62, 67, 68, 70, 75, 77, 78, 83, 85,
92, 93, 95, 99, 102, 104, 105, 107,
110, 111
aqtransactionssample_by_county, 9, 20,
31, 37, 45, 54, 62, 71, 79, 92, 106
aqtransactionssample_by_MA, 108, 112
aqtransactionssample_by_site, 11, 22,
32, 42, 50, 59, 67, 76, 84, 94, 103,
109
aqtransactionssample_by_state, 109,
111
RAQSAPI, 112