

# Package ‘ROCKET’

February 17, 2021

**Type** Package

**Title** Simple and Fast ROC Curves

**Version** 1.0.1

**Description** A set of functions for receiver operating characteristic (ROC) curve estimation and area under the curve (AUC) calculation.

All functions are designed to work with aggregated data; nevertheless, they can also handle raw samples.

In 'ROCKET', we distinguish two types of ROC curve representations:

- 1) parametric curves - the true positive rate (TPR) and the false positive rate (FPR) are functions of a parameter (the score),
- 2) functions - TPR is a function of FPR.

There are several ROC curve estimation methods available. An introduction to the mathematical background of the implemented methods (and much more) can be found in de Zea Bermudez, Gonçalves, Oliveira & Subtil (2014) <<https://www.ine.pt/revstat/pdf/rs140101.pdf>> and Cai & Pepe (2004) <[doi:10.1111/j.0006-341X.2004.00200.x](https://doi.org/10.1111/j.0006-341X.2004.00200.x)>.

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**URL** <https://github.com/da-zar/ROCKET>

**BugReports** <https://github.com/da-zar/ROCKET/issues>

**Imports** data.table (>= 1.13.0)

**Suggests** testthat

**RoxygenNote** 7.1.1

**Collate** 'ROCKET.R' 'generics.R' 'auc.R' 'rkt\_ecdf.R' 'rkt\_prep.R' 'rkt\_roc.R' 'roc\_methods.R' 'utils.R' 'zzz.R'

**NeedsCompilation** no

**Author** Daniel Lazar [aut, cre]

**Maintainer** Daniel Lazar <[da-zar@gmx.net](mailto:da-zar@gmx.net)>

**Repository** CRAN

**Date/Publication** 2021-02-17 09:10:07 UTC

## R topics documented:

auc . . . . .	2
rkt_ecdf . . . . .	3
rkt_prep . . . . .	4
rkt_roc . . . . .	5
show_methods . . . . .	6
variance . . . . .	6

<b>Index</b>	<b>7</b>
--------------	----------

---

auc	<i>Calculate the AUC</i>
-----	--------------------------

---

### Description

Calculate the AUC

### Usage

```
auc(x, ...)

## S3 method for class '`function`'
auc(x, ...)

## S3 method for class 'curve'
auc(x, lower, upper, n = 10000, ...)

## S3 method for class 'rkt_roc'
auc(x, exact = TRUE, ...)
```

### Arguments

x	An R object.
...	Further parameters.
lower, upper	The limits of integration.
n	The number of integration points.
exact	Logical. If the exact formula should be used for calculating the AUC instead of numerical approximation.

### Value

The area under the curve as a numeric value.

---

`rkt_ecdf`*Empirical estimate of the CDF*

---

## Description

Calculate an empirical cumulative distribution function based on a sample `x` and optionally a vector `w` of weights.

## Usage

```
rkt_ecdf(x, w)

## S3 method for class 'rkt_ecdf'
print(x, ...)

## S3 method for class 'rkt_ecdf'
mean(x, ...)

## S3 method for class 'rkt_ecdf'
variance(x, ...)

## S3 method for class 'rkt_ecdf'
plot(x, ...)
```

## Arguments

<code>x</code>	Numeric vector containing the sample. Alternatively, if <code>w</code> is supplied, distinct values within the sample. For S3 methods, a function of class <code>rkt_ecdf</code> .
<code>w</code>	Optional. Numeric vector containing the weights of each value in <code>x</code> .
<code>...</code>	Further parameters.

## Details

The weights vector `w` can contain the counts of each distinct value in `x`, this is the most natural use case. In general the weights are describing the jumps of the final ecdf. Normalization is handled internally.

If `x` contains duplicates, corresponding values in `w` will be summed up. Only positive weights are allowed. Elements in `x` with non-positive weights will be ignored.

## Value

A function of class `rkt_ecdf`.

**Examples**

```
require(ROCKET)

plot(rkt_ecdf(rnorm(100)))
plot(rkt_ecdf(c(0, 1)))
plot(rkt_ecdf(c(0, 1), c(1, 10)))
```

---

rkt_prep	<i>ROC points</i>
----------	-------------------

---

**Description**

Calculate the ROC points for all meaningful cutoff values based on predicted scores.

**Usage**

```
rkt_prep(scores, positives, negatives = totals - positives, totals = 1)

## S3 method for class 'rkt_prep'
print(x, ...)

## S3 method for class 'rkt_prep'
plot(x, ...)
```

**Arguments**

scores	Numeric vector containing the predicted scores.
positives	Numeric vector of the same length as scores. The number of positive entities associated with each score. If data is not aggregated, a vector of 0's and 1's.
negatives	Similar to positives. Defaults to totals - positives.
totals	How many times each score was predicted. Defaults to 1 (assuming data is not aggregated). If any value in positives is greater than 1 (aggregated data), totals must be a vector. Not needed if negatives is supplied.
x	An environment of class rkt_prep for S3 methods.
...	Further parameters.

**Details**

In a situation where many of the predicted scores have the same value it might be easier and faster to use aggregated data.

**Value**

An environment of class rkt\_prep.

**Examples**

```
require(ROCKET)

plot(rkt_prep(1:4, c(0, 1, 0, 1)))
plot(rkt_prep(1:4, c(0, 1000, 0, 1000), totals = 1000))
plot(rkt_prep(1:4, c(100, 200, 300, 400), totals = c(1000, 800, 600, 400)))
```

rkt\_roc

*Empirical estimate of the ROC***Description**

Calculate the empirical estimate of the ROC from raw sample or aggregated data.

**Usage**

```
rkt_roc(prepare, method = 1)

## S3 method for class 'rkt_roc'
print(x, ...)

## S3 method for class 'rkt_roc'
plot(x, ...)
```

**Arguments**

prepare	A rkt_prep object.
method	A number specifying the type of ROC estimate. Possible values can be viewed with <code>show_methods()</code> .
x	An object of class rkt_roc.
...	Further parameters passed to <code>plot</code> and <code>lines</code>

**Value**

An object of class rkt\_roc, i.e. a function or a list of two functions (for method = 1).

**Examples**

```
require(ROCKET)

scores <- c(1, 2, 3, 4)
positives <- c(0, 1, 0, 1)
prep <- rkt_prep(scores, positives)

roc1 <- rkt_roc(prepare, method = 1)
roc2 <- rkt_roc(prepare, method = 2)
roc3 <- rkt_roc(prepare, method = 3)
```

```
plot(roc1)
plot(roc2)
plot(roc3)
```

---

show_methods	<i>Available ROC estimation methods</i>
--------------	---

---

### Description

Show the implemented ROC estimation methods.

### Usage

```
show_methods()
```

### Value

A [data table](#) containing the number and a short description of each implemented method.

---

variance	<i>Sample Variance</i>
----------	------------------------

---

### Description

Sample Variance

### Usage

```
variance(x, ...)
```

```
## Default S3 method:
```

```
variance(x, ...)
```

### Arguments

x	An R object.
...	Further parameters.

### Value

The (biased) sample variance as a numeric value.

### See Also

[variance.rkt\\_ecdf](#), [var](#)

# Index

`auc`, 2

`data.table`, 6

`lines`, 5

`mean.rkt_ecdf (rkt_ecdf)`, 3

`plot`, 5

`plot.rkt_ecdf (rkt_ecdf)`, 3

`plot.rkt_prep (rkt_prep)`, 4

`plot.rkt_roc (rkt_roc)`, 5

`print.rkt_ecdf (rkt_ecdf)`, 3

`print.rkt_prep (rkt_prep)`, 4

`print.rkt_roc (rkt_roc)`, 5

`rkt_ecdf`, 3

`rkt_prep`, 4

`rkt_roc`, 5

`show_methods`, 6

`var`, 6

`variance`, 6

`variance.rkt_ecdf`, 6

`variance.rkt_ecdf (rkt_ecdf)`, 3