

Package ‘VicmapR’

July 26, 2021

Title Access Victorian Spatial Data Through Web File Services (WFS)

Version 0.1.7

Description Easily interfaces R to spatial datasets available through the Victorian Government's WFS (Web Feature Service): https://services.land.vic.gov.au/catalogue/publicproxy/guest/dv_geoserver/wfs?request=getCapabilities, which allows users to read in 'sf' data from these sources. VicmapR uses the lazy querying approach and code developed by Teucher et al. (2021) for the 'bdata' R package [doi:10.21105/joss.02927](https://doi.org/10.21105/joss.02927).

License Apache License (== 2.0)

Encoding UTF-8

RoxygenNote 7.1.1

URL <https://justincally.github.io/VicmapR/>,
<https://mapshare.vic.gov.au/vicplan/>,
<https://github.com/justincally/VicmapR/>

BugReports <https://github.com/justincally/VicmapR/issues>

Suggests testthat (>= 2.1.0), covr, knitr, rmarkdown, leaflet

Imports magrittr, httr, sf (>= 0.7), dplyr, purrr, methods, cli, DBI, xml2, glue, dbplyr, rlang, curl

VignetteBuilder knitr

Collate 'globals.R' 'build-query.R' 'check_geoserver.R'
'cql-predicates.R' 'cql-translate.R' 'filter.R' 'select.R'
'listFeatures.R' 'polygonFormat.R' 'utils-collect.R'
'utils-classes.R' 'utils-head.R' 'utils-metadata.R'
'utils-options.R' 'utils-pipe.R' 'utils-show_query.R'

NeedsCompilation no

Author Justin Cally [aut, cre] (<https://orcid.org/0000-0003-4584-2220>),
Rachel Swain [ctb],
Andy Teucher [aut] (<https://orcid.org/0000-0002-7840-692X>), bdata
author),
Sam Albers [aut] (<https://orcid.org/0000-0002-9270-7884>), bdata
author),

Stephanie Hazlitt [aut] (<<https://orcid.org/0000-0002-3161-2304>>,
 bcdata author),
 Province of British Columbia [cph] (bcdata copyright)

Maintainer Justin Cally <justin.g.cally@gmail.com>

Repository CRAN

Date/Publication 2021-07-26 04:40:05 UTC

R topics documented:

check_geoserver	2
CQL	3
cql_geom_predicates	4
feature_hits	5
geom_col_name	6
listLayers	7
print.vicmap_promise	7
vicmap_options	8
vicmap_query	9
Index	10

check_geoserver	<i>Check Geoserver Response</i>
-----------------	---------------------------------

Description

VicmapR relies upon a functioning geoserver. If for whatever reason the geoserver is not functioning then the functions in this package will not work. This function will check the response of the geoserver; erroring out if the connection is down.

Usage

```
check_geoserver(timeout = 15, quiet = FALSE)
```

Arguments

timeout	numeric: the time (in seconds) to wait for the response before timing out (default is 15)
quiet	logical: whether to silently check the connection and if working, return nothing. If FALSE (default), the status message will be printed (http_status)

Value

logical, TRUE if the geoserver is working

Examples

```
check_geoserver()
```

CQL

CQL escaping

Description

Write a CQL expression to escape its inputs, and return a CQL/SQL object. Used when writing filter expressions in `vicmap_query()`.

Usage

```
CQL(...)
```

Arguments

... Character vectors that will be combined into a single CQL statement.

Details

See [the CQL/ECQL for Geoserver website](#).

The code for cql escaping was developed by the bcdata team: https://bcgov.github.io/bcdata/reference/cql_geom_predicates.html

Value

An object of class `c("CQL", "SQL")`

Examples

```
CQL("FOO > 12 & NAME LIKE 'A'")
```

cql_geom_predicates *CQL Geometry Predicates*

Description

Functions to construct a CQL expression to be used to filter results from `vicmap_query()`. See [the geoserver CQL documentation for details](#). The sf object is automatically simplified to a less complex sf object to reduce the complexity of the Web Service call. Subsequent in-memory filtering may be needed to achieve exact results.

Usage

EQUALS(geom)

DISJOINT(geom)

INTERSECTS(geom)

TOUCHES(geom)

CROSSES(geom)

WITHIN(geom)

CONTAINS(geom)

OVERLAPS(geom)

RELATE(geom, pattern)

BBOX(coords, crs = NULL)

```
DWITHIN(  
  geom,  
  distance,  
  units = c("meters", "feet", "statute miles", "nautical miles", "kilometers")  
)
```

```
BEYOND(  
  geom,  
  distance,  
  units = c("meters", "feet", "statute miles", "nautical miles", "kilometers")  
)
```

Arguments

geom an sf/sfc/sfg or bbox object (from the sf package)

pattern	spatial relationship specified by a DE-9IM matrix pattern. A DE-9IM pattern is a string of length 9 specified using the characters *TF012. Example: '1*T**T**'
coords	the coordinates of the bounding box as four-element numeric vector <code>c(xmin, ymin, xmax, ymax)</code> , a <code>bbox</code> object from the <code>sf</code> package (the result of running <code>sf::st_bbox()</code> on an <code>sf</code> object), or an <code>sf</code> object which then gets converted to a bounding box on the fly.
crs	(Optional) A numeric value or string containing an SRS code. If <code>coords</code> is a <code>bbox</code> object with non-empty <code>crs</code> , it is taken from that. (For example, 'EPSG:3005' or just 3005. The default is to use the CRS of the queried layer)
distance	numeric value for distance tolerance
units	units that distance is specified in. One of "feet", "meters", "statute miles", "nautical miles", "kilometers"

Details

The code for these cql predicates was developed by the bcdata team: https://bcgov.github.io/bcdata/reference/cql_geom_predicates.html

Value

a CQL expression to be passed on to the WFS call

feature_hits	<i>The Number of Rows of the Promised Data</i>
--------------	--

Description

`feature_hits()` returns an integer of the number of rows that match the passed query/promise. This is similar to how `nrow()` works for a `data.frame`, however it will evaluate the number of rows to be returned without having to download the data.

Usage

```
feature_hits(x)
```

Arguments

x object of class `vicmap_promise`

Value

integer

Examples

```
vicmap_query(layer = "datavic:VMHYDRO_WATERCOURSE_DRAIN") %>%
  feature_hits()
```

geom_col_name	<i>Get Column Information</i>
---------------	-------------------------------

Description

geom_col_name returns a single value for the name of the geometry column for the WFS layer selected in the vicmap_promise object (e.g. SHAPE). This column will become the geometry column when using collect(). feature_cols() provides a vector of all column names for the WFS layer selected in the vicmap_promise object and get_col_df() returns a data.frame with the column names and their XML schema string datatypes.

Usage

```
geom_col_name(x)
```

```
feature_cols(x)
```

```
get_col_df(x)
```

Arguments

x object of class vicmap_promise

Value

character/data.frame

Examples

```
# Return the name of the geometry column
vicmap_query(layer = "datavic:VMHYDRO_WATERCOURSE_DRAIN") %>%
  geom_col_name()
```

```
# Return the column names as a character vector
vicmap_query(layer = "datavic:VMHYDRO_WATERCOURSE_DRAIN") %>%
  feature_cols()
```

```
# Return a data.frame of the columns and their XML schema string datatypes
vicmap_query(layer = "datavic:VMHYDRO_WATERCOURSE_DRAIN") %>%
  get_col_df()
```

listLayers	<i>List Available WFS Layers</i>
------------	----------------------------------

Description

Lists layers available from the WFS geoserver. This is similar to sending the WFS request of `getFeatureTypes`. `listLayers()` returns a `data.frame` with the 'Name' and title of the layers available. The 'Name' is what is used within `vicmap_query()` while the title provides somewhat of a description/clarification about the layer.

Usage

```
listLayers(...)
```

Arguments

... Additional arguments passed to `grep`. The pattern argument can be used to search for specific layers with matching names or titles.

Value

`data.frame`

Examples

```
listLayers(pattern = "trees", ignore.case = TRUE)
```

```
print.vicmap_promise Print a Snapshot of the Data
```

Description

`print()` displays a cut of the data (no more than six rows) alongside the number of rows and columns that would be returned.

Usage

```
## S3 method for class 'vicmap_promise'  
print(x, ...)
```

Arguments

x object of class `vicmap_promise` (likely passed from `vicmap_query()`)
... arguments to be passed to `print`

Value

vicmap_promise (invisible), promise sample printed to console

Examples

```
query <- vicmap_query(layer = "datavic:VMHYDRO_WATERCOURSE_DRAIN")
print(query)
```

vicmap_options	<i>options</i>
----------------	----------------

Description

This function retrieves bdata specific options that can be set. These options can be set using `option({name of the option} = {value of the option})`. The default options are purposefully set conservatively to hopefully ensure successful requests. Resetting these options may result in failed calls to the data catalogue. Options in R are reset every time R is re-started.

`vicmap.max_geom_pred_size` is the maximum size of an object used for a geometric operation. Objects that are bigger than this value will be simplified in the request call using `sf::st_simplify()`. This is done to reduce the size of the query being sent to the WFS geoserver.

`vicmap.chunk_limit` is an option useful when dealing with very large data sets. When requesting large objects from the catalogue, the request is broken up into smaller chunks which are then re-combined after they've been downloaded. VicmapR does this all for you but using this option you can set the size of the chunk requested. On faster internet connections, a bigger chunk limit could be useful while on slower connections, it is advisable to lower the chunk limit. Chunks must be less than 70000.

`vicmap.base_url` is the base wfs url used to query the geoserver.

Usage

```
vicmap_options()

check_chunk_limit()
```

Value

`vicmap_options()` returns a `data.frame`

Examples

```
vicmap_options()
```

vicmap_query	<i>Establish Vicmap Query</i>
--------------	-------------------------------

Description

Begin a Vicmap WFS query by selecting a WFS layer. The record must be available as a Web Feature Service (WFS) layer (listed in `listLayers()`)

Usage

```
vicmap_query(layer, CRS = 4283, wfs_version = "2.0.0")
```

Arguments

layer	vicmap layer to query. Options are listed in <code>listLayers()</code>
CRS	Coordinate Reference System (default is 4283)
wfs_version	The current version of WFS is 2.0.0. GeoServer supports versions 2.0.0, 1.1.0, and 1.0.0. However in order for filtering to be correctly applied wfs_version must be 2.0.0 (default is 2.0.0)

Details

The returned `vicmap_promise` object is not data, rather it is a 'promise' of the data that can be returned if `collect()` is used; which returns an `sf` object.

Value

object of class `vicmap_promise`, which is a 'promise' of the data that can be returned if `collect()` is used

Examples

```
vicmap_query(layer = "datavic:VMHYDRO_WATERCOURSE_DRAIN")
```

Index

BBOX (cql_geom_predicates), 4
BEYOND (cql_geom_predicates), 4

check_chunk_limit (vicmap_options), 8
check_geoserver, 2
CONTAINS (cql_geom_predicates), 4
CQL, 3
cql_geom_predicates, 4
CROSSES (cql_geom_predicates), 4

DISJOINT (cql_geom_predicates), 4
DWITHIN (cql_geom_predicates), 4

EQUALS (cql_geom_predicates), 4

feature_cols (geom_col_name), 6
feature_hits, 5

geom_col_name, 6
get_col_df (geom_col_name), 6
grep, 7

http_status, 2

INTERSECTS (cql_geom_predicates), 4

listLayers, 7

OVERLAPS (cql_geom_predicates), 4

print, 7
print.vicmap_promise, 7

RELATE (cql_geom_predicates), 4

TOUCHES (cql_geom_predicates), 4

vicmap_options, 8
vicmap_query, 9
vicmap_query(), 3, 4, 7

WITHIN (cql_geom_predicates), 4