

# Package ‘gdalcubes’

December 3, 2021

**Title** Earth Observation Data Cubes from Satellite Image Collections

**Version** 0.5.1

**Date** 2021-12-02

**Description** Processing collections of Earth observation images as on-demand multispectral, multitemporal raster data cubes. Users define cubes by spatiotemporal extent, resolution, and spatial reference system and let 'gdalcubes' automatically apply cropping, reprojection, and resampling using the 'Geospatial Data Abstraction Library' ('GDAL'). Implemented functions on data cubes include reduction over space and time, applying arithmetic expressions on pixel band values, moving window aggregates over time, filtering by space, time, bands, and predicates on pixel values, exporting data cubes as 'netCDF' or 'GeoTIFF' files, and plotting. The package implements lazy evaluation and multithreading. All computational parts are implemented in C++, linking to the 'GDAL', 'netCDF', 'CURL', and 'SQLite' libraries. See Appel and Pebesma (2019) <[doi:10.3390/data4030092](https://doi.org/10.3390/data4030092)> for further details.

**Depends** R (>= 3.4)

**Imports** Rcpp, RcppProgress, jsonlite, ncdf4

**License** MIT + file LICENSE

**URL** [https://github.com/appelmar/gdalcubes\\_R](https://github.com/appelmar/gdalcubes_R)

**BugReports** [https://github.com/appelmar/gdalcubes\\_R/issues/](https://github.com/appelmar/gdalcubes_R/issues/)

**Encoding** UTF-8

**RoxygenNote** 7.1.2

**LinkingTo** Rcpp, RcppProgress

**Suggests** knitr, magrittr, rmarkdown, stars, magick, sf

**VignetteBuilder** knitr

**Copyright** file inst/COPYRIGHTS

**NeedsCompilation** yes

**SystemRequirements** cxx11, gdal, libgdal, libproj, netcdf4

**Author** Marius Appel [aut, cre] (<<https://orcid.org/0000-0001-5281-3896>>),  
 Edzer Pebesma [ctb] (<<https://orcid.org/0000-0001-8049-7069>>),  
 Roger Bivand [ctb],  
 Jeroen Ooms [ctb] (<<https://orcid.org/0000-0002-4035-0289>>),  
 Lewis Van Winkle [cph],  
 Ole Christian Eidheim [cph],  
 Howard Hinnant [cph],  
 Adrian Colomitchi [cph],  
 Florian Dang [cph],  
 Paul Thompson [cph],  
 Tomasz Kamiński [cph],  
 Dropbox, Inc. [cph]

**Maintainer** Marius Appel <marius.appel@uni-muenster.de>

**Repository** CRAN

**Date/Publication** 2021-12-03 10:00:07 UTC

## R topics documented:

.copy_cube	4
add_collection_format	4
add_images	5
aggregate_time	6
animate	7
apply_pixel	8
apply_pixel.array	9
apply_pixel.cube	10
apply_time	12
apply_time.array	13
apply_time.cube	14
as_array	15
as_json	16
bands	17
chunk_apply	18
collection_formats	19
create_image_collection	20
crop	21
cube_view	23
dim.cube	25
dimensions	26
dimension_bounds	27
dimension_values	27
extent	28
fill_time	29
filter_geom	30
filter_pixel	31
gdalcubes	32
gdalcubes_gdalformats	33

gdalcubes_gdalversion . . . . .	33
gdalcubes_gdal_has_geos . . . . .	34
gdalcubes_options . . . . .	34
gdalcubes_selection . . . . .	35
gdalcubes_version . . . . .	37
image_collection . . . . .	38
image_mask . . . . .	38
join_bands . . . . .	40
memsize . . . . .	41
names.cube . . . . .	42
nbands . . . . .	42
ncdf_cube . . . . .	43
nt . . . . .	44
nx . . . . .	45
ny . . . . .	46
pack_minmax . . . . .	46
plot.cube . . . . .	47
print.cube . . . . .	49
print.cube_view . . . . .	50
print.image_collection . . . . .	51
proj4 . . . . .	51
query_points . . . . .	52
query_timeseries . . . . .	53
raster_cube . . . . .	54
raster_cube_dummy . . . . .	55
read_chunk_as_array . . . . .	56
reduce_space . . . . .	57
reduce_space.array . . . . .	58
reduce_space.cube . . . . .	59
reduce_time . . . . .	60
reduce_time.array . . . . .	61
reduce_time.cube . . . . .	62
rename_bands . . . . .	64
select_bands . . . . .	65
select_time . . . . .	66
size . . . . .	67
slice_space . . . . .	68
slice_time . . . . .	69
srs . . . . .	70
stack_cube . . . . .	71
stac_image_collection . . . . .	73
st_as_stars.cube . . . . .	74
window_time . . . . .	75
window_time.cube . . . . .	76
write_chunk_from_array . . . . .	77
write_ncdf . . . . .	78
write_tif . . . . .	80
zonal_statistics . . . . .	82

**Index****84**


---

<code>.copy_cube</code>	<i>Create a data cube proxy object copy</i>
-------------------------	---

---

**Description**

Copy a data cube proxy object without copying any data

**Usage**

```
.copy_cube(cube)
```

**Arguments**

<code>cube</code>	source data cube proxy object
-------------------	-------------------------------

**Details**

This internal function copies the complete processing chain / graph of a data cube but does not copy any data. It is used internally to avoid in-place modification for operations with potential side effects on source data cubes.

**Value**

copied data proxy object

---

<code>add_collection_format</code>	<i>Download and install an image collection format from a URL</i>
------------------------------------	---

---

**Description**

Download and install an image collection format from a URL

**Usage**

```
add_collection_format(url, name = NULL)
```

**Arguments**

<code>url</code>	URL pointing to the collection format JSON file
<code>name</code>	optional name used to refer to the collection format

**Details**

By default, the collection format name will be derived from the basename of the URL.

**Examples**

```
add_collection_format(
    "https://raw.githubusercontent.com/appeymar/gdalcubes/dev/formats/Sentinel1_IW_GRD.json")
```

---

add_images	<i>Add images to an existing image collection</i>
------------	---

---

**Description**

This function adds provided files or GDAL dataset identifiers and to an existing image collection by extracting datetime, image identifiers, and band information according to the collection's format.

**Usage**

```
add_images(
    image_collection,
    files,
    unroll_archives = TRUE,
    out_file = "",
    quiet = FALSE
)
```

**Arguments**

image_collection	image_collection object or path to an existing collection file
files	character vector with paths to image files on disk or any GDAL dataset identifiers (including virtual file systems and higher level drivers or GDAL sub-datasets)
unroll_archives	automatically convert .zip, .tar archives and .gz compressed files to GDAL virtual file system dataset identifiers (e.g. by prepending /vsizip/) and add contained files to the list of considered files
out_file	path to output file, an empty string (the default) will update the collection in-place, whereas images will be added to a new copy of the image collection at the given location otherwise.
quiet	logical; if TRUE, do not print resulting image collection if return value is not assigned to a variable

**Value**

image collection proxy object, which can be used to create a data cube using [raster\\_cube](#)

**Examples**

```
L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                      ".TIF", recursive = TRUE, full.names = TRUE)
L8_col = create_image_collection(L8_files[1:12], "L8_L1TP")
add_images(L8_col, L8_files[13:24])
```

---

aggregate_time	<i>Aggregate data cube time series to lower temporal resolution</i>
----------------	---

---

**Description**

Create a proxy data cube, which applies an aggregation function over pixel time series to lower temporal resolution.

**Usage**

```
aggregate_time(cube, dt, method = "mean", fact = NULL)
```

**Arguments**

cube	source data cube
dt	character; new temporal resolution, datetime period string, e.g. "P1M"
method	aggregation method, one of "mean", "min", "max", "median", "count", "sum", "prod", "var", and "sd"
fact	simple integer factor defining how many cells become aggregated to a single new cell, can be used instead of dt

**Details**

This function can be used to aggregate time series to lower resolution or to regularize a data cube with irregular (labeled) time axis. It is possible to change the unit of the temporal resolution (e.g. to create monthly composites from daily images). The size of the cube may be expanded automatically if the original temporal extent is not divisible by the new temporal size of pixels.

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}
```

```

}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P3M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.two_monthly = aggregate_time(L8.rgb, "P6M", "min")
L8.two_monthly

plot(L8.two_monthly, rgb=3:1, zlim=c(5000,12000))

```

---

animate

*Animate a data cube as an image time series*


---

## Description

Animate a data cube as an image time series

## Usage

```

animate(
  x,
  ...,
  fps = 1,
  loop = 0,
  width = dev.size(units = "px")[1],
  height = dev.size(units = "px")[2],
  save_as = NULL,
  plot = TRUE
)

```

## Arguments

x	a data cube proxy object (class cube)
...	parameters passed to plot.cube
fps	frames per second of the animation
loop	how many iterations, 0 = infinite
width	width (in pixels) of the animation
height	height (in pixels) of the animation
save_as	character path where the animation shall be stored as a gif file
plot	logical; plot the animation (default is TRUE)

**Details**

Animations can be created for single band data cubes or RGB plots of multi-band data cubes (by providing the argument `rgb`) only.

**See Also**

[plot.cube](#)

**Examples**

```
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P16D")

animate(select_bands(raster_cube(L8.col, v), c("B02", "B03", "B04")), rgb=3:1,
        zlim=c(0,20000), fps=1, loop=1)

animate(select_bands(raster_cube(L8.col, v), c("B05")), col=terrain.colors, key.pos=1)
```

---

apply\_pixel

*Apply a function over (multi-band) pixels*

---

**Description**

This generic function applies a function on pixels of a data cube, an R array, or other classes if implemented.

**Usage**

```
apply_pixel(x, ...)
```

**Arguments**

<code>x</code>	input data
<code>...</code>	additional arguments passed to method implementations

**Value**

return value and type depend on the class of `x`



**See Also**

[apply\\_pixel.cube](#)  
[apply\\_pixel.array](#)

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

L8.col = image_collection(file.path(tempdir(), "L8.db"))
apply_pixel(raster_cube(L8.col, v), "(B05-B04)/(B05+B04)", "NDVI")

d <- c(4,16,128,128)
x <- array(rnorm(prod(d)), d)
y <- apply_pixel(x, function(v) {
  v[1] + v[2] + v[3] - v[4]
})
```

---

apply_pixel.array	<i>Apply a function over pixels in a four-dimensional (band, time, y, x) array</i>
-------------------	--

---

**Description**

Apply a function over pixels in a four-dimensional (band, time, y, x) array

**Usage**

```
## S3 method for class 'array'
apply_pixel(x, FUN, ...)
```

**Arguments**

x	four-dimensional input array with dimensions band, time, y, x (in this order)
FUN	function that receives a vector of band values in a one-dimensional array
...	further arguments passed to FUN

**Details**

FUN is expected to produce a numeric vector (or scalar) where elements are interpreted as new bands in the result.

**Note**

This is a helper function that uses the same dimension ordering as gdalcubes. It can be used to simplify the application of R functions e.g. over time series in a data cube.

**Examples**

```
d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
y <- apply_pixel(x, function(v) {
  v[1] + v[2] + v[3] - v[4]
})
dim(y)
```

---

 apply\_pixel.cube

*Apply arithmetic expressions over all pixels of a data cube*


---

**Description**

Create a proxy data cube, which applies arithmetic expressions over all pixels of a data cube. Expressions may access band values by name.

**Usage**

```
## S3 method for class 'cube'
apply_pixel(x, expr, names = NULL, keep_bands = FALSE, ..., FUN)
```

**Arguments**

x	source data cube
expr	character vector with one or more arithmetic expressions (see Details)
names	optional character vector with the same length as expr to specify band names for the output cube
keep_bands	logical; keep bands of input data cube, defaults to FALSE, i.e. original bands will be dropped
...	not used
FUN	user-defined R function that is applied on all pixels (see Details)

## Details

The function can either apply simple arithmetic C expressions given as a character vector (expr argument), or apply a custom R reducer function if FUN is provided.

In the former case, gdalcubes uses the [tinyexpr library](#) to evaluate expressions in C / C++, you can look at the [library documentation](#) to see what kind of expressions you can execute. Pixel band values can be accessed by name.

FUN receives values of the bands from one pixel as a (named) vector and should return a numeric vector with identical length for all pixels. Elements of the result vectors will be interpreted as bands in the result data cube.

## Value

a proxy data cube object

## Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

# 1. Apply a C expression
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")
L8.ndvi

plot(L8.ndvi)

# 2. Apply a user defined R function
L8.ndvi.noisy = apply_pixel(L8.cube, names="NDVI_noisy",
                           FUN=function(x) {
                             rnorm(1, 0, 0.1) + (x["B05"]-x["B04"])/(x["B05"]+x["B04"])
                           })
L8.ndvi.noisy
```

```
plot(L8.ndvi.noisy)
```

---

apply_time	<i>Apply a function over (multi-band) pixel time series</i>
------------	---

---

### Description

This generic function applies a function on pixel time series of a data cube, an R array, or other classes if implemented. The resulting object is expected to have the same spatial and temporal shape as the input, i.e., no reduction is performed.

### Usage

```
apply_time(x, ...)
```

### Arguments

x	input data
...	additional arguments passed to method implementations

### Value

return value and type depend on the class of x

### See Also

[apply\\_time.cube](#)  
[apply\\_time.array](#)

### Examples

```
# 1. input is data cube
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
```

```

L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")

# Apply a user defined R function
apply_time(L8.ndvi, names="NDVI_residuals",
  FUN=function(x) {
    y = x["NDVI",]
    if (sum(is.finite(y)) < 3) {
      return(rep(NA,ncol(x)))
    }
    t = 1:ncol(x)
    return(predict(lm(y ~ t)) - x["NDVI",,]))

# 2. input is array
d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
z <- apply_time(x, function(v) {
  y = matrix(NA, ncol=ncol(v), nrow=2)
  y[1,] = (v[1,] + v[2,]) / 2
  y[2,] = (v[3,] + v[4,]) / 2
  y
})
dim(z)

```

---

apply_time.array	<i>Apply a function over pixel time series in a four-dimensional (band, time, y, x) array</i>
------------------	---

---

## Description

Apply a function over pixel time series in a four-dimensional (band, time, y, x) array

## Usage

```
## S3 method for class 'array'
apply_time(x, FUN, ...)
```

## Arguments

x	four-dimensional input array with dimensions band, time, y, x (in this order)
FUN	function that receives a vector of band values in a one-dimensional array
...	further arguments passed to FUN

## Details

FUN is expected to produce a matrix (or vector if result has only one band) where rows are interpreted as new bands and columns represent time.

**Note**

This is a helper function that uses the same dimension ordering as `gdalcubes`. It can be used to simplify the application of R functions e.g. over time series in a data cube.

**Examples**

```
d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
z <- apply_time(x, function(v) {
  y = matrix(NA, ncol=ncol(v), nrow=2)
  y[1,] = (v[1,] + v[2,]) / 2
  y[2,] = (v[3,] + v[4,]) / 2
  y
})
dim(z)
```

---

apply\_time.cube

*Apply a user-defined R function over (multi-band) pixel time series*

---

**Description**

Create a proxy data cube, which applies a user-defined R function over all pixel time series of a data cube. In contrast to `reduce_time`, the time dimension is not reduced, i.e., resulting time series must have identical length as the input data cube but may contain a different number of bands / variables. Example uses of this function may include time series decompositions, cumulative sums / products, smoothing, sophisticated NA filling, or similar.

**Usage**

```
## S3 method for class 'cube'
apply_time(x, names = NULL, keep_bands = FALSE, FUN, ...)
```

**Arguments**

<code>x</code>	source data cube
<code>names</code>	optional character vector to specify band names for the output cube
<code>keep_bands</code>	logical; keep bands of input data cube, defaults to FALSE, i.e., original bands will be dropped
<code>FUN</code>	user-defined R function that is applied on all pixel time series (see Details)
<code>...</code>	not used

**Details**

`FUN` receives a single (multi-band) pixel time series as a matrix with rows corresponding to bands and columns corresponding to time. In general, the function must return a matrix with the same number of columns. If the result contains only a single band, it may alternatively return a vector with length identical to the length of the input time series (number of columns of the input).

**Value**

a proxy data cube object

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")

# Apply a user defined R function
L8.ndvi.resid = apply_time(L8.ndvi, names="NDVI_residuals",
  FUN=function(x) {
    y = x["NDVI",]
    if (sum(is.finite(y)) < 3) {
      return(rep(NA,ncol(x)))
    }
    t = 1:ncol(x)
    return(predict(lm(y ~ t)) - x["NDVI",])
  })
L8.ndvi.resid

plot(L8.ndvi.resid)
```

**Description**

Convert a data cube to an in-memory R array

**Usage**

```
as_array(x)
```

**Arguments**

```
x          data cube
```

**Value**

Four dimensional array with dimensions band, t, y, x

**Note**

Depending on the data cube size, this function may require substantial amounts of main memory, i.e. it makes sense for small data cubes only.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-05"),
              srs="EPSG:32618", nx = 100, ny=100, dt="P1M")
as_array(select_bands(raster_cube(L8.col, v), c("B04", "B05")))
```

---

as\_json

*Query data cube properties*

---

**Description**

gdalcubes uses a graph (currently a tree) to serialize data cubes (including chains of cubes). This function gives a JSON representation, which will be communicated to gdalcubes\_server instances to create identical cube instances remotely.

**Usage**

```
as_json(obj)
```



**Arguments**

obj                    a data cube proxy object (class cube)

**Value**

A JSON string representing a graph (currently a tree) that can be used to create the same chain of gdalcubes operations.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-04"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
cat(as_json(select_bands(raster_cube(L8.col, v), c("B04", "B05"))))
```

bands

*Query data cube properties***Description**

Query data cube properties

**Usage**

```
bands(obj)
```

**Arguments**

obj                    a data cube proxy object (class cube)

**Value**

A data.frame with rows representing the bands and columns representing properties of a band (name, type, scale, offset, unit)

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
bands(raster_cube(L8.col, v))
```

---

 chunk\_apply

*Apply an R function on chunks of a data cube*


---

**Description**

Apply an R function on chunks of a data cube

**Usage**

```
chunk_apply(cube, f)
```

**Arguments**

cube	source data cube
f	R function to apply over all chunks

**Details**

This function internally creates a gdalcubes stream data cube, which streams data of a chunk to a new R process. For reading data, the function typically calls `x <- read_chunk_as_array()` which then results in a 4 dimensional (band, time, y, x) array. Similarly `write_chunk_from_array(x)` will write a result array as a chunk in the resulting data cube. The chunk size of the input cube is important to control how the function will be exposed to the data cube. For example, if you want to apply an R function over complete pixel time series, you must define the chunk size argument in [raster\\_cube](#) to make sure that chunk contain the correct parts of the data.

**Value**

a proxy data cube object

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
f <- function() {
  x <- read_chunk_as_array()
  out <- reduce_time(x, function(x) {
    cor(x[1,], x[2,], use="na.or.complete", method = "kendall")
  })
  write_chunk_from_array(out)
}
L8.cor = chunk_apply(L8.cube, f)
```

---

collection\_formats      *List predefined image collection formats*

---

## Description

gdalcubes comes with some predefined collection formats e.g. to scan Sentinel 2 data. This function lists available formats including brief descriptions.

## Usage

```
collection_formats(print = TRUE)
```

## Arguments

print	logical; should available formats and their descriptions be printed nicely, defaults to TRUE
-------	--

## Details

Image collection formats define how individual files / GDAL datasets relate to an image collection, i.e., which bands they contain, to which image they belong, and how to derive acquisition date/time. They are described as a set of regular expressions in a JSON file and used by gdalcubes to extract this information from the paths and/or filenames.

**Value**

data.frame with columns name and description where the former describes the unique identifier that can be used in create\_image\_collection and the latter gives a brief description of the format.

**Examples**

```
collection_formats()
```

---

```
create_image_collection
```

*Create an image collection from a set of GDAL datasets or files*

---

**Description**

This function iterates over files or GDAL dataset identifiers and extracts datetime, image identifiers, and band information according to a given collection format.

**Usage**

```
create_image_collection(
  files,
  format = NULL,
  out_file = tempfile(fileext = ".sqlite"),
  date_time = NULL,
  band_names = NULL,
  use_subdatasets = FALSE,
  unroll_archives = TRUE,
  quiet = FALSE
)
```

**Arguments**

files	character vector with paths to image files on disk or any GDAL dataset identifiers (including virtual file systems and higher level drivers or GDAL subdatasets)
format	collection format, can be either a name to use predefined formats (as output from <a href="#">collection_formats</a> ) or a path to a custom JSON format description file
out_file	optional name of the output SQLite database file, defaults to a temporary file
date_time	vector with date/ time for files; can be of class character, Date, or POSIXct (argument is only applicable for image collections without collection format)
band_names	character vector with band names, length must match the number of bands in provided files (argument is only applicable for image collections without collection format)
use_subdatasets	logical; use GDAL subdatasets of provided files (argument is only applicable for image collections without collection format)

unroll_archives	automatically convert .zip, .tar archives and .gz compressed files to GDAL virtual file system dataset identifiers (e.g. by prepending /vsizip/) and add contained files to the list of considered files
quiet	logical; if TRUE, do not print resulting image collection if return value is not assigned to a variable

## Details

An image collection is a simple SQLite database file that indexes and references existing image files / GDAL dataset identifiers.

Collections can be created in two different ways: First, if a collection format is specified (argument `format`), date/time, bands, and metadata are automatically extracted from provided files / GDAL datasets. Second, image collections can be created without collection format by manually specifying date/time of images (argument `date_time`) and (optional) names of bands. In this case, however, all provided images must contain the same bands. If this is not possible for a dataset, a collection format must be used.

## Value

image collection proxy object, which can be used to create a data cube using [raster\\_cube](#)

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}
```

---

crop

*Crop data cube extent by space and/or time*

---

## Description

Create a proxy data cube, which crops a data cube by a spatial and/or temporal extent.

## Usage

```
crop(cube, extent = NULL, iextent = NULL, snap = "near")
```

**Arguments**

cube	source data cube
extent	list with numeric items left, right, top, bottom, and character items t0 and t1, or a subset thereof, see examples
iextent	list with length-two integer items named x, y, and t, defining the lower and upper boundaries as integer coordinates, see examples
snap	one of 'near', 'in', or 'out'; ignored if using iextent

**Details**

The new extent can be specified by spatial coordinates and datetime values (using the extent argument), or as zero-based integer indexes (using the iextent argument). In the former case, extent expects a list with numeric items left, right, top, bottom, t0, and t1, or a subset thereof. In the latter case, iextent is expected as a list with length-two integer vectors x, y, and t as items, defining the lower and upper cell indexes per dimension.

Notice that it is possible to crop only selected boundaries (e.g., only the right boundary) as missing boundaries in the extent or NA / NULL values in the iextent arguments are considered as "no change". It is, however, not possible to mix arguments extent and iextent.

If extent is given, the snap argument can be used to define what happens if the new boundary falls within a data cube cell.

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P3M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))

# crop by integer indexes
L8.cropped = crop(L8.rgb, iextent = list(x=c(0,400), y=c(0,400), t=c(1,1)))

# crop by spatiotemporal coordinates
L8.cropped = crop(L8.rgb, extent = list(left=388941.2, right=766552.4,
                                       bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"), snap = "in")
L8.cropped
```

```
L8.cropped = crop(L8.rgb, extent = list(left=388941.2, right=766552.4,  
    bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"), snap = "near")  
L8.cropped  
  
plot(L8.cropped, rgb = 3:1, zlim=c(5000,10000))
```

---

cube\_view

*Create or update a spatiotemporal data cube view*

---

## Description

Data cube views define the shape of a cube, i.e., the spatiotemporal extent, resolution, and spatial reference system (srs). They are used to access image collections as on-demand data cubes. The data cube will filter images based on the view's extent, read image data at the defined resolution, and warp / reproject images to the target srs automatically.

## Usage

```
cube_view(  
  view,  
  extent,  
  srs,  
  nx,  
  ny,  
  nt,  
  dx,  
  dy,  
  dt,  
  aggregation,  
  resampling,  
  keep.asp = TRUE  
)
```

## Arguments

view	if provided, update this cube_view object instead of creating a new data cube view where fields that are already set will be overwritten
extent	spatiotemporal extent as a list e.g. from <a href="#">extent</a> or an image collection object, see <a href="#">Details</a>
srs	target spatial reference system as a string; can be a proj4 definition, WKT, or in the form "EPSG:XXXX"
nx	number of pixels in x-direction (longitude / easting)
ny	number of pixels in y-direction (latitude / northing)

nt	number of pixels in t-direction
dx	size of pixels in x-direction (longitude / easting)
dy	size of pixels in y-direction (latitude / northing)
dt	size of pixels in time-direction, expressed as ISO8601 period string (only 1 number and unit is allowed) such as "P16D"
aggregation	aggregation method as string, defining how to deal with pixels containing data from multiple images, can be "min", "max", "mean", "median", or "first"
resampling	resampling method used in gdalwarp when images are read, can be "near", "bilinear", "bicubic" or others as supported by gdalwarp (see <a href="https://gdal.org/programs/gdalwarp.html">https://gdal.org/programs/gdalwarp.html</a> )
keep.asp	if TRUE, derive ny or dy automatically from nx or dx (or vice versa) based on the aspect ratio of the spatial extent

### Details

The extent argument expects a simple list with elements left, right, bottom, top, t0 (start date/time), t1 (end date/time) or an image collection object. In the latter case, the `extent` function is automatically called on the image collection object to get the full spatiotemporal extent of the collection. In the former case, datetimes are expressed as ISO8601 datetime strings.

The function can be used in two different ways. First, it can create data cube views from scratch by defining the extent, the spatial reference system, and for each dimension either the cell size (dx, dy, dt) or the total number of cells (nx, ny, nt). Second, the function can update an existing data cube view by overwriting specific fields. In this case, the extent or some elements of the extent may be missing.

In some cases, the extent of the view is automatically extended if the provided resolution would end within a pixel. For example, if the spatial extent covers an area of 1km x 1km and dx = dy = 300m, the extent would be enlarged to 1.2 km x 1.2km. The alignment will be reported to the user in a diagnostic message.

### Value

A list with data cube view properties

### Examples

```
L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                      ".TIF", recursive = TRUE, full.names = TRUE)
L8.col = create_image_collection(L8_files, "L8_L1TP")

# 1. Create a new data cube view specification
v = cube_view(extent=extent(L8.col,"EPSG:4326"), srs="EPSG:4326", dt="P1M",
              nx=1000, ny=500, aggregation = "mean", resampling="bilinear")
v

# 2. overwrite parts of an existing data cube view
vnew = cube_view(v, dt="P1M")
```



---

dim.cube	<i>Query data cube properties</i>
----------	-----------------------------------

---

## Description

Query data cube properties

## Usage

```
## S3 method for class 'cube'  
dim(x)
```

## Arguments

x a data cube proxy object (class cube)

## Value

size of a data cube (number of cells) as integer vector in the order t, y, x

## See Also

[size](#)

## Examples

```
# create image collection from example Landsat data only  
# if not already done in other examples  
if (!file.exists(file.path(tempdir(), "L8.db"))) {  
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),  
                        ".TIF", recursive = TRUE, full.names = TRUE)  
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))  
}  
  
L8.col = image_collection(file.path(tempdir(), "L8.db"))  
v = cube_view(extent=list(left=388941.2, right=766552.4,  
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),  
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")  
dim(raster_cube(L8.col, v))
```

---

dimensions	<i>Query data cube properties</i>
------------	-----------------------------------

---

### Description

Query data cube properties

### Usage

```
dimensions(obj)
```

### Arguments

obj                    a data cube proxy object (class cube)

### Details

Elements of the returned list represent individual dimensions with properties such as dimension boundaries, names, and chunk size stored as inner lists

### Value

Dimension information as a list

### Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
dimensions(raster_cube(L8.col, v))
```

---

dimension\_bounds      *Query coordinate bounds for all dimensions of a data cube*

---

### Description

Dimension values give the coordinates bounds the spatial and temporal axes of a data cube.

### Usage

```
dimension_bounds(obj, datetime_unit = NULL)
```

### Arguments

`obj`                    a data cube proxy (class cube)  
`datetime_unit`        unit used to format values in the datetime dimension, one of "Y", "m", "d", "H", "M", "S", defaults to the unit of the cube.

### Value

list with elements t,y,x, each a list with two elements, start and end

### Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
dimension_bounds(raster_cube(L8.col, v))
```

---

dimension\_values      *Query coordinate values for all dimensions of a data cube*

---

### Description

Dimension values give the coordinates along the spatial and temporal axes of a data cube.

### Usage

```
dimension_values(obj, datetime_unit = NULL)
```

**Arguments**

`obj` a data cube proxy (class `cube`), or a data cube view object

`datetime_unit` unit used to format values in the datetime dimension, one of "Y", "m", "d", "H", "M", "S", defaults to the unit of the cube.

**Value**

list with elements `t,y,x`

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
dimension_values(raster_cube(L8.col, v))
```

---

extent

*Derive the spatiotemporal extent of an image collection*

---

**Description**

Derive the spatiotemporal extent of an image collection

**Usage**

```
extent(x, srs = "EPSG:4326")
```

**Arguments**

`x` image collection proxy object

`srs` target spatial reference system

**Value**

a list with elements `left`, `right`, `bottom`, `top`, `t0` (start date/time), and `t1` (end date/time)

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
extent(L8.col, "EPSG:32618")
cube_view(extent=extent(L8.col, "EPSG:32618"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
```

---

fill\_time

---

*Fill NA data cube pixels by simple time series interpolation*


---

**Description**

Create a proxy data cube, which fills NA pixels of a data cube by nearest neighbor or linear time series interpolation.

**Usage**

```
fill_time(cube, method = "near")
```

**Arguments**

cube	source data cube
method	interpolation method, can be "near" (nearest neighbor), "linear" (linear interpolation), "lof" (last observation carried forward), or "nocb" (next observation carried backward)

**Details**

Please notice that completely empty (NA) time series will not be filled, i.e. the result cube might still contain NA values.

**Value**

a proxy data cube object

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P3M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.filled = fill_time(L8.rgb, "linear")
L8.filled

plot(L8.filled, rgb=3:1, zlim=c(5000,12000))
```

---

 filter\_geom

*Filter data cube pixels by a polygon*


---

## Description

Create a proxy data cube, which filters pixels by a spatial (multi)polygon For all pixels whose center is within the polygon, the original

## Usage

```
filter_geom(cube, geom, srs = NULL)
```

## Arguments

cube	source data cube
geom	either a WKT string, or an sfc or sfg object (sf package)
srs	string identifier of the polygon's coordinate reference system understandable for GDAL

## Details

The resulting data cube will not be cropped but pixels outside of the polygon will be set to NAN.

If geom is provided as an sfc object with length > 1, geometries will be combined with sf::st\_combine() before.

The geometry is automatically transformed to the data cube's spatial reference system if needed.

**Value**

a proxy data cube object

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")
WKT = gsub(pattern='\\n',replacement="",x =
  "Polygon ((-74.3541 40.9254,
    -73.9813 41.2467,
    -73.9997 41.4400,
    -74.5362 41.1795,
    -74.6286 40.9137,
    -74.3541 40.9254)))")
L8.ndvi.filtered = filter_geom(L8.ndvi, WKT, "EPSG:4326")
L8.ndvi.filtered

plot(L8.ndvi.filtered)
```

---

 filter\_pixel

*Filter data cube pixels by a user-defined predicate on band values*


---

**Description**

Create a proxy data cube, which evaluates a predicate over all pixels of a data cube. For all pixels that fulfill the predicate, the original band values are returned. Other pixels are simply filled with NaNs. The predicate may access band values by name.

**Usage**

```
filter_pixel(cube, pred)
```

**Arguments**

cube	source data cube
pred	predicate to be evaluated over all pixels

**Details**

gdalcubes uses and extends the [tinyexpr library](#) to evaluate expressions in C / C++, you can look at the [library documentation](#) to see what kind of expressions you can execute. Pixel band values can be accessed by name.

**Value**

a proxy data cube object

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")
L8.ndvi.filtered = filter_pixel(L8.ndvi, "NDVI > 0.5")
L8.ndvi.filtered

plot(L8.ndvi.filtered)
```



**Description**

Processing collections of Earth observation images as on-demand multispectral, multitemporal raster data cubes. Users define cubes by spatiotemporal extent, resolution, and spatial reference system and let 'gdalcubes' automatically apply cropping, reprojection, and resampling using the 'Geospatial Data Abstraction Library' ('GDAL'). Implemented functions on data cubes include reduction over space and time, applying arithmetic expressions on pixel band values, moving window aggregates over time, filtering by space, time, bands, and predicates on pixel values, exporting data cubes as 'netCDF' or 'GeoTIFF' files, and plotting. The package implements lazy evaluation and multithreading. All computational parts are implemented in C++, linking to the 'GDAL', 'netCDF', 'CURL', and 'SQLite' libraries. See Appel and Pebesma (2019) <doi:10.3390/data4030092> for further details.

---

gdalcubes\_gdalformats *Get available GDAL drivers*

---

**Description**

Get available GDAL drivers

**Usage**

```
gdalcubes_gdalformats()
```

**Examples**

```
gdalcubes_gdalformats()
```

---

gdalcubes\_gdalversion *Get the GDAL version used by gdalcubes*

---

**Description**

Get the GDAL version used by gdalcubes

**Usage**

```
gdalcubes_gdalversion()
```

**Examples**

```
gdalcubes_gdalversion()
```

---

 gdalcubes\_gdal\_has\_geos

*Check if GDAL was built with GEOS*


---

### Description

Check if GDAL was built with GEOS

### Usage

```
gdalcubes_gdal_has_geos()
```

### Examples

```
gdalcubes_gdal_has_geos()
```

---

gdalcubes\_options

*Set or read global options of the gdalcubes package*


---

### Description

Set global package options to change the default behavior of gdalcubes. These include how many threads are used to process data cubes, how created netCDF files are compressed, and whether or not debug messages should be printed.

### Usage

```
gdalcubes_options(
  ...,
  threads,
  ncdf_compression_level,
  debug,
  cache,
  ncdf_write_bounds,
  use_overview_images,
  show_progress
)
```

### Arguments

...	not used
threads	number of threads used to process data cubes
ncdf_compression_level	integer; compression level for created netCDF files, 0=no compression, 1=fast compression, 9=small compression

debug	logical; print debug messages
cache	logical; TRUE if temporary data cubes should be cached to support fast reprocessing of the same cubes
ncdf_write_bounds	logical; write dimension bounds as additional variables in netCDF files
use_overview_images	logical; if FALSE, all images are read on original resolution and existing overviews will be ignored
show_progress	logical; if TRUE, a progress bar will be shown for actual computations

### Details

Data cubes can be processed in parallel where one thread processes one chunk at a time. Setting more threads than the number of chunks of a cube thus has no effect and will not further reduce computation times.

Caching has no effect on disk or memory consumption, it simply tries to reuse existing temporary files where possible. For example, changing only parameters to plot will not require rerunning the full data cube operation chain.

Passing no arguments will return the current options as a list.

### Examples

```
gdalcubes_options(threads=4) # set the number of threads
gdalcubes_options() # print current options
gdalcubes_options(threads=1) # reset
```

---

gdalcubes\_selection    *Select a data cube band by name*

---

### Description

Select a data cube band by name

Extract a subset of a data cube

### Usage

```
## S3 method for class 'cube'
x$name

## S3 method for class 'cube'
cube[ib = TRUE, it = TRUE, iy = TRUE, ix = TRUE, ...]
```

**Arguments**

x	source data cube
name	character; name of selected band
cube	source data cube
ib	first selector (optional), object of type character, list, Date, POSIXt, numeric, <a href="#">st_bbox</a> ), or <a href="#">st_sfc</a> ), see Details and examples
it	second selector (optional), see ib
iy	third selector (optional), see ib
ix	fourth selector (optional), see ib
...	further arguments, not used

**Details**

The [] operator allows for flexible subsetting of data cubes by date, datetime, bounding box, spatial points, and band names. Depending on the arguments, it supports slicing ( selecting one element of a dimension) and cropping (selecting a subinterval of a dimension) and combinations thereof (e.g., selecting a spatial window and a temporal slice). Dimension subsets can be specified by integer indexes or coordinates / datetime values. Arguments are matched by type and order. For example, if the first argument is a length-two vector of type Date, the function will realize that this is for subsetting the time dimension. If needed, arguments are treated in the order band, time, y, x.

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P3M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.red = L8.cube$B04

plot(L8.red)

# create image collection from example Landsat data only
```

```

# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01-01", t1="2018-12-31"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1D", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))

L8.cube[c("B05","B04")] # select bands
L8.cube[as.Date(c("2018-01-10", "2018-01-20"))] # crop by time
L8.cube[as.Date("2018-01-10")] # slice by time
L8.cube["B05", "2018-01-10"] # select bands and slice by time
L8.cube["B05", c("2018-01-10","2018-01-17")] # select bands and crop by time
L8.cube[, c("2018-01-10","2018-01-17")] # crop by time

# crop by space (coordinates and integer indexes respectively)
L8.cube[list(left=388941.2 + 1e5, right=766552.4 - 1e5, bottom=4345299 + 1e5, top=4744931 - 1e5)]
L8.cube[, ,c(1,100), c(1,100)]

L8.cube[,c(1,2),,] # crop by time (integer indexes)

# select by spatial point or bounding box
if (requireNamespace("sf", quietly = TRUE)) {
  s = sf::st_sfc(sf::st_point(c(500000, 4500000)), crs = "EPSG:32618")
  L8.cube[s]

  bbox = sf::st_bbox(c(xmin = 388941.2 + 1e5, xmax = 766552.4 - 1e5,
    ymax = 4744931 - 1e5, ymin = 4345299 + 1e5), crs = sf::st_crs(32618))
  L8.cube[bbox]
}

```

---

gdalcubes\_version      *Query gdalcubes version information*

---

## Description

Query gdalcubes version information

## Usage

```
gdalcubes_version()
```

## Value

List with gdalcubes library version information

**Examples**

```
gdalcubes_version()
```

---

image_collection	<i>Load an existing image collection from a file</i>
------------------	--

---

**Description**

This function will load an image collection from an SQLite file. Image collection files index and reference existing imagery. To create a collection from files on disk, use [create\\_image\\_collection](#).

**Usage**

```
image_collection(path)
```

**Arguments**

path                    path to an existing image collection file

**Value**

an image collection proxy object, which can be used to create a data cube using [raster\\_cube](#)

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
L8.col
```

---

image_mask	<i>Create a mask for images in a raster data cube</i>
------------	---

---

**Description**

Create an image mask based on a band and provided values to filter pixels of images read by [raster\\_cube](#)

**Usage**

```
image_mask(  
  band,  
  min = NULL,  
  max = NULL,  
  values = NULL,  
  bits = NULL,  
  invert = FALSE  
)
```

**Arguments**

band	name of the mask band
min	minimum value, values between min and max will be masked
max	maximum value, values between min and max will be masked
values	numeric vector; specific values that will be masked.
bits	for bitmasks, extract the given bits (integer vector) with a bitwise AND before filtering the mask values, bit indexes are zero-based
invert	logical; invert mask

**Details**

Values of the selected mask band can be based on a range (by passing min and max) or on a set of values (by passing values). By default pixels with mask values contained in the range or in the values are masked out, i.e. set to NA. Setting invert = TRUE will invert the masking behavior. Passing values will override min and max.

**Note**

Notice that masks are applied per image while reading images as a raster cube. They can be useful to eliminate e.g. cloudy pixels before applying the temporal aggregation to merge multiple values for the same data cube pixel.

**Examples**

```
image_mask("SCL", values = c(3,8,9)) # Sentinel 2 L2A: mask cloud and cloud shadows  
image_mask("BQA", bits=4, values=16) # Landsat 8: mask clouds  
image_mask("B10", min = 8000, max=65000)
```

---

 join\_bands

*Join bands of two identically shaped data cubes*


---

### Description

Create a proxy data cube, which joins the bands of two identically shaped data cubes. The resulting cube will have bands from both input cubes.

### Usage

```
join_bands(cube_list, cube_names = NULL)
```

### Arguments

cube_list	a list with two or more source data cubes
cube_names	list or character vector with optional name prefixes for bands in the output data cube (see Details)

### Details

The number of provided cube\_names must match the number of provided input cubes. If no cube\_names are provided, bands of the output cube will adopt original names from the input cubes (without any prefix). If any two of the input bands have identical names, prefixes default prefixes ("X1", "X2", ...) will be used.

### Value

proxy data cube object

### Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

### Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-05"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
```



```

L8.cube = raster_cube(L8.col, v)
L8.cube.b04 = select_bands(raster_cube(L8.col, v), c("B04"))
L8.cube.b05 = select_bands(raster_cube(L8.col, v), c("B05"))
join_bands(list(L8.cube.b04,L8.cube.b05))

plot(join_bands(list(L8.cube.b04,L8.cube.b05)))

```

---

memsize

*Query data cube properties*


---

## Description

Query data cube properties

## Usage

```
memsize(obj, unit = "MiB")
```

## Arguments

obj	a data cube proxy object (class cube)
unit	Unit of data size, can be "B", "KB", "KiB", "MB", "MiB", "GB", "GiB", "TB", "TiB", "PB", "PiB"

## Value

Total data size of data cube values expressed in the given unit

## Examples

```

# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
memsize(raster_cube(L8.col, v))

```

---

names.cube                      *Query data cube properties*

---

### Description

Query data cube properties

### Usage

```
## S3 method for class 'cube'
names(x)
```

### Arguments

x                      a data cube proxy object (class cube)

### Value

Band names as character vector

### Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
names(raster_cube(L8.col, v))
```

---

nbands                      *Query data cube properties*

---

### Description

Query data cube properties

### Usage

```
nbands(obj)
```

**Arguments**

obj                    a data cube proxy object (class cube)

**Value**

Number of bands

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
nbands(raster_cube(L8.col, v))
```

---

ncdf\_cube

*Read a data cube from an existing netCDF file*


---

**Description**

Create a proxy data cube from a netCDF file that has been created using [write\\_ncdf](#). This function does not read cubes from arbitrary netCDF files and can be used e.g., to load intermediate results and/or plotting existing netCDF cubes on disk without doing the data cube creation from image collections.

**Usage**

```
ncdf_cube(path, chunking = NULL, auto_unpack = TRUE)
```

**Arguments**

path                    path to an existing netCDF file

chunking                custom chunk sizes to read from the netCDF file; defaults to using chunk sizes from the netCDF file

auto\_unpack            logical; automatically apply offset and scale when reading data values

**Value**

a proxy data cube object

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

ncfile = write_ncdf(select_bands(raster_cube(L8.col, v), c("B02", "B03", "B04")))
ncdf_cube(ncfile)
```

---

 nt

---

*Query data cube properties*


---

**Description**

Query data cube properties

**Usage**

```
nt(obj)
```

**Arguments**

obj                    a data cube proxy object (class cube)

**Value**

Number of pixels in the time dimension

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
nt(raster_cube(L8.col, v))
```

---

 nx

*Query data cube properties*


---

## Description

Query data cube properties

## Usage

```
nx(obj)
```

## Arguments

obj                    a data cube proxy object (class cube)

## Value

Number of pixels in the x dimension

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
nx(raster_cube(L8.col, v))
```

---

ny *Query data cube properties*

---

### Description

Query data cube properties

### Usage

ny(obj)

### Arguments

obj a data cube proxy object (class cube)

### Value

Number of pixels in the y dimension

### Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
ny(raster_cube(L8.col, v))
```

---

pack\_minmax *Helper function to define packed data exports by min / max values*

---

### Description

This function can be used to define packed exports in [write\\_ncdf](#) and [write\\_tif](#). It will generate scale and offset values with maximum precision (unless simplify=TRUE).

### Usage

```
pack_minmax(type = "int16", min, max, simplify = FALSE)
```

**Arguments**

type	target data type of packed values (one of "uint8", "uint16", "uint32", "int16", or "int32")
min	numeric; minimum value(s) of original values, will be packed to the 2nd lowest value of the target data type
max	numeric; maximum value(s) in original scale, will be packed to the highest value of the target data type
simplify	logical; round resulting scale and offset to power of 10 values

**Details**

Nodata values will be mapped to the lowest value of the target data type.

Arguments min and max must have length 1 or length equal to the number of bands of the data cube to be exported. In the former case, the same values are used for all bands of the exported target cube, whereas the latter case allows to use different ranges for different bands.

**Note**

Using simplify=TRUE will round scale values to the next smaller power of 10.

**Examples**

```
ndvi_packing = pack_minmax(type="int16", min=-1, max=1)
ndvi_packing
```

---

plot.cube

*Plot a gdalcubes data cube*


---

**Description**

Plot a gdalcubes data cube

**Usage**

```
## S3 method for class 'cube'
plot(
  x,
  y,
  ...,
  nbreaks = 11,
  breaks = NULL,
  col = grey(1:(nbreaks - 1)/nbreaks),
  key.pos = NULL,
  bands = NULL,
  t = NULL,
```

```

    rgb = NULL,
    zlim = NULL,
    periods.in.title = TRUE,
    join.timeseries = FALSE,
    axes = TRUE,
    ncol = NULL,
    nrow = NULL,
    na.color = "#AAAAAA"
)

```

### Arguments

x	a data cube proxy object (class cube)
y	___not used___
...	further arguments passed to <code>image.default</code>
nbreaks	number of breaks, should be one more than the number of colors given
breaks	actual breaks used to assign colors to values; if missing, the function subsamples values and uses equally sized intervals between min and max or <code>zlim[0]</code> and <code>zlim[1]</code> if defined
col	color definition, can be a character vector with <code>nbreaks - 1</code> elements or a function such as <code>heat.colors</code>
key.pos	position for the legend, 1 (bottom), 2 (left), 3 (top), or 4 (right). If NULL (the default), do not plot a legend.
bands	integer vector with band numbers to plot (this must be band numbers, not band names)
t	integer vector with time indexes to plot (this must be time indexes, not date / time)
rgb	bands used to assign RGB color channels, vector of length 3 (this must be band numbers, not band names)
zlim	vector of length 2, defining the minimum and maximum values to either derive breaks, or define black and white values in RGB plots
periods.in.title	logical value, if TRUE, the title of plots includes the datetime period length as ISO 8601 string
join.timeseries	logical, for pure time-series plots, shall time series of multiple bands be plotted in a single plot (with different colors)?
axes	logical, if TRUE, plots include axes
ncol	number of columns for arranging plots with <code>layout()</code> , see Details
nrow	number of rows for arranging plots with <code>layout()</code> , see Details
na.color	color used to plot NA pixels



## Details

The style of the plot depends on provided parameters and on the shape of the cube, i.e., whether it is a pure time series and whether it contains multiple bands or not. Multi-band, multi-temporal images will be arranged with `layout()` such that bands are represented by the x axis and time is represented by the y axis. Time series plots can be combined to a single plot by setting `join.timeseries = TRUE`. For other cases, a default arrangement of the plots is derived, trying to reach a square overall plot. The layout can be controlled with `ncol` and `nrow`, which define the number of rows and columns in the plot layout. Typically, only one of `ncol` and `nrow` is provided. For multi-band, multi-temporal plots, the actual number of rows or columns can be less if the input cube has less bands or time slices.

## Note

If caching is enabled for the package (see [gdalcubes\\_options](#)), repeated calls of `plot` for the same data cube will not reevaluate the cube. Instead, the temporary result file will be reused, if possible.

Some parts of the function have been copied from the `stars` package (c) Edzer Pebesma

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

plot(select_bands(raster_cube(L8.col, v), c("B02", "B03", "B04")), rgb=3:1)

L8.cube = select_bands(raster_cube(L8.col, v), c("B04", "B05"))
L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")
plot(reduce_time(L8.ndvi, "median(NDVI)"), key.pos=1, zlim=c(0,1))
```

---

print.cube

*Print data cube information*

---

## Description

Prints information about the dimensions and bands of a data cube.

**Usage**

```
## S3 method for class 'cube'
print(x, ...)
```

**Arguments**

```
x          Object of class "cube"
...        Further arguments passed to the generic print function
```

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
print(raster_cube(L8.col, v))
```

---

```
print.cube_view      Print data cube view information
```

---

**Description**

Prints information about a data cube view, including its dimensions, spatial reference, aggregation method, and resampling method.

**Usage**

```
## S3 method for class 'cube_view'
print(x, ...)
```

**Arguments**

```
x          Object of class "cube_view"
...        Further arguments passed to the generic print function
```

**Examples**

```
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
print(v)
```

---

```
print.image_collection
      Print image collection information
```

---

**Description**

Prints information about images in an image collection.

**Usage**

```
## S3 method for class 'image_collection'
print(x, ..., n = 6)
```

**Arguments**

x	Object of class "image_collection"
...	Further arguments passed to the generic print function
n	Number of images for which details are printed

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
print(L8.col)
```

---

```
proj4      Query data cube properties
```

---

**Description**

Query data cube properties

**Usage**

```
proj4(obj)
```

**Arguments**

obj	a data cube proxy object (class cube)
-----	---------------------------------------

**Value**

The spatial reference system expressed as proj4 string

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
proj4(raster_cube(L8.col, v))
```

---

query\_points

*Query data cube values at irregular spatiotemporal points*


---

**Description**

This function will overlay provided spatiotemporal points with a data cube and return all band values of the cells for each query point, as a data.frame where rows correspond to points and columns represent bands. If needed, point coordinates are automatically transformed to the SRS of the data cube.

**Usage**

```
query_points(x, px, py, pt, srs)
```

**Arguments**

x	source data cube
px	vector of x coordinates
py	vector of y coordinates
pt	vector of date/ time coordinates
srs	spatial reference system string identifier (as GDAL understands)

**Details**

Date and time of the query points can be provided as vector of class character, Date, or POSIXct.

**Value**

a data.frame with one row per point and one column per data cube band or variable

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01-01", t1="2018-12-02"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P14D")
L8.cube = raster_cube(L8.col, v)
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))

x = seq(from = 388941.2, to = 766552.4, length.out = 10)
y = seq(from = 4345299, to = 4744931, length.out = 10)
t = seq(as.Date("2018-01-01"), as.Date("2018-12-02"), length.out = 10 )

query_points(L8.rgb, x, y, t, srs(L8.rgb))
```

---

query\_timeseries

*Query data cube timeseries at irregular spatial points*

---

## Description

This function will overlay provided spatial points with a data cube and return time series of all bands of the cells for each query point, as a list of data.frame (one data frame per band) where rows correspond to points and columns represent time. If needed, point coordinates are automatically transformed to the SRS of the data cube.

## Usage

```
query_timeseries(x, px, py, srs)
```

## Arguments

x	source data cube
px	vector of x coordinates
py	vector of y coordinates
srs	spatial reference system string identifier (as GDAL understands)

## Value

a list of data.frames (one per band / variable) with one row per point and one column per data cube time slice

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01-01", t1="2018-12-02"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P14D")
L8.cube = raster_cube(L8.col, v)
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))

x = seq(from = 388941.2, to = 766552.4, length.out = 10)
y = seq(from = 4345299, to = 4744931, length.out = 10)

query_timeseries(L8.rgb, x, y, srs(L8.rgb))
```

---

raster\_cube

*Create a data cube from an image collection*


---

## Description

Create a proxy data cube, which loads data from a given image collection according to a data cube view

## Usage

```
raster_cube(image_collection, view, mask = NULL, chunking = c(1, 256, 256))
```

## Arguments

image_collection	Source image collection as from <code>image_collection</code> or <code>create_image_collection</code>
view	A data cube view defining the shape (spatiotemporal extent, resolution, and spatial reference), if missing, a default overview is used
mask	mask pixels of images based on band values, see <a href="#">image_mask</a>
chunking	Vector of length 3 defining the size of data cube chunks in the order time, y, x.

## Details

The following steps will be performed when the data cube is requested to read data of a chunk:

1. Find images from the input collection that intersect with the spatiotemporal extent of the chunk
2. For all resulting images, apply `gdalwarp` to reproject, resize, and resample to an in-memory GDAL

dataset 3. Read the resulting data to the chunk buffer and optionally apply a mask on the result  
 4. Update pixel-wise aggregator (as defined in the data cube view) to combine values of multiple images within the same data cube pixels

### Value

A proxy data cube object

### Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

### Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
raster_cube(L8.col, v)

# using a mask on the Landsat quality bit band to filter out clouds
raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
```

---

raster\_cube\_dummy      *Create a dummy data cube with a fill value*

---

### Description

Create a data cube with a constant fill value for one or more bands from a data cube view. Use this cube for testing.

### Usage

```
raster_cube_dummy(view, nbands = 1, fill = 1, chunking = c(16, 256, 256))
```

**Arguments**

view	a data cube view defining the shape (spatiotemporal extent, resolution, and spatial reference)
nbands	number of bands
fill	fill value
chunking	vector of length 3 defining the size of data cube chunks in the order time, y, x.

**Value**

a proxy data cube object

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube_dummy(v, 1, 2.345)

plot(L8.cube, zlim=c(0,4))
```

---

read\_chunk\_as\_array *Read chunk data of a data cube from stdin or a file*

---

**Description**

This function can be used within function passed to [chunk\\_apply](#) in order to read a data cube chunk as a four-dimensional R array. It works only for R processes, which have been started from the gdalcubes C++ library. The resulting array has dimensions band, time, y, x (in this order).

**Usage**

```
read_chunk_as_array(with.dimnames = TRUE)
```

**Arguments**

with.dimnames if TRUE, the resulting array will contain dimnames with coordinates, datetime, and band names

**Value**

four-dimensional array



**Note**

Call this function **ONLY** from a function passed to `chunk_apply`.

This function only works in R sessions started from gdalcubes streaming.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
f <- function() {
  x <- read_chunk_as_array()
  out <- reduce_time(x, function(x) {
    cor(x[1,], x[2,], use="na.or.complete", method = "kendall")
  })
  write_chunk_from_array(out)
}
L8.cor = chunk_apply(L8.cube, f)
plot(L8.cor, zlim=c(0,1), key.pos=1)
```

---

 reduce\_space

*Reduce multidimensional data over space*


---

**Description**

This generic function applies a reducer function over a data cube, an R array, or other classes if implemented.

**Usage**

```
reduce_space(x, ...)
```

**Arguments**

`x` object to be reduced  
`...` further arguments passed to specific implementations

**Value**

return value and type depend on the class of x

**See Also**

[reduce\\_space.cube](#)

[reduce\\_space.array](#)

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
reduce_space(raster_cube(L8.col, v) , "median(B02)")

d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
y <- reduce_space(x, function(v) {
  apply(v, 1, mean)
})
```

---

reduce_space.array	<i>Apply a function over space and bands in a four-dimensional (band, time, y, x) array and reduce spatial dimensions</i>
--------------------	---

---

**Description**

Apply a function over space and bands in a four-dimensional (band, time, y, x) array and reduce spatial dimensions

**Usage**

```
## S3 method for class 'array'
reduce_space(x, FUN, ...)
```

**Arguments**

x	four-dimensional input array with dimensions band, time, y, x (in this order)
FUN	function which receives one spatial slice in a three-dimensional array with dimensions bands, y, x as input
...	further arguments passed to FUN

**Details**

FUN is expected to produce a numeric vector (or scalar) where elements are interpreted as new bands in the result.

**Note**

This is a helper function that uses the same dimension ordering as gdalcubes streaming. It can be used to simplify the application of R functions e.g. over spatial slices in a data cube.

**Examples**

```
d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
# reduce individual bands over spatial slices
y <- reduce_space(x, function(v) {
  apply(v, 1, mean)
})
dim(y)
```

---

reduce_space.cube	<i>Reduce a data cube over spatial (x,y or lat,lon) dimensions</i>
-------------------	--

---

**Description**

Create a proxy data cube, which applies one or more reducer functions to selected bands over spatial slices of a data cube

**Usage**

```
## S3 method for class 'cube'
reduce_space(x, expr, ..., FUN, names = NULL)
```

**Arguments**

x	source data cube
expr	either a single string, or a vector of strings defining which reducers will be applied over which bands of the input cube
...	optional additional expressions (if expr is not a vector)
FUN	a user-defined R function applied over pixel time series (see Details)
names	character vector; if FUN is provided, names can be used to define the number and name of output bands

**Details**

Notice that expressions have a very simple format: the reducer is followed by the name of a band in parantheses. You cannot add more complex functions or arguments.

Possible reducers currently are "min", "max", "sum", "prod", "count", "mean", "median", "var", "sd".

**Value**

proxy data cube object

**Note**

Implemented reducers will ignore any NAN values (as na.rm=TRUE does).

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

L8.cube = raster_cube(L8.col, v)
L8.b02 = select_bands(L8.cube, c("B02"))
L8.b02.median = reduce_space(L8.b02, "median(B02)")
L8.b02.median

plot(L8.b02.median, key.pos=1)
```

---

reduce\_time

*Reduce multidimensional data over time*

---

**Description**

This generic function applies a reducer function over a data cube, an R array, or other classes if implemented.

**Usage**

```
reduce_time(x, ...)
```

**Arguments**

```
x          object to be reduced
...        further arguments passed to specific implementations
```

**Value**

return value and type depend on the class of x

**See Also**

[reduce\\_time.cube](#)  
[reduce\\_time.array](#)

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
reduce_time(raster_cube(L8.col, v) , "median(B02)", "median(B03)", "median(B04)")

d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
y <- reduce_time(x, function(v) {
  apply(v, 1, mean)
})
```

---

reduce_time.array	<i>Apply a function over time and bands in a four-dimensional (band, time, y, x) array and reduce time dimension</i>
-------------------	--

---

**Description**

Apply a function over time and bands in a four-dimensional (band, time, y, x) array and reduce time dimension

**Usage**

```
## S3 method for class 'array'
reduce_time(x, FUN, ...)
```

**Arguments**

x	four-dimensional input array with dimensions band, time, y, x (in this order)
FUN	function which receives one time series in a two-dimensional array with dimensions bands, time as input
...	further arguments passed to FUN

**Details**

FUN is expected to produce a numeric vector (or scalar) where elements are interpreted as new bands in the result.

**Note**

This is a helper function that uses the same dimension ordering as `gdalcubes` streaming. It can be used to simplify the application of R functions e.g. over time series in a data cube.

**Examples**

```
d <- c(4,16,32,32)
x <- array(rnorm(prod(d)), d)
# reduce individual bands over pixel time series
y <- reduce_time(x, function(v) {
  apply(v, 1, mean)
})
dim(y)
```

---

```
reduce_time.cube
```

*Reduce a data cube over the time dimension*

---

**Description**

Create a proxy data cube, which applies one or more reducer functions to selected bands over pixel time series of a data cube

**Usage**

```
## S3 method for class 'cube'
reduce_time(x, expr, ..., FUN, names = NULL)
```

**Arguments**

x	source data cube
expr	either a single string, or a vector of strings defining which reducers will be applied over which bands of the input cube
...	optional additional expressions (if expr is not a vector)
FUN	a user-defined R function applied over pixel time series (see Details)
names	character vector; if FUN is provided, names can be used to define the number and name of output bands

**Details**

The function can either apply a built-in reducer if `expr` is given, or apply a custom R reducer function if `FUN` is provided.

In the former case, notice that expressions have a very simple format: the reducer is followed by the name of a band in parentheses. You cannot add more complex functions or arguments. Possible reducers currently are "min", "max", "sum", "prod", "count", "mean", "median", "var", "sd", "which\_min", and "which\_max".

User-defined R reducer functions receive a two-dimensional array as input where rows correspond to the band and columns represent the time dimension. For example, one row is the time series of a specific band. `FUN` should always return a numeric vector with the same number of elements, which will be interpreted as bands in the result cube. Notice that it is recommended to specify the names of the output bands as a character vector. If names are missing, the number and names of output bands is tried to be derived automatically, which may fail in some cases.

**Value**

proxy data cube object

**Note**

Implemented reducers will ignore any NAN values (as `na.rm=TRUE` does)

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-06"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
```

```

L8.cube = raster_cube(L8.col, v)
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.rgb.median = reduce_time(L8.rgb, "median(B02)", "median(B03)", "median(B04)")
L8.rgb.median

plot(L8.rgb.median, rgb=3:1)

# user defined reducer calculating interquartile ranges
L8.rgb.iqr = reduce_time(L8.rgb, names=c("iqr_R", "iqr_G", "iqr_B"), FUN = function(x) {
  c(diff(quantile(x[["B04"],],c(0.25,0.75), na.rm=TRUE)),
    diff(quantile(x[["B03"],],c(0.25,0.75), na.rm=TRUE)),
    diff(quantile(x[["B02"],],c(0.25,0.75), na.rm=TRUE)))
})
L8.rgb.iqr

plot(L8.rgb.iqr, key.pos=1)

```

---

 rename\_bands

*Rename bands of a data cube*


---

## Description

Create a proxy data cube, which renames specific bands of a data cube.

## Usage

```
rename_bands(cube, ...)
```

## Arguments

cube	source data cube
...	named arguments with bands that will be renamed, see Details

## Details

The result data cube always contains the same number of bands. No subsetting is done if only names for some of the bands are provided. In this case, only provided bands are renamed whereas other bands keep their original name. Variable arguments must be named by the old band name and the new names must be provided as simple character values (see example).

## Value

proxy data cube object



**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-07"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.rgb
L8.rgb = rename_bands(L8.cube, B02 = "blue", B03 = "green", B04 = "red")
L8.rgb
```

---

select\_bands

*Select bands of a data cube*

---

**Description**

Create a proxy data cube, which selects specific bands of a data cube. The resulting cube will drop any other bands.

**Usage**

```
select_bands(cube, bands)
```

**Arguments**

cube	source data cube
bands	character vector with band names

**Value**

proxy data cube object

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

For performance reasons, `select_bands` should always be called directly on a cube created with `raster_cube` and drop all unneeded bands. This allows to reduce RasterIO and warp operations in GDAL.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-07"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.rgb

plot(L8.rgb, rgb=3:1)
```

---

 select\_time

*Select time slices of a data cube*


---

**Description**

Create a proxy data cube, which selects specific time slices of a data cube. The time dimension of the resulting cube will be irregular / labeled.

**Usage**

```
select_time(cube, t)
```

**Arguments**

cube	source data cube
t	character vector with date/time

**Value**

proxy data cube object

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-04", t1="2018-07"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.rgb = select_time(L8.rgb, c("2018-04", "2018-07"))
L8.rgb

plot(L8.rgb, rgb=3:1)
```

---

size

*Query data cube properties*


---

**Description**

Query data cube properties

**Usage**

```
size(obj)
```

**Arguments**

obj                    a data cube proxy object (class cube)

**Value**

size of a data cube (number of cells) as integer vector in the order t, y, x

**See Also**

[dim.cube](#)

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
size(raster_cube(L8.col, v))
```

---

 slice\_space

---

*Extract a single time series (spatial slice) from a data cube*


---

**Description**

Create a proxy data cube, which extracts a time series from a data cube defined by spatial coordinates or integer x and y indexes.

**Usage**

```
slice_space(cube, loc = NULL, i = NULL)
```

**Arguments**

cube	source data cube
loc	numeric length-two vector; spatial coordinates (x, y) of the time series, expressed in the coordinate reference system of the source data cube
i	integer length-2 vector; indexes (x,y) of the time slice (zero-based)

**Details**

Either loc or i must be non-NULL. If both arguments are provided, integer indexes i are ignored.

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P3M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.ts = slice_space(L8.rgb, loc = c(5e05, 4400000))
L8.ts

plot(L8.ts, join.timeseries = TRUE)
```

---

 slice\_time

*Extract a single time slice from a data cube*


---

**Description**

Create a proxy data cube, which extracts a time slice from a data cube defined by label (datetime string) or integer index.

**Usage**

```
slice_time(cube, datetime = NULL, it = NULL)
```

**Arguments**

cube	source data cube
datetime	character; datetime string of the time slice
it	integer; index of the time slice (zero-based)

**Details**

Either datetime or it must be non-NULL. If both arguments are provided, the integer index it is ignored.

**Note**

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M", aggregation = "median")
L8.cube = raster_cube(L8.col, v, mask=image_mask("BQA", bits=4, values=16))
L8.rgb = select_bands(L8.cube, c("B02", "B03", "B04"))
L8.slice = slice_time(L8.rgb, "2018-03")
L8.slice

plot(L8.slice, rgb=3:1, zlim=c(5000,12000))
```

---

srs

*Query data cube properties*

---

## Description

Query data cube properties

## Usage

```
srs(obj)
```

## Arguments

obj                    a data cube proxy object (class cube)

## Value

The spatial reference system expressed as a string readable by GDAL

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}
```

```

}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                        bottom=4345299, top=4744931, t0="2018-04", t1="2018-06"),
             srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
srs(raster_cube(L8.col, v))

```

---

stack_cube	<i>Create a data cube from a set of images with the same spatial extent and spatial reference system</i>
------------	--

---

### Description

Create a spatiotemporal data cube directly from images with identical spatial extent and spatial reference system, similar to a raster stack with an additional dimension supporting both, time and multiple bands / variables.

### Usage

```

stack_cube(
  x,
  datetime_values,
  bands = NULL,
  band_names = NULL,
  chunking = c(1, 256, 256),
  dx = NULL,
  dy = NULL
)

```

### Arguments

x	character vector where items point to image files
datetime_values	vector of type character, Date, or POSIXct with recording date of images
bands	optional character vector defining the band or spectral band of each item in x, if files relate to different spectral bands or variables
band_names	name of bands, only used if bands is NULL, i.e., if all files contain the same spectral band(s) / variable(s)
chunking	vector of length 3 defining the size of data cube chunks in the order time, y, x.
dx	optional target pixel size in x direction, by default (NULL) the original or highest resolution of images is used
dy	optional target pixel size in y direction, by default (NULL) the original or highest resolution of images is used

## Details

This function creates a four-dimensional (space, time, bands / variables) raster data cube from a set of provided files without the need to create an image collection before. This is possible if all images have the same spatial extent and spatial reference system and can be used for two different file organizations:

1. If all image files share the same bands / variables, the bands argument can be ignored (default NULL) can names of the bands can be specified using the band\_names argument.
2. If image files represent different band / variable (e.g. individual files for red, green, and blue channels), the bands argument must be used to define the corresponding band / variable. Notice that in this case all files are expected to represent exactly one variable / band at one point in datetime. It is not possible to combine files with different numbers of variables / bands. If image files for different bands have different pixel sizes, the smallest size is used by default.

Notice that to avoid opening all image files in advance, no automatic check whether all images share the spatial extent and spatial reference system is performed.

## Value

A proxy data cube object

## Note

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

## Examples

```
# toy example, repeating the same image as a daily time series
L8_file_nir <-
system.file("L8NY18/LC08_L1TP_014032_20181122_20181129_01_T1/LC08_L1TP_014032_20181122_B5.TIF",
           package = "gdalcubes")
files = rep(L8_file_nir, 10)
datetime = as.Date("2018-11-22") + 1:10
stack_cube(files, datetime, band_names = "B05")

# using a second band from different files
L8_file_red <-
system.file("L8NY18/LC08_L1TP_014032_20181122_20181129_01_T1/LC08_L1TP_014032_20181122_B4.TIF",
           package = "gdalcubes")
files = rep(c(L8_file_nir, L8_file_red), each = 10)
datetime = rep(as.Date("2018-11-22") + 1:10, 2)
bands = rep(c("B5", "B4"), each = 10)
stack_cube(files, datetime, bands = bands)
```



---

stac\_image\_collection *Create an image collection from a STAC feature collection*

---

## Description

This function creates an image collection from a STAC API collection response. It does not need to read any image data. Additionally, bands can be filtered and asset links can be transformed to make them readable for GDAL.

## Usage

```
stac_image_collection(
  s,
  out_file = tempfile(fileext = ".sqlite"),
  asset_names = NULL,
  asset_regex = NULL,
  url_fun = function(x) { paste0("/vsicurl/", x) },
  property_filter = NULL,
  skip_image_metadata = FALSE
)
```

## Arguments

s	STAC feature collection
out_file	optional name of the output SQLite database file, defaults to a temporary file
asset_names	character vector with names of assets (e.g., bands) to be used, other assets will be ignored. By default (NULL), all asset names with "eo:bands" attributes will be used
asset_regex	length 1 character defining a regular expression asset names must match to be considered
url_fun	optional function to modify URLs of assets, e.g, to add /vsicurl/ to URLs (the default)
property_filter	optional function to filter STAC items (images) by their properties; see Details
skip_image_metadata	logical, if TRUE per-image metadata (STAC item properties) will not be added to the image collection

## Details

The `property_filter` argument can be used to filter images by metadata such as cloud coverage. The function receives all properties of a STAC item (image) as input list and is expected to produce a single logical value, where an image will be ignored if the function returns FALSE.

**Note**

Currently, bbox results are expected to be WGS84 coordinates, even if bbox-crs is given in the STAC response.

This function is experimental.

---

st_as_stars.cube	<i>Coerce gdalcubes object into a stars object</i>
------------------	--

---

**Description**

The function materializes a data cube as a temporary netCDF file and loads the file with the stars package.

**Usage**

```
st_as_stars.cube(.x, ...)
```

**Arguments**

.x	data cube object to coerce
...	not used

**Value**

stars object

**Examples**

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-04"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
if(require("stars"))
  st_as_stars(select_bands(raster_cube(L8.col, v), c("B04", "B05")))
```

---

window_time	<i>Apply a moving window operation over time</i>
-------------	--

---

### Description

This generic function applies a reducer function over a moving window over the time dimension of a data cube, an R array, or other classes if implemented.

### Usage

```
window_time(x, ...)
```

### Arguments

x	object to be reduced
...	further arguments passed to specific implementations

### Value

value and type depend on the class of x

### See Also

[window\\_time.cube](#)

### Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-07"),
  srs="EPSG:32618", nx = 400, dt="P1M")
L8.cube = raster_cube(L8.col, v)
L8.nir = select_bands(L8.cube, c("B05"))
window_time(L8.nir, window = c(2,2), "min(B05)")
window_time(L8.nir, kernel=c(-1,1), window=c(1,0))

plot(window_time(L8.nir, kernel=c(-1,1), window=c(1,0)), key.pos=1)
```

---

window_time.cube	<i>Apply a moving window function over the time dimension of a data cube</i>
------------------	--

---

### Description

Create a proxy data cube, which applies one or more moving window functions to selected bands over pixel time series of a data cube. The function can either use a predefined aggregation function or apply a custom convolution kernel.

### Usage

```
## S3 method for class 'cube'
window_time(x, expr, ..., kernel, window)
```

### Arguments

x	source data cube
expr	either a single string, or a vector of strings defining which reducers will be applied over which bands of the input cube
...	optional additional expressions (if expr is not a vector)
kernel	numeric vector with elements of the kernel
window	integer vector with two elements defining the size of the window before and after a cell, the total size of the window is window[1] + 1 + window[2]

### Details

The function either applies a kernel convolution (if the kernel argument is provided) or a general reducer function over moving temporal windows. In the former case, the kernel convolution will be applied over all bands of the input cube, i.e., the output cube will have the same number of bands as the input cubes. If a kernel is given and the window argument is missing, the window will be symmetric to the center pixel with the size of the provided kernel. For general reducer functions, the window argument must be provided and several expressions can be used to create multiple bands in the output cube.

Notice that expressions have a very simple format: the reducer is followed by the name of a band in parentheses. You cannot add more complex functions or arguments.

Possible reducers currently are "min", "max", "sum", "prod", "count", "mean", "median".

### Value

proxy data cube object

### Note

Implemented reducers will ignore any NAN values (as na.rm=TRUE does).

This function returns a proxy object, i.e., it will not start any computations besides deriving the shape of the result.

**Examples**

```

# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-01", t1="2018-07"),
              srs="EPSG:32618", nx = 400, dt="P1M")

L8.cube = raster_cube(L8.col, v)
L8.nir = select_bands(L8.cube, c("B05"))
L8.nir.min = window_time(L8.nir, window = c(2,2), "min(B05)")
L8.nir.min

L8.nir.kernel = window_time(L8.nir, kernel=c(-1,1), window=c(1,0))
L8.nir.kernel

```

---

```
write_chunk_from_array
```

*Write chunk data of a cube to stdout or a file*

---

**Description**

This function can be used within function passed to [chunk\\_apply](#) in order to pass four-dimensional R arrays as a data cube chunk to the gdalcubes C++ library. It works only for R processes, which have been started from the gdalcubes C++ library. The input array must have dimensions band, time, y, x (in this order).

**Usage**

```
write_chunk_from_array(v)
```

**Arguments**

`v` four-dimensional array with dimensions band, time, y, and x

**Note**

Call this function ONLY from a function passed to [chunk\\_apply](#).

This function only works in R sessions started from gdalcubes streaming.

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-01", t1="2018-12"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")

L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
f <- function() {
  x <- read_chunk_as_array()
  out <- reduce_time(x, function(x) {
    cor(x[1,], x[2,], use="na.or.complete", method = "kendall")
  })
  write_chunk_from_array(out)
}
L8.cor = chunk_apply(L8.cube, f)
plot(L8.cor, zlim=c(0,1), key.pos=1)
```

---

write\_ncdf

*Export a data cube as netCDF file(s)*

---

## Description

This function will read chunks of a data cube and write them to a single (the default) or multiple (if chunked = TRUE) netCDF file(s). The resulting file(s) uses the enhanced netCDF-4 format, supporting chunking and compression.

## Usage

```
write_ncdf(
  x,
  fname = tempfile(pattern = "gdalcubes", fileext = ".nc"),
  overwrite = FALSE,
  write_json_descr = FALSE,
  with_VRT = FALSE,
  pack = NULL,
  chunked = FALSE
)
```

## Arguments

x	a data cube proxy object (class cube)
fname	output file name
overwrite	logical; overwrite output file if it already exists
write_json_descr	logical; write a JSON description of x as additional file
with_VRT	logical; write additional VRT datasets (one per time slice)
pack	reduce output file size by packing values (see Details), defaults to no packing
chunked	logical; if TRUE, write one netCDF file per chunk; defaults to FALSE

## Details

The resulting netCDF file(s) contain three dimensions (t, y, x) and bands as variables.

If `write_json_descr` is TRUE, the function will write an addition file with the same name as the NetCDF file but ".json" suffix. This file includes a serialized description of the input data cube, including all chained data cube operations.

To reduce the size of created files, values can be packed by applying a scale factor and an offset value and using a smaller integer data type for storage (only supported if `chunked = TRUE`). The `pack` argument can be either NULL (the default), or a list with elements `type`, `scale`, `offset`, and `nodata`. `type` can be any of "uint8", "uint16", "uint32", "int16", or "int32". `scale`, `offset`, and `nodata` must be numeric vectors with length one or length equal to the number of data cube bands (to use different values for different bands). The helper function [pack\\_minmax](#) can be used to derive offset and scale values with maximum precision from minimum and maximum data values on original scale.

If `chunked = TRUE`, names of the produced files will start with `name` (with removed extension), followed by an underscore and the internal integer chunk number.

## Value

returns (invisibly) the path of the created netCDF file(s)

## Note

Packing is currently ignored if `chunked = TRUE`

## See Also

<https://www.unidata.ucar.edu/software/netcdf/docs/>

[gdalcubes\\_options](#)

[pack\\_minmax](#)

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
    ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
  bottom=4345299, top=4744931, t0="2018-04", t1="2018-04"),
  srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
write_ncdf(select_bands(raster_cube(L8.col, v), c("B04", "B05")), fname=tempfile(fileext = ".nc"))
```

---

write\_tif

*Export a data cube as a collection of GeoTIFF files*

---

## Description

This function will time slices of a data cube as GeoTIFF files in a given directory.

## Usage

```
write_tif(
  x,
  dir = tempfile(pattern = ""),
  prefix = basename(tempfile(pattern = "cube_")),
  overviews = FALSE,
  COG = FALSE,
  rsmpl_overview = "nearest",
  creation_options = NULL,
  write_json_descr = FALSE,
  pack = NULL
)
```

## Arguments

x	a data cube proxy object (class cube)
dir	destination directory
prefix	output file name
overviews	logical; generate overview images
COG	logical; create cloud-optimized GeoTIFF files (forces overviews=TRUE)
rsmpl_overview	resampling method for overviews (image pyramid) generation (see <a href="https://gdal.org/programs/gdaladdo.html">https://gdal.org/programs/gdaladdo.html</a> for available methods)



creation_options	additional creation options for resulting GeoTIFF files, e.g. to define compression (see <a href="https://gdal.org/drivers/raster/gtiff.html#creation-options">https://gdal.org/drivers/raster/gtiff.html#creation-options</a> )
write_json_descr	logical; write a JSON description of x as additional file
pack	reduce output file size by packing values (see Details), defaults to no packing

## Details

If `write_json_descr` is TRUE, the function will write an additional file with name according to prefix (if not missing) or simply `cube.json`. This file includes a serialized description of the input data cube, including all chained data cube operations.

Additional GDAL creation options for resulting GeoTIFF files must be passed as a named list of simple strings, where element names refer to the key. For example, `creation_options = list("COMPRESS" = "DEFLATE", "ZLEVEL" = "5")` would enable deflate compression at level 5.

To reduce the size of created files, values can be packed by applying a scale factor and an offset value and using a smaller integer data type for storage. The `pack` argument can be either NULL (the default), or a list with elements `type`, `scale`, `offset`, and `nodata`. `type` can be any of "uint8", "uint16", "uint32", "int16", or "int32". `scale`, `offset`, and `nodata` must be numeric vectors with length one or length equal to the number of data cube bands (to use different values for different bands). The helper function `pack_minmax` can be used to derive offset and scale values with maximum precision from minimum and maximum data values on original scale.

If `overviews=TRUE`, the numbers of pixels are halved until the longer spatial dimensions counts less than 256 pixels. Setting `COG=TRUE` automatically sets `overviews=TRUE`.

## Value

returns (invisibly) a vector of paths pointing to the created GeoTIFF files

## See Also

[pack\\_minmax](#)

## Examples

```
# create image collection from example Landsat data only
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}

L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931, t0="2018-04", t1="2018-04"),
              srs="EPSG:32618", nx = 497, ny=526, dt="P1M")
write_tif(select_bands(raster_cube(L8.col, v), c("B04", "B05")), dir=)
```

---

zonal\_statistics      *Query summary statistics of data cube values over polygons*

---

### Description

This function will overlay spatial polygons with a data cube and compute summary statistics of pixel values within the polygons over all time slices.

### Usage

```
zonal_statistics(
  x,
  geom,
  expr,
  out_path = tempfile(fileext = ".gpkg"),
  overwrite = FALSE,
  ogr_layer = NULL,
  as_stars = FALSE,
  stars_use_intervals = FALSE
)
```

### Arguments

x	source data cube
geom	Either an sf object, or a path to an OGR dataset (Shapefile, GeoPackage, or similar) with input (multi)polygon geometries
expr	character vector of summary statistics expressions, describing pairs of aggregation functions and data cube bands (e.g. "mean(band1)")
out_path	path to where resulting GeoPackage will be written to
overwrite	logical; overwrite out_path if file already exists, defaults to FALSE
ogr_layer	If the input OGR dataset has multiple layers, a layer can be chosen by name
as_stars	logical; if TRUE, the created gpkg file will be loaded as a stars vector data cube
stars_use_intervals	logical; if TRUE, time dimension of a resulting stars object includes time intervals, otherwise the start date/time of pixels is used as time labels

### Details

The function creates a single GeoPackage output file containing:

- A single layer "geom" containing the geometries (and feature identifiers) only.
- Attribute tables (layers without geometry) for each time slice of the data cube containing summary statistics as columns. Corresponding layer names start with "attr\_", followed by date and time.

- Virtual spatial views for each time slice, joining the geometries and attribute tables. Corresponding layer names start with "map\_", followed by date and time.

You will most-likely want to use the spatial view layers directly e.g. with the sf package.

Available summary statistics currently include "min", "max", "mean", "median", "count", "sum", "prod", "var", and "sd".

### Value

character length-one vector containing the path to the resulting GeoPackage file (see Details) or a stars object (if as\_stars is TRUE)

### Note

This function requires GDAL with built-in GEOS support, which can be checked with [gdalcubes\\_gdal\\_has\\_geos\(\)](#)

### Examples

```
# if not already done in other examples
if (!file.exists(file.path(tempdir(), "L8.db"))) {
  L8_files <- list.files(system.file("L8NY18", package = "gdalcubes"),
                        ".TIF", recursive = TRUE, full.names = TRUE)
  create_image_collection(L8_files, "L8_L1TP", file.path(tempdir(), "L8.db"))
}
L8.col = image_collection(file.path(tempdir(), "L8.db"))
v = cube_view(srs="EPSG:32618", dy=300, dx=300, dt="P1M",
              aggregation = "median", resampling = "bilinear",
              extent=list(left=388941.2, right=766552.4,
                          bottom=4345299, top=4744931,
                          t0="2018-01-01", t1="2018-04-30"))
L8.cube = raster_cube(L8.col, v)
L8.cube = select_bands(L8.cube, c("B04", "B05"))
L8.ndvi = apply_pixel(L8.cube, "(B05-B04)/(B05+B04)", "NDVI")
L8.ndvi

# toy example: overlay NDVI data with NYC districts
if (gdalcubes_gdal_has_geos()) {
  x = zonal_statistics(L8.ndvi, system.file("nycd.gpkg", package = "gdalcubes"),
                      expr = "median(NDVI)")
  x
}
```

# Index

.copy\_cube, 4  
[.cube (gdalcubes\_selection), 35  
\$.cube (gdalcubes\_selection), 35

add\_collection\_format, 4  
add\_images, 5  
aggregate\_time, 6  
animate, 7  
apply\_pixel, 8  
apply\_pixel.array, 9, 9  
apply\_pixel.cube, 9, 10  
apply\_time, 12  
apply\_time.array, 12, 13  
apply\_time.cube, 12, 14  
as\_array, 15  
as\_json, 16

bands, 17

chunk\_apply, 18, 56, 57, 77  
collection\_formats, 19, 20  
create\_image\_collection, 20, 38  
crop, 21  
cube\_view, 23

dim.cube, 25, 67  
dimension\_bounds, 27  
dimension\_values, 27  
dimensions, 26

extent, 23, 24, 28

fill\_time, 29  
filter\_geom, 30  
filter\_pixel, 31

gdalcubes, 32  
gdalcubes\_gdal\_has\_geos, 34, 83  
gdalcubes\_gdalformats, 33  
gdalcubes\_gdalversion, 33  
gdalcubes\_options, 34, 49, 79

gdalcubes\_selection, 35  
gdalcubes\_version, 37

image\_collection, 38  
image\_mask, 38, 54

join\_bands, 40

memsizes, 41

names.cube, 42  
nbands, 42  
ncdf\_cube, 43  
nt, 44  
nx, 45  
ny, 46

pack\_minmax, 46, 79, 81  
plot.cube, 8, 47  
print.cube, 49  
print.cube\_view, 50  
print.image\_collection, 51  
proj4, 51

query\_points, 52  
query\_timeseries, 53

raster\_cube, 5, 18, 21, 38, 54, 66  
raster\_cube\_dummy, 55  
read\_chunk\_as\_array, 56  
reduce\_space, 57  
reduce\_space.array, 58, 58  
reduce\_space.cube, 58, 59  
reduce\_time, 14, 60  
reduce\_time.array, 61, 61  
reduce\_time.cube, 61, 62  
rename\_bands, 64

select\_bands, 65  
select\_time, 66  
size, 25, 67

slice\_space, [68](#)  
slice\_time, [69](#)  
srs, [70](#)  
st\_as\_stars.cube, [74](#)  
st\_bbox, [36](#)  
st\_sfc, [36](#)  
stac\_image\_collection, [73](#)  
stack\_cube, [71](#)  
  
window\_time, [75](#)  
window\_time.cube, [75](#), [76](#)  
write\_chunk\_from\_array, [77](#)  
write\_ncdf, [43](#), [46](#), [78](#)  
write\_tif, [46](#), [80](#)  
  
zonal\_statistics, [82](#)