

Package ‘gqlr’

December 2, 2019

Title 'GraphQL' Server in R

Version 0.0.2

Description Server implementation of 'GraphQL' <<http://graphql.github.io/graphql-spec/>>, a query language originally created by Facebook for describing data requirements on complex application data models. Visit <<http://graphql.org>> to learn more about 'GraphQL'.

Depends R (>= 3.2.2)

License MIT + file LICENSE

URL <https://github.com/schloerke/gqlr>,
<http://graphql.github.io/graphql-spec/>, <http://graphql.org>

BugReports <https://github.com/schloerke/gqlr/issues>

LazyData true

Imports graphql (>= 1.3), magrittr, pryr, R6, jsonlite

Suggests plumber, roxygen2 (>= 7.0.0), testthat

RoxygenNote 7.0.1

Encoding UTF-8

Collate 'AAA-utils.R' 'R6--aaa-utils.R' 'S3--aaa-setup.R'
'R6--definition.R' 'R6-3.1.1-types-scalars.R'
'R6-6.1-executing-requests.R' 'R6-Schema.R' 'R6z-from-json.R'
'graphql_json.R' 'R6-3.2-directives.R' 'gqlr_schema.R'
'R6-4-introspection.R' 'R6-6.2-executing-operations.R'
'R6-6.3-executing-selection-sets.R' 'R6-6.4-executing-fields.R'
'R6-7-response.R' 'R6-ErrorList.R' 'R6-ObjectHelpers.R'
'R6-Result.R' 'R6-VariableValidationHelper.R'
'S3-3.1.2.3-validation-object-type.R' 'S3-str.R'
'gqlr-package.R' 'server.R' 'upgrade_query_remove_fragments.R'
'validation-arguments.R' 'validation-input-coercion.R'
'validation-selection-set-can-merge.R' 'validation-query.R'
'zzz.R'

NeedsCompilation no

Author Barret Schloerke [aut, cre],
 Ryan Hafen [ths],
 GraphQL [cph] (<http://graphql.github.io/graphql-spec/>)

Maintainer Barret Schloerke <schloerke@gmail.com>

Repository CRAN

Date/Publication 2019-12-02 16:20:03 UTC

R topics documented:

as_R6	2
ErrorList	3
execute_request	4
gqlr_schema	6
parse_ast	11
Schema	12
server	13
Index	15

as_R6

As R6

Description

Debug method that strips all gqlr classes and assigns the class as 'R6'

Usage

```
as_R6(x)
```

Arguments

x any object. If it inherits 'R6', then the class of x is set to 'R6'

Examples

```
Int <- getFromNamespace("Int", "gqlr")$clone()
print(Int)
print(as_R6(Int))
```

ErrorList
ErrorList

Description

Handles all errors that occur during query validation. This object is returned from execute request function (`ans <-execute_request(query, schema)`) under the field 'error_list' (`ans$error_list`).

Usage

```
answer <- execute_request(my_request, my_schema)
answer$error_list
```

Initialize

verbose boolean that determines if errors will be printed on occurrence. Defaults to TRUE

Details

`$n` count of errors received

`$errors` list of error information

`$verbose` boolean that determines if errors are printed when received

`$has_no_errors()` helper method to determine if there are no errors

`$has_any_errors()` helper method to determine if there are any errors

`$get_sub_source(loc)` helper method to display a subsection of source text given Location information

`$add(rule_code, ...)` add a new error according to the rule_code provided. Remaining arguments are passed directly to `paste(..., sep = "")` with extra error rule information

`$.format(...)` formats the error list into user friendly text. Remaining arguments are ignored

`$print(...)` prints the error list by calling `self$format(...)`

Examples

```
error_list <- ErrorList$new()
error_list
error_list$has_any_errors() # FALSE
error_list$has_no_errors() # TRUE

error_list$add("3.1.1", "Multiple part", " error about Scalars")
error_list
error_list$has_any_errors() # TRUE
error_list$has_no_errors() # FALSE
```

execute_request	<i>Execute GraphQL server response</i>
-----------------	--

Description

Executes a GraphQL server request with the provided request.

Usage

```
execute_request(  
  request,  
  schema,  
  operation_name = NULL,  
  variables = list(),  
  initial_value = NULL  
)
```

Arguments

request	a valid GraphQL string
schema	a character string (to be used along side <code>initial_value</code>) or a schema object created from <code>gqlr_schema</code>
operation_name	name of request operation to execute. If not value is provided it will use the operation in the request string. If more than one operations exist, an error will be produced. See <code>https://graphql.github.io/graphql-spec/October2016/#GetOperation()</code>
variables	a named list containing variable values. <code>https://graphql.github.io/graphql-spec/October2016/#sec-Language.Variables</code>
initial_value	default value for executing requests. This value can either be provided and/or combined with the resolve method of the query root type or mutation root type. The value provided should be a named list of the field name (key) and a value matching that field name type. The value may be a function that returns a value of the field name type.

References

[`https://graphql.github.io/graphql-spec/October2016/#sec-Execution`](https://graphql.github.io/graphql-spec/October2016/#sec-Execution)

Examples

```
# bare bones  
schema <- gqlr_schema("  
  type Person {  
    name: String  
    friends: [Person]  
  }  
)
```

```

    schema {
      query: Person
    }
  ")

data <- list(
  name = "Barret",
  friends = list(
    list(name = "Ryan", friends = list(list(name = "Bill"), list(name = "Barret"))),
    list(name = "Bill", friends = list(list(name = "Ryan")))
  )
)

ans <- execute_request("{ name }", schema, initial_value = data)
ans$sas_json()

execute_request("
{
  name
  friends {
    name
    friends {
      name
      friends {
        name
      }
    }
  }
}",
schema,
initial_value = data
)$sas_json()

# Using resolve method to help with recursion
people <- list(
  "id_Barret" = list(name = "Barret", friends = list("id_Ryan", "id_Bill")),
  "id_Ryan" = list(name = "Ryan", friends = list("id_Barret", "id_Bill")),
  "id_Bill" = list(name = "Bill", friends = list("id_Ryan"))
)
schema <- gqlr_schema("
  type Person {
    name: String
    friends: [Person]
  }
  schema {
    query: Person
  }
",

```

```

Person = list(
  resolve = function(name, schema, ...) {
    if (name %in% names(people)) {
      people[[name]]
    } else {
      NULL
    }
  }
)
)
)

ans <- execute_request("{ name }", schema, initial_value = "id_Barret")
ans$as_json()

execute_request(
  {
    name
    friends {
      name
      friends {
        name
        friends {
          name
        }
      }
    }
  },
  schema,
  initial_value = "id_Barret"
)$as_json()

```

gqlr_schema

Create Schema definitions

Description

Creates a Schema object from the defined GraphQL string and inserts the provided descriptions, resolve methods, resolve_type methods into the appropriate place.

Usage

```
gqlr_schema(schema, ...)
```

Arguments

schema	GraphQL schema string or Schema object
...	named lists of information to help produce the schema definition. See Details

Details

The ... should be named arguments whose values are lists of information. What information is needed for each type is described below.

ScalarTypeDefinition:

resolve function with two parameters: *x* (the raw to be parsed, such as 5.0) and *schema* (the full Schema definition). Should return a parsed value

description (optional) single character value that describes the Scalar definition

parse_ast (optional) function with two parameters: *obj* (a GraphQL wrapped raw value, such as an object of class IntValue with value 5) and *schema* (the full Schema definition). If the function returns NULL then the AST could not be parsed.

EnumTypeDefinition:

resolve (optional) function with two parameters: *x* and *schema* (the full Schema definition). Should return the value *x* represents, such as the Star Wars Episode enum value "4" could represent Episode "NEWHOPE". By default, EnumTypeDefinitions will return the current value.

description (optional) single character value that describes the Enum definition

values (optional) named list of enum value descriptions. Such as `values = list(ENUMA = "description for ENUMA", ENUMZ = "description for ENUMZ")`

ObjectTypeDefinition:

resolve function with two parameters: *x* (place holder value to be expanded into a named list) and *schema* (the full Schema definition). By using the resolve method, recursive relationships, such as friends, can easily be handled. The resolve function should return a fully named list of all the fields the definition defines. Missing fields are automatically interpreted as NULL.

Values in the returned list may be a function of the form `function(obj,args,schema) { . . . }`. This allows for fields to be determined dynamically and lazily. See how `add_human` makes a field for `totalCredits`, while the `add_droid` pre computes the information.

description (optional) single character value that describes the object

fields (optional) named list of field descriptions. Such as `fields = list(fieldA = "description for field A", fieldB = "description for field B")`

InterfaceTypeDefinition and UnionTypeDefinition:

resolve_type function with two parameters: *x* (a pre-resolved object value) and *schema* (the full Schema definition). This function is required to determine which object type is being used. `resolve_type` is called before any `ObjectTypeDefinition` resolve methods are called.

description (optional) single character value that describes the object

Examples

```
library(magrittr)

## Set up data
add_human <- function(human_data, id, name, appear, home, friend) {
```

```

human <- list(id = id, name = name, appearsIn = appear, friends = friend, homePlanet = home)
# set up a function to be calculated if the field totalCredits is required
human$totalCredits <- function(obj, args, schema) {
  length(human$appearsIn)
}
human_data[[id]] <- human
human_data
}
add_droid <- function(droid_data, id, name, appear, pf, friend) {
droid <- list(id = id, name = name, appearsIn = appear, friends = friend, primaryFunction = pf)
# set extra fields manually
droid$totalCredits <- length(droid$appearsIn)
droid_data[[id]] <- droid
droid_data
}

human_data <- list() %>%
  add_human("1000", "Luke Skywalker", c(4, 5, 6), "Tatooine", c("1002", "1003", "2000", "2001")) %>%
  add_human("1002", "Han Solo", c(4, 5, 6), "Coreellia", c("1000", "1003", "2001")) %>%
  add_human("1003", "Leia Organa", c(4, 5, 6), "Alderaan", c("1000", "1002", "2000", "2001"))

droid_data <- list() %>%
  add_droid("2000", "C-3PO", c(4, 5, 6), "Protocol", c("1000", "1002", "1003", "2001")) %>%
  add_droid("2001", "R2-D2", c(4, 5, 6), "Astromech", c("1000", "1002", "1003"))

all_characters <- list() %>% append(human_data) %>% append(droid_data) %>% print()
## End data set up

# Define the schema using GraphQL code
star_wars_schema <- Schema$new()

"
enum Episode { NEWHOPE, EMPIRE, JEDI }
" %>%
  gqlr_schema(
    Episode = list(
      resolve = function(episode_id, schema) {
        switch(as.character(episode_id),
          "4" = "NEWHOPE",
          "5" = "EMPIRE",
          "6" = "JEDI",
          "UNKNOWN_EPISODE"
        )
      }
    )
  ) ->
episode_schema
# display the schema
episode_schema$get_schema()
# add the episode definitions to the Star Wars schema
star_wars_schema$add(episode_schema)

```

```

"
interface Character {
  id: String!
  name: String
  friends: [Character]
  appearsIn: [Episode]
}
" %>%
gqlr_schema(
  Character = list(
    resolve_type = function(id, schema) {
      if (id %in% names(droid_data)) {
        "Droid"
      } else {
        "Human"
      }
    }
  )
) ->
character_schema
# print the Character schema with no extra formatting
character_schema$get_schema() %>% format() %>% cat("\n")
star_wars_schema$add(character_schema)

"
type Droid implements Character {
  id: String!
  name: String
  friends: [Character]
  appearsIn: [Episode]
  primaryFunction: String
}
type Human implements Character {
  id: String!
  name: String
  friends: [Character]
  appearsIn: [Episode]
  homePlanet: String
}
" %>%
gqlr_schema(
  Human = list(
    # Add a resolve method for type Human that takes in an id and returns the human data
    resolve = function(id, args, schema) {
      human_data[[id]]
    }
  ),
  Droid = list(
    # description for Droid
    description = "A mechanical creature in the Star Wars universe.",

```

```

    # Add a resolve method for type Droid that takes in an id and returns the droid data
    resolve = function(id, schema) {
      droid_data[[id]]
    }
  )
) ->
human_and_droid_schema
human_and_droid_schema$get_schema()
star_wars_schema$add(human_and_droid_schema)

"
type Query {
  hero(episode: Episode): Character
  human(id: String!): Human
  droid(id: String!): Droid
}
# the schema type must be provided if a query or mutation is to be executed
schema {
  query: Query
}
" %>%
gqlr_schema(
  Query = function(null, schema) {
    list(
      # return a function for key 'hero'
      # the id will be resolved by the appropriate resolve() method of Droid or Human
      hero = function(obj, args, schema) {
        episode <- args$episode
        if (identical(episode, 5) || identical(episode, "EMPIRE")) {
          "1000" # Luke Skywalker
        } else {
          "2001" # R2-D2
        }
      },
      # the id will be resolved by the Human resolve() method
      human = function(obj, args, schema) {
        args$id
      },
      # the id will be resolved by the Droid resolve() method
      droid = function(obj, args, schema) {
        args$id
      }
    )
  }
) ->
schema_def
# print Schema with no extra formatting
schema_def$get_schema() %>% format() %>% cat("\n")
star_wars_schema$add(schema_def)

# view the final schema definition

```

```
star_wars_schema$get_schema()
```

parse_ast

Parse AST

Description

This is a helper function for Scalars. Given a particular kind and a resolve function, it produces a function that will only parse values of a particular kind.

Usage

```
parse_ast(kind, resolve)
```

Arguments

kind	single character name of a class to parse
resolve	function to parse the value if the kind is correct

Details

Typically, kind is the same as the class of the Scalar. When making a new Scalar, parse_ast defaults to use the name of the scalar and the scalar's parse value function.

This function should only need to be used when defining a schema in [gqlr_schema\(\)](#)

Value

function that takes obj and schema that will only parse the value if the kind is inherited in the obj

Examples

```
parse_date_value <- function(obj, schema) {
  as.Date(obj)
}
parse_ast("Date", parse_date_value)

# Example from Int scalar
parse_int <- function(value, ...) {
  MAX_INT <- 2147483647
  MIN_INT <- -2147483648
  num <- suppressWarnings(as.integer(value))
  if (!is.na(num)) {
    if (num <= MAX_INT && num >= MIN_INT) {
      return(num)
    }
  }
  return(NULL)
}
parse_ast("IntValue", parse_int)
```

 Schema

GraphQL Schema object

Description

Manages a GraphQL schema definition. A Schema can add more GraphQL type definitions, assist in determining definition types, retrieve particular definitions, and can combine with other schema definitions.

Typically, Schema class objects are created using `gqlr_schema`. Creating a `Schema$new()` object should be reserved for when multiple Schema objects are combined.

Usage

```
## using star_wars_schema from
# example(gqlr_schema)
star_wars_schema$get_schema()
star_wars_schema$is_enum("Episode") # TRUE
star_wars_schema$is_object("Episode") # FALSE
execute_request("{ hero { name } }", star_wars_schema)
```

Initialize

schema Either a character GraphQL definition of a schema or another Schema object. Extending methods and descriptions should be added with `gqlr_schema`.

The initialize function will automatically add

- Scalars: Int, Float, String, Boolean
- Directives: `@skip` and `@include`
- Introspection Capabilities

Details

`$add(obj)`: function to add either another Schema's definitions or Document of definitions. `obj` must inherit class of either 'Schema' or 'Document'

`$is_scalar(name)`, `$is_enum(name)`, `$is_object(name)`, `$is_interface(name)`, `$is_union(name)`, `$is_input_object(name)`, `$is_directive(name)`, `$is_value(name)`: methods to determine if there is a definition of the corresponding definition type for the provided name.

`$get_scalar(name)`, `$get_enum(name)`, `$get_object(name)`, `$get_interface(name)`, `$get_union(name)`, `$get_input_object(name)`, `$get_directive(name)`, `$get_value(name)`: methods to retrieve a definition of the corresponding definition type for the provided name. If the object can't be found, NULL is returned. When printed, it quickly conveys all known information of the definition. Due to the nature of R6 objects, definitions may be retrieved and altered after retrieval. This is helpful for adding descriptions or resolve after the initialization.

`$get_scalars(name)`, `$get_enums(name)`, `$get_objects(name)`, `$get_interfaces(name)`, `$get_unions(name)`, `$get_input_objects(name)`, `$get_directives(name)`, `$get_values(name)`: methods to retrieve all definitions of the corresponding definition type.

`$get_type(name)`: method to retrieve an object of unknown type. If the object can't be found, NULL is returned. When printed, it quickly conveys all known information of the definition.

`$get_type(name)`: method to retrieve an object of unknown type. If the object can't be found, NULL is returned.

`$get_schema()`: method to retrieve full definition of schema. When printed, it quickly conveys all types in the schema.

`$get_query_object()`, `$get_mutation_object()`: helper method to retrieve the schema definition query or mutation object.

`$implements_interface()`: helper method to retrieve all objects who implement a particular interface.

`$is_valid`: boolean that determines if a Schema object has been validated. All Schema objects are validated at the time of request execution. The Schema will remain valid until new definitions are added.

See Also

[gqlr_schema](#)

server

Run basic GraphQL server

Description

Run a basic GraphQL server using plumber. This server is provided to show basic interaction with GraphQL. The server will run until the function execution is canceled.

Usage

```
server(schema, port = 8000L, log = TRUE, initial_value = NULL)
```

Arguments

<code>schema</code>	Schema object to use execute requests
<code>port</code>	web port to serve the server from. Set port to NULL to not run the plumber server and return it.
<code>log</code>	boolean that determines if server logging is done. Defaults to TRUE
<code>initial_value</code>	default value to use in execute_request()

Details

`server()` implements the basic necessities described in <http://graphql.org/learn/serving-over-http/>. There are three routes implemented:

`/'/` GET. Returns a GraphQL formatted schema definition

`/graphql` GET. Executes a query. The parameter `'query'` (which contains a GraphQL formatted query string) must be included. Optional parameters include: `'variables'` a JSON string containing a dictionary of variables (defaults to an empty named list), `'operationName'` name of the particular query operation to execute (defaults to NULL), and `'pretty'` boolean to determine if the response should be compact (FALSE, default) or expanded (TRUE)

`/graphql` POST. Executes a query. Must provide Content-Type of either `'application/json'` or `'application/graphql'`.

If `'application/json'` is provided, a named JSON list containing `'query'`, `'operationName'` (optional, default = NULL), `'variables'` (optional, default = list()) and `'pretty'` (optional, default = TRUE). The information will used just the same as the GET-`/graphql` route.

If `'application/graphql'` is provided, the POST body will be interpreted as the query string. All other possible parameters will take on their default value.

Using bash's curl, we can ask the server questions:

```
#R
# load Star Wars schema from 'execute_request' example
example(gqlr_schema)
# run server
server(star_wars_schema, port = 8000)

#bash
# GET Schema definition
curl '127.0.0.1:8000/'

## POST for R2-D2 and his friends' names
# defaults to parse as JSON
curl --data '{"query":"{hero{name, friends { name }}}", "pretty": true}' '127.0.0.1:8000/graphql'
# send json header
curl --data '{"query":"{hero{name, friends { name }}}}' '127.0.0.1:8000/graphql' --header "Content-Type: application/json"
# send graphql header
curl --data '{hero{name, friends { name }}}' '127.0.0.1:8000/graphql' --header "Content-Type: application/graphql"
# use variables
curl --data '{"query":"query Droid($someId: String!) {droid(id: $someId) {name, friends { name }}}}' '127.0.0.1:8000/graphql'

# GET R2-D2 and his friends' names
curl '127.0.0.1:8000/graphql?query=query'
# ... using a variable
curl '127.0.0.1:8000/graphql?query=query'
```

Index

`as_R6`, [2](#)

`ErrorList`, [3](#)

`execute_request`, [3](#), [4](#), [13](#)

`gqlr_schema`, [4](#), [6](#), [11–13](#)

`parse_ast`, [11](#)

`Schema`, [12](#)

`server`, [13](#)