

# Package ‘markmyassignment’

September 12, 2020

**Type** Package

**Title** Automatic Marking of R Assignments

**Version** 0.8.3

**Date** 2020-09-11

**Author** Mans Magnusson, Oscar Pettersson

**Maintainer** Mans Magnusson <mons.magnusson@gmail.com>

**Description** Automatic marking of R assignments for students and teachers based on 'testthat' test suites.

**License** BSD\_2\_clause + file LICENSE

**Encoding** UTF-8

**Depends** R (>= 3.2.0)

**Imports** methods, yaml, testthat (>= 2.0.0), httr (>= 1.0.0), checkmate (>= 1.0.0), codetools, lazyeval, rlang

**RoxygenNote** 7.1.1

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2020-09-12 13:20:08 UTC

## R topics documented:

markmyassignment . . . . .	2
mark_my_assignment . . . . .	2
mark_my_file . . . . .	3
set_assignment . . . . .	4
show_tasks . . . . .	4

<b>Index</b>	<b>6</b>
--------------	----------

---

markmyassignment	<i>Automatic Marking of R Assignments</i>
------------------	---

---

**Description**

Automatic marking of R assignments for students and teachers based on testthat test suites.

---

mark_my_assignment	<i>Mark assignment in global environment</i>
--------------------	--

---

**Description**

Mark assignment in global environment.

**Usage**

```
mark_my_assignment(
  tasks = NULL,
  mark_file = NULL,
  force_get_tests = FALSE,
  quiet = FALSE,
  ...
)
```

**Arguments**

tasks	Which task should be corrected (if more than one). Default is all. To see the different task, see <a href="#">show_tasks</a> .
mark_file	Argument is deprecated, use mark_my_file instead.
force_get_tests	Argument is deprecated, use set_assignment() instead.
quiet	Should test be run without output?
...	further arguments sent to test_dir().

**Examples**

```
assignment_path <-
  file.path(system.file(package = "markmyassignment"), "extdata", "example_assignment01.yml")
set_assignment(assignment_path)
source(file.path(system.file(package = "markmyassignment"), "extdata", "example_lab_file.R"))
mark_my_assignment()
```

---

mark_my_file	<i>Mark assignment file</i>
--------------	-----------------------------

---

## Description

Mark a specific assignment file

## Usage

```
mark_my_file(  
  tasks = NULL,  
  mark_file = file.choose(),  
  assignment_path = NULL,  
  force_get_tests = FALSE,  
  quiet = FALSE,  
  ...  
)
```

## Arguments

tasks	Which task should be corrected (if more than one). Default is all. To see the different task, see <a href="#">show_tasks</a> .
mark_file	Path to the file to mark.
assignment_path	Assignment file to set before marking the assignment (url or local path).
force_get_tests	Argument is deprecated, use <code>set_assignment()</code> instead.
quiet	Should test be run without output?
...	further arguments sent to <code>test_dir()</code> .

## Examples

```
## Not run:  
assignment_path <-  
  file.path(system.file(package = "markmyassignment"), "extdata", "example_assignment01.yml")  
file_path <- file.path(system.file(package = "markmyassignment"), "extdata", "example_lab_file.R")  
mark_my_file(mark_file = file_path, assignment_path = assignment_path)  
  
## End(Not run)
```

---

set_assignment	<i>Set and remove assignments</i>
----------------	-----------------------------------

---

### Description

Sets the assignment to mark and downloads necessary files.

### Usage

```
set_assignment(path, auth = NULL)
```

```
remove_assignment()
```

```
is_assignment_set()
```

```
show_assignment()
```

### Arguments

path	Path to the yml file
auth	Authorization object generated by <code>httr::authenticate()</code> . See <code>authenticate</code> and <a href="https://github.com/r-lib/httr/blob/master/demo/oauth2-github.r">https://github.com/r-lib/httr/blob/master/demo/oauth2-github.r</a> on details on how to use <code>authenticate()</code> .

### Examples

```
assignment_path <- path <-  
  file.path(system.file(package = "markmyassignment"), "/extdata/example_assignment01.yml")  
set_assignment(assignment_path)  
assignment_path <- path <-  
  file.path(system.file(package = "markmyassignment"), "/extdata/assignment_template.yml")  
set_assignment(assignment_path)
```

---

show_tasks	<i>Get the name of the tasks in the assignment.</i>
------------	---

---

### Description

Get the name of the tasks in the assignment.

### Usage

```
show_tasks()
```

**Examples**

```
# We first set the assignment
assignment_path <-
  file.path(system.file(package = "markmyassignment"), "extdata/example_assignment01.yml")
set_assignment(assignment_path)

show_tasks()
```

# Index

`is_assignment_set (set_assignment)`, 4

`mark_my_assignment`, 2

`mark_my_file`, 3

`markmyassignment`, 2

`remove_assignment (set_assignment)`, 4

`set_assignment`, 4

`show_assignment (set_assignment)`, 4

`show_tasks`, 2, 3, 4