

Package ‘mlr3fairness’

May 12, 2022

Type Package

Title Fairness Auditing and Debiasing for 'mlr3'

Version 0.3.0

Description Integrates fairness auditing and bias mitigation methods for the 'mlr3' ecosystem.

This includes fairness metrics, reporting tools, visualizations and bias mitigation techniques such as

``Reweighting" described in 'Kamiran, Calders' (2012) <[doi:10.1007/s10115-011-0463-8](https://doi.org/10.1007/s10115-011-0463-8)> and

``Equalized Odds" described in 'Hardt et al.' (2016) <<https://papers.nips.cc/paper/2016/file/9d2682367c3935defcb1f9e247a97c0d-Paper.pdf>>.

Integration with 'mlr3' allows for auditing of ML models as well as convenient joint tuning of machine learning algorithms and debiasing methods.

URL <https://mlr3fairness.mlr-org.com>,

<https://github.com/mlr-org/mlr3fairness>

BugReports <https://github.com/mlr-org/mlr3fairness/issues>

License LGPL-3

Encoding UTF-8

LazyData true

Depends R (>= 3.5.0), mlr3 (>= 0.13.0)

Imports checkmate, R6 (>= 2.4.1), data.table (>= 1.13.6), paradox, mlr3measures, mlr3misc, mlr3pipelines, ggplot2

Suggests mlr3viz, rmarkdown, knitr, rpart, testthat (>= 3.0.0), patchwork, ranger, mlr3learners, linprog, posterdown, kableExtra, fairml, iml

RoxygenNote 7.1.2

VignetteBuilder knitr

NeedsCompilation no

Author Florian Pfisterer [cre, aut] (<<https://orcid.org/0000-0001-8867-762X>>),

Wei Siyi [aut],

Michel Lang [aut] (<<https://orcid.org/0000-0001-9754-0393>>)

Maintainer Florian Pfisterer <pfistererf@googlemail.com>

Repository CRAN

Date/Publication 2022-05-12 19:30:02 UTC

R topics documented:

adult	2
compare_metrics	3
compas	5
fairness_accuracy_tradeoff	6
fairness_prediction_density	7
fairness_tensor	8
groupdiff_tau	9
groupwise_metrics	10
MeasureFairness	11
MeasureFairnessComposite	13
MeasureFairnessConstraint	14
MeasureSubgroup	16
mlr_learners_fairness	17
mlr_measures_fairness	18
mlr_measures_positive_probability	19
mlr_pipeops_equalized_odds	20
mlr_pipeops_explicit_pta	22
mlr_pipeops_reweighing	24
report_datasheet	27
report_fairness	28
report_modelcard	29
task_summary	30
Index	31

adult	<i>Adult Dataset</i>
-------	----------------------

Description

Dataset used to predict whether income exceeds \$50K/yr based on census data. Also known as "Census Income" dataset Train dataset contains 13 features and 30178 observations. Test dataset contains 13 features and 15315 observations. Target column is "target": A binary factor where 1: <=50K and 2: >50K for annual income. The column "sex" is set as protected attribute.

Pre-processing

- `fnlwgt` Remove final weight, which is the number of people the census believes the entry represents
- `native-country` Remove Native Country, which is the country of origin for an individual
- Rows containing NA in workclass and occupation have been removed.
- Pre-processing inspired by article: @url <https://cseweb.ucsd.edu/classes/sp15/cse190-c/reports/sp15/048.pdf>

Metadata

- (integer) age: The age of the individuals
- (factor) workclass: A general term to represent the employment status of an individual
- (factor) education: The highest level of education achieved by an individual.
- (integer) education_num: the highest level of education achieved in numerical form.
- (factor) marital_status: marital status of an individual.
- (factor) occupation: the general type of occupation of an individual
- (factor) relationship: whether the individual is in a relationship-
- (factor) race: Descriptions of an individual's race
- (factor) sex: the biological sex of the individual
- (integer) captain-gain: capital gains for an individual
- (integer) captain-loss: capital loss for an individual
- (integer) hours-per-week: the hours an individual has reported to work per week
- (factor) target: whether or not an individual makes more than \$50,000 annually

Source

Dua, Dheeru, Graff, Casey (2017). "UCI Machine Learning Repository." <http://archive.ics.uci.edu/ml/>.

Examples

```
data("adult_test", package = "mlr3fairness")
data("adult_train", package = "mlr3fairness")
```

compare_metrics

Compare different metrics

Description

Compare learners with respect to one or multiple metrics. Metrics can but be but are not limited to fairness metrics.

Usage

```
compare_metrics(object, ...)
```

Arguments

- object [\(PredictionClassif | BenchmarkResult | ResampleResult\)](#)
The object to create a plot for.
- If provided a [\(PredictionClassif\)](#). Then the visualization will compare the fairness metrics among the binary level from protected field through bar plots.
 - If provided a [\(ResampleResult\)](#). Then the visualization will generate the boxplots for fairness metrics, and compare them among the binary level from protected field.
 - If provided a [\(BenchmarkResult\)](#). Then the visualization will generate the boxplots for fairness metrics, and compare them among both the binary level from protected field and the models implemented.
- ... The arguments to be passed to methods, such as:
- `fairness_measures` (list of [Measure](#))
The fairness measures that will be evaluated on object, could be single [Measure](#) or list of [Measures](#). Default measure set to be `msr("fairness.acc")`.
 - `task` ([TaskClassif](#))
The data task that contains the protected column, only required when object is [\(PredictionClassif\)](#).

Value

A 'ggplot2' object.

Examples

```
library(mlr3learners)

# Setup the Fairness Measures and tasks
task = tsk("adult_train")$filter(1:500)
learner = lrn("classif.ranger", predict_type = "prob")
learner$train(task)
predictions = learner$predict(task)
design = benchmark_grid(
  tasks = task,
  learners = lrns(c("classif.ranger", "classif.rpart"),
    predict_type = "prob", predict_sets = c("train", "predict")),
  resamplings = rsmpls("cv", folds = 3)
)

bmr = benchmark(design)
fairness_measure = msr("fairness.tpr")
fairness_measures = msrs(c("fairness.tpr", "fairness.fnr", "fairness.acc"))

# Predictions
compare_metrics(predictions, fairness_measure, task)
compare_metrics(predictions, fairness_measures, task)

# BenchmarkResult and ResamplingResult
```

```
compare_metrics(bmr, fairness_measure)
compare_metrics(bmr, fairness_measures)
```

 compas

COMPAS Dataset

Description

The COMPAS dataset includes the processed COMPAS data between 2013-2014. The data cleaning process followed the guidance in the original COMPAS repo. Contains 6172 observations and 14 features. The target column could either be "is_recid" or "two_year_recid", but often "two_year_recid" is preferred. The column "sex" is set as protected attribute, but more often "race" is used.

A classification task for the [compas](#) data set.

A classification task for the [compas](#) data set. The observations have been filtered, keeping only observations with race "Caucasian" and "African-American". The protected attribute has been set to "race".

Format

R6::R6Class inheriting from [TaskClassif](#).

R6::R6Class inheriting from [TaskClassif](#).

Pre-processing

- Identifying columns are removed
- Removed the outliers for `abs(days_b_screening_arrest) >= 30`.
- Removed observations where `is_recid != -1`.
- Removed observations where `c_charge_degree != "O"`.
- Removed observations where `score_text != 'N/A'`.
- Factorize the features that are categorical.
- Add length of stay (`c_jail_out - c_jail_in`) in the dataset.
- Pre-processing Resource: @url <https://github.com/propublica/compas-analysis/blob/master/Compas%20Analysis.ip>

Metadata

- (integer) age : The age of defendants.
- (factor) c_charge_degree : The charge degree of defendants. F: Felony M: Misdemeanor
- (factor) race: The race of defendants.
- (factor) age_cat: The age category of defendants.
- (factor) score_text: The score category of defendants.
- (factor) sex: The sex of defendants.
- (integer) priors_count: The prior criminal records of defendants.

- (integer) `days_b_screening_arrest`: The count of days between screening date and (original) arrest date. If they are too far apart, that may indicate an error. If the value is negative, that indicate the screening date happened before the arrest date.
- (integer) `decile_score`: Indicate the risk of recidivism (Min=1, Max=10)
- (integer) `is_recid`: Binary variable indicate whether defendant is rearrested at any time.
- (factor) `two_year_recid`: Binary variable indicate whether defendant is rearrested at within two years.
- (numeric) `length_of_stay`: The count of days stay in jail.

Construction

```
mlr_tasks$get("compas")
tsk("compas")
```

```
mlr_tasks$get("compas_race_binary")
tsk("compas_race_binary")
```

Source

<https://github.com/propublica/compas-analysis>

Examples

```
data("compas", package = "mlr3fairness")
```

```
fairness_accuracy_tradeoff
      Plot Fairness Accuracy Trade-offs
```

Description

Provides visualization wrt. trade-offs between fairness and accuracy metrics across learners and resampling iterations. This can assist in gauging the optimal model from a set of options along with estimates of variance (through individual resampling iterations).

Usage

```
fairness_accuracy_tradeoff(object, ...)
```

Arguments

- `object` ([PredictionClassif](#) | [BenchmarkResult](#) | [ResampleResult](#))
 The binary class prediction object that will be evaluated.
- If provided a [PredictionClassif](#). Then only one point will indicate the accuracy and fairness metrics for the current predictions. Requires also passing a [Task](#).

- If provided a [ResampleResult](#). Then the plot will compare the accuracy and fairness metrics for the same model, but different resampling iterations as well as the aggregate indicated by a cross.
- If provided a [BenchmarkResult](#). Then the plot will compare the accuracy and fairness metrics for all models and all resampling iterations. Points are colored according to the learner_id and faceted by task_id. The aggregated score is indicated by a cross.

...

Arguments to be passed to methods. Such as:

- `fairness_measure` ([Measure](#))
The fairness measures that will be evaluated. Default measure set to be `msr("fairness.fpr")`
- `accuracy_measure` ([Measure](#))
The accuracy measure that will be evaluated. Default measure set to be `msr("classif.acc")`.
- `task` ([TaskClassif](#))
The data task that contains the protected column, only required when the class of object is ([PredictionClassif](#))

Value

A 'ggplot2' object.

Examples

```
library(mlr3learners)
library(ggplot2)

# Setup the Fairness Measures and tasks
task = tsk("adult_train")$filter(1:500)
learner = lrn("classif.ranger", predict_type = "prob")
learner$train(task)
predictions = learner$predict(task)
design = benchmark_grid(
  tasks = task,
  learners = lrns(c("classif.ranger", "classif.rpart"),
    predict_type = "prob", predict_sets = c("train", "predict")),
  resamplings = rsmpls("cv", folds = 3)
)

bmr = benchmark(design)
fairness_measure = msr("fairness.tpr")

fairness_accuracy_tradeoff(predictions, fairness_measure, task = task)
fairness_accuracy_tradeoff(bmr, fairness_measure)
```

fairness_prediction_density

Probability Density Plot

Description

Visualizes per-subgroup densities across learners, task and class. The plot is a combination of boxplot and violin plot. The y-axis shows the levels in protected columns. And the x-axis shows the predicted probability. The title for the plot will demonstrate which class for predicted probability.

Usage

```
fairness_prediction_density(object, ...)
```

Arguments

object	(PredictionClassif ResampleResult BenchmarkResult) The binary class prediction object that will be evaluated. If PredictionClassif , a Task is required.
...	The arguments to be passed to methods, such as: <ul style="list-style-type: none"> task (TaskClassif) The data task that contains the protected column. type character The plot type. Either violin or density.

Value

A 'ggplot2' object.

Examples

```
library(mlr3learners)

task = tsk("adult_train")$filter(1:500)
learner = lrn("classif.rpart", predict_type = "prob", cp = 0.001)
learner$train(task)

# For prediction
predictions = learner$predict(task)
fairness_prediction_density(predictions, task)

# For resampling
rr = resample(task, learner, rsmpl("cv"))
fairness_prediction_density(rr)
```

 fairness_tensor

Compute the Fairness Tensor given a Prediction and a Task

Description

A fairness tensor is a list of groupwise confusion matrices.

Usage

```

fairness_tensor(object, ...)

## S3 method for class 'data.table'
fairness_tensor(object, task, ...)

## S3 method for class 'PredictionClassif'
fairness_tensor(object, task, ...)

## S3 method for class 'ResampleResult'
fairness_tensor(object, ...)

```

Arguments

object	(data.table() PredictionClassif ResampleResult) A data.table with columns truth and prediction, a PredictionClassif or a ResampleResult .
...	any Currently not used.
task	(TaskClassif) A TaskClassif . Needs col_role "pta" to be set.

Value

list() of confusion matrix for every group in "pta".

Examples

```

task = tsk("compas")
prediction = lrn("classif.rpart")$train(task)$predict(task)
fairness_tensor(prediction, task)

```

groupdiff_tau

Groupwise Operations

Description

groupdiff_tau() computes $\min(x/y, y/x)$, i.e. the smallest symmetric ratio between x and y that is smaller than 1. If x is a vector, the symmetric ratio between all elements in x is computed.

groupdiff_absdiff() computes $\max(\text{abs}(x - y, y - x))$, i.e. the smallest absolute difference between x and y . If x is a vector, the symmetric absolute difference between all elements in x is computed.

Usage

```

groupdiff_tau(x)

groupdiff_absdiff(x)

groupdiff_diff(x)

```

Arguments

x (numeric())
Measured performance in group 1, 2, ...

Value

A single numeric.

Examples

```

groupdiff_tau(1:3)
groupdiff_diff(1:3)
groupdiff_absdiff(1:3)

```

groupwise_metrics *Evaluate a metric on each protected subgroup in a task.*

Description

Instantiates one new measure per protected attribute group in a task. Each metric is then evaluated only on predictions made for the given specific subgroup.

Usage

```
groupwise_metrics(base_measure, task, intersect = TRUE)
```

Arguments

base_measure (Measure())
The base metric evaluated within each subgroup.

task [Task](#)
[mlr3::Task\(\)](#) to instantiate measures for.

intersect [logical](#)
Should multiple pta groups be intersected? Defaults to TRUE. Only relevant if more than one pta columns are provided.

Value

list
List of [mlr3::Measures](#).

See Also[MeasureSubgroup](#)**Examples**

```
t = tsk("compas")
l = lrn("classif.rpart")
m = groupwise_metrics(msr("classif.acc"), t)
l$train(t)$predict(t)$score(m, t)
```

MeasureFairness

*Base Measure for Fairness***Description**

This measure extends `mlr3::Measure()` with statistical group fairness: A common approach to quantifying a model's fairness is to compute the difference between a protected and an unprotected group according w.r.t. some performance metric, e.g. classification error (`mlr_measures_classif.ce`) or false positive rate (`mlr_measures_classif.fpr`). The operation for comparison (e.g., difference or quotient) can be specified using the operation parameter, e.g. `groupdiff_absdiff()` or `groupdiff_tau()`.

Composite measures encompassing multiple fairness metrics can be built using [MeasureFairness-Composite](#).

Some popular predefined measures can be found in the [dictionary mlr_measures](#).

Super class

`mlr3::Measure` -> MeasureFairness

Public fields

`base_measure` (`Measure()`)

The base measure to be used by the fairness measures, e.g. `mlr_measures_classif.fpr` for the false positive rate.

`operation` (`function()`)

The operation used to compute the difference. A function with args 'x' and 'y' that returns a single value. Defaults to `abs(x - y)`.

Methods**Public methods:**

- [MeasureFairness\\$new\(\)](#)
- [MeasureFairness\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
MeasureFairness$new(
  id = NULL,
  base_measure,
  operation = groupdiff_absdiff,
  minimize = TRUE,
  range = c(-Inf, Inf)
)
```

Arguments:

id (character)

The measure's id. Set to 'fairness.<base_measure_id>' if omitted.

base_measure (Measure())

The base metric evaluated within each subgroup.

operation (function)

The operation used to compute the difference. A function that returns a single value given input: computed metric for each subgroup. Defaults to [groupdiff_absdiff](#).

minimize (logical())

Should the measure be minimized? Defaults to TRUE.

range (numeric(2))

Range of the resulting measure. Defaults to c(-Inf, Inf).

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
MeasureFairness$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

[MeasureFairnessComposite](#)

Examples

```
# Create MeasureFairness to measure the Predictive Parity.
t = tsk("adult_train")
learner = lrn("classif.rpart", cp = .01)
learner$train(t)
measure = msr("fairness", base_measure = msr("classif.ppv"))
predictions = learner$predict(t)
predictions$score(measure, task = t)
```

 MeasureFairnessComposite

Composite Fairness Measure

Description

Computes a composite measure from multiple fairness metrics and aggregates them using `aggfun` (defaulting to `mean()`).

Super class

`m1r3::Measure` -> MeasureFairnessComposite

Methods

Public methods:

- `MeasureFairnessComposite$new()`
- `MeasureFairnessComposite$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
MeasureFairnessComposite$new(
  id = NULL,
  measures,
  aggfun = function(x) mean(x, na.rm = TRUE),
  operation = groupdiff_absdiff,
  minimize = TRUE,
  range = c(-Inf, Inf)
)
```

Arguments:

`id` (character(1))

Id of the measure. Defaults to the concatenation of ids in measure.

`measures` (list of `MeasureFairness`)

List of fairness measures to aggregate.

`aggfun` (function())

Aggregation function used to aggregate results from respective measures. Defaults to `sum`.

`operation` (function())

The operation used to compute the difference. A function that returns a single value given input: computed metric for each subgroup. Defaults to `groupdiff_absdiff`. See `MeasureFairness` for more information.

`minimize` (logical(1))

Should the measure be minimized? Defaults to `TRUE`.

`range` (numeric(2))

Range of the resulting measure. Defaults to `c(-Inf, Inf)`.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureFairnessComposite$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
# Equalized Odds Metric
MeasureFairnessComposite$new(measures = msrs(c("fairness.fpr", "fairness.tpr")))

# Other metrics e.g. based on negative rates
MeasureFairnessComposite$new(measures = msrs(c("fairness.fnr", "fairness.tnr")))
```

MeasureFairnessConstraint

Fairness Constraint Measure

Description

This measure allows constructing for 'constraint' measures of the following form:

$$\text{minperformance}_{\text{subject to fairness}} < \epsilon$$

Super class

```
m1r3::Measure -> MeasureFairnessConstraint
```

Public fields

```
performance_measure (Measure())
  The performance measure to be used.
fairness_measure (Measure())
  The fairness measure to be used.
epsilon (numeric)
  Deviation from perfect fairness that is allowed.
```

Methods

Public methods:

- `MeasureFairnessConstraint$new()`
- `MeasureFairnessConstraint$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
MeasureFairnessConstraint$new(
  id = NULL,
  performance_measure,
  fairness_measure,
  epsilon = 0.01,
  range = c(-Inf, Inf)
)
```

Arguments:

`id` (character)
The measure's id. Set to 'fairness.<base_measure_id>' if omitted.

`performance_measure` (Measure())
The measure used to measure performance (e.g. accuracy).

`fairness_measure` (Measure())
The measure used to measure fairness (e.g. equalized odds).

`epsilon` (numeric)
Allowed divergence from perfect fairness. Initialized to 0.01.

`range` (numeric)
Range of the resulting measure. Defaults to `c(-Inf, Inf)`.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureFairnessConstraint$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

`mlr_measures_fairness`

Examples

```
# Accuracy subject to equalized odds fairness constraint:
library(mlr3)
t = tsk("adult_train")
learner = lrn("classif.rpart", cp = .01)
learner$train(t)
measure = msr("fairness.constraint", id = "acc_tpr", msr("classif.acc"), msr("fairness.tpr"))
predictions = learner$predict(t)
predictions$score(measure, task = t)
```

MeasureSubgroup	<i>Evaluate a metric on a subgroup</i>
-----------------	--

Description

Allows for calculation of arbitrary `mlr3::Measure()`s on a selected sub-group.

Super class

`mlr3::Measure` -> MeasureSubgroup

Public fields

`base_measure` (Measure())

The base measure to be used by the fairness measures, e.g. `mlr_measures_classif.fpr` for the false positive rate.

`subgroup` (character)|(integer)

Subgroup identifier.

`intersect` (logical)

Should groups be intersected?

Methods**Public methods:**

- `MeasureSubgroup$new()`
- `MeasureSubgroup$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
MeasureSubgroup$new(id = NULL, base_measure, subgroup, intersect = TRUE)
```

Arguments:

`id` (character)

The measure's id. Set to 'fairness.<base_measure_id>' if omitted.

`base_measure` (Measure())

The measure used to measure fairness.

`subgroup` (character)|(integer)

Subgroup identifier. Either value for the protected attribute or position in `task$levels`.

`intersect` **logical**

Should multiple pta groups be intersected? Defaults to TRUE. Only relevant if more than one pta columns are provided.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureSubgroup$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

[MeasureFairness](#), [groupwise_metrics](#)

Examples

```
# Create MeasureFairness to measure the Predictive Parity.
t = tsk("adult_train")
learner = lrn("classif.rpart", cp = .01)
learner$train(t)
measure = msr("subgroup", base_measure = msr("classif.acc"), subgroup = "Female")
predictions = learner$predict(t)
predictions$score(measure, task = t)
```

mlr_learners_fairness *Fair Learners in mlr3*

Description

Fair Learners in mlr3

Usage

```
mlr_learners_fairness
```

Format

An object of class `data.table` (inherits from `data.frame`) with 5 rows and 3 columns.

Value

A `data.table` containing an overview of available fair learners.

Predefined measures

mlr3fairness comes with a set of predefined fair learners listed below:

key	package	reference
regr.fairfrm	fairml	Scutari et al., 2021
classif.fairfgrm	fairml	Scutari et al., 2021
regr.fairzlm	fairml	Zafar et al., 2019
classif.fairzlm	fairml	Zafar et al., 2019
regr.fairnclm	fairml	Komiyama et al., 2018

Examples

```
# Available learners:
mlr_learners_fairness
```

 mlr_measures_fairness *Fairness Measures in mlr3*

Description

Fairness Measures in mlr3

Usage

```
mlr_measures_fairness
```

Format

An object of class `data.table` (inherits from `data.frame`) with 18 rows and 2 columns.

Value

A `data.table` containing an overview of available fairness metrics.

Predefined measures

mlr3fairness comes with a set of predefined fairness measures as listed below. For full flexibility, [MeasureFairness](#) can be used to construct classical group fairness measures based on a difference between a performance metrics across groups by combining a performance measure with an operation for measuring differences. Furthermore [MeasureSubgroup](#) can be used to measure performance in a given subgroup, or alternatively `groupwise_metrics(measure, task)` to instantiate a measure for each subgroup in a [Task](#).

key	description
fairness.acc	Absolute differences in accuracy across groups
fairness.mse	Absolute differences in mean squared error across groups
fairness.fnr	Absolute differences in false negative rates across groups
fairness.fpr	Absolute differences in false positive rates across groups
fairness.tnr	Absolute differences in true negative rates across groups
fairness.tpr	Absolute differences in true positive rates across groups
fairness.npv	Absolute differences in negative predictive values across groups
fairness.ppv	Absolute differences in positive predictive values across groups
fairness.fomr	Absolute differences in false omission rates across groups
fairness.fp	Absolute differences in false positives across groups
fairness.tp	Absolute differences in true positives across groups
fairness.tn	Absolute differences in true negatives across groups
fairness.fn	Absolute differences in false negatives across groups
fairness.cv	Difference in positive class prediction, also known as Calders-Wevers gap or demographic parity
fairness.eod	Equalized Odds: Sum of absolute differences between true positive and false positive rates across groups
fairness.ppv	Predictive Parity: Sum of absolute differences between ppv and npv across groups
fairness.acc_eod=.05	Accuracy under equalized odds < 0.05 constraint
fairness.acc_ppv=.05	Accuracy under ppv difference < 0.05 constraint

Examples

```
# Predefined measures:
mlr_measures_fairness$key
```

```
mlr_measures_positive_probability
      Positive Probability Measure
```

Description

Return the probability of a positive prediction, often known as 'Calders-Wevers' gap. This is defined as count of positive predictions divided by the number of observations.

Super class

```
mlr3::Measure -> MeasurePositiveProbability
```

Methods**Public methods:**

- [MeasurePositiveProbability\\$new\(\)](#)
- [MeasurePositiveProbability\\$clone\(\)](#)

Method `new()`: Initialize a Measure Positive Probability Object

Usage:

```
MeasurePositiveProbability$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasurePositiveProbability$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
# Create Positive Probability Measure
t = tsk("adult_train")
learner = lrn("classif.rpart", cp = .01)
learner$train(t)
measure = msr("classif.pp")
predictions = learner$predict(t)
predictions$score(measure, task = t)
```

mlr_pipeops_equalized_odds

Equalized Odds Debiasing

Description

Fairness post-processing method to achieve equalized odds fairness. Works by randomly flipping a subset of predictions with pre-computed probabilities in order to satisfy equalized odds constraints.

NOTE: Carefully assess the correct privileged group.

Format

[R6Class](#) object inheriting from [PipeOpTaskPreproc/PipeOp](#).

Construction

```
PipeOpEod$new(id = "eod", param_vals = list())
```

- `id` (`character(1)`).
- `param_vals` (`list()`)

Input and Output Channels

Input and output channels are inherited from [PipeOpTaskPreproc](#). Instead of a [Task](#), a [TaskClassif](#) is used as input and output during training and prediction.

The output during training is the input [Task](#). The output during prediction is a [PredictionClassif](#) with partially flipped predictions.

State

The `$state` is a named list with the `$state` elements inherited from [PipeOpTaskPreproc](#).

Parameters

- `alpha` (`numeric()`): A number between 0 (no debiasing) and 1 (full debiasing). Controls the debiasing strength by multiplying the flipping probabilities with alpha.
- `privileged` (`character()`): The privileged group.

Fields

Only fields inherited from [PipeOpTaskPreproc/PipeOp](#).

Methods

Methods inherited from [PipeOpTaskPreproc/PipeOp](#).

Super class

`mlr3pipelines::PipeOp` -> `PipeOpE0d`

Methods**Public methods:**

- `PipeOpE0d$new()`
- `PipeOpE0d$clone()`

Method `new()`: Creates a new instance of this [R6][R6::R6Class][PipeOp] R6 class.

Usage:

```
PipeOpE0d$new(id = "E0d", param_vals = list())
```

Arguments:

`id` character

The PipeOps identifier in the PipeOps library.

`param_vals` list

The parameter values to be set. See Parameters.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpE0d$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Hardt M, Price E, Srebro N (2016). "Equality of Opportunity in Supervised Learning." In *Advances in Neural Information Processing Systems*, volume 29, 3315–3323. <https://papers.nips.cc/paper/2016/file/9d2682367c3935defcb1f9e247a97c0d-Paper.pdf>.

Pleiss, Geoff, Raghavan, Manish, Wu, Felix, Kleinberg, Jon, Weinberger, Q K (2017). "On Fairness and Calibration." In Guyon I, Luxburg UV, Bengio S, Wallach H, Fergus R, Vishwanathan S, Garnett R (eds.), *Advances in Neural Information Processing Systems*, volume 30. <https://proceedings.neurips.cc/paper/2017/file/b8b9c74ac526fffb2d39ab038d1cd7-Paper.pdf>.

See Also

<https://mlr3book.mlr-org.com/list-pipeops.html>

Other PipeOps: `mlr_pipeops_explicit_pta`, `mlr_pipeops_reweighing`

Examples

```
library(mlr3pipelines)

eod = po("E0d")
learner_po = po("learner_cv",
  learner = lrn("classif.rpart"),
```

```

    resampling.method = "insample"
  )

  task = tsk("compas")
  graph = learner_po %>>% eod
  glrn = GraphLearner$new(graph)
  glrn$train(task)

  # On a Task
  glrn$predict(task)

  # On newdata
  glrn$predict_newdata(task$data(cols = task$feature_names))

```

```

mlr_pipeops_explicit_pta
      PipeOpExplicitPta

```

Description

Turns the column with column role 'pta' into an explicit separate column prefixed with *"..internal_pta"*. This keeps it from getting changed or adapted by subsequent pipelines that operate on the feature pta.

Format

[R6Class](#) object inheriting from [PipeOpTaskPreproc/PipeOp](#).

Construction

```
PipeOpExplicitPta$new(id = "reweighing", param_vals = list())
```

- `id` (`character(1)`).
- `param_vals` (`list()`)

Input and Output Channels

Input and output channels are inherited from [PipeOpTaskPreproc](#). Instead of a [Task](#), a [TaskClassif](#) is used as input and output during training and prediction.

The output during training is the input [Task](#) with added weights column according to target class. The output during prediction is the unchanged input.

State

The `$state` is a named list with the `$state` elements inherited from [PipeOpTaskPreproc](#).

Parameters

The [PipeOp](#) does not have any hyperparameters.

Internals

Copies the existing pta column to a new column.

Fields

Only fields inherited from [PipeOpTaskPreproc/PipeOp](#).

Methods

Methods inherited from [PipeOpTaskPreproc/PipeOp](#).

Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3pipelines::PipeOpTaskPreproc](#) -> [PipeOpExplicitPta](#)

Methods**Public methods:**

- [PipeOpExplicitPta\\$new\(\)](#)
- [PipeOpExplicitPta\\$clone\(\)](#)

Method `new()`: Creates a new instance of this `[R6][R6::R6Class][PipeOp]` R6 class.

Usage:

```
PipeOpExplicitPta$new(id = "explicit_pta", param_vals = list())
```

Arguments:

`id` character

The PipeOps identifier in the PipeOps library.

`param_vals` list

The parameter values to be set. See Parameters.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpExplicitPta$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

<https://mlr3book.mlr-org.com/list-pipeops.html>

Other PipeOps: [mlr_pipeops_equalized_odds](#), [mlr_pipeops_reweighing](#)

Examples

```
library(mlr3pipelines)
epta = po("explicit_pta")
new = epta$train(list(tsk("adult_train")))
```

mlr_pipeops_reweighing

Reweighing to balance disparate impact metric

Description

Adjusts class balance and protected group balance in order to achieve fair(er) outcomes.

Format

[R6Class](#) object inheriting from [PipeOpTaskPreproc/PipeOp](#).

PipeOpReweightingWeights

Adds a class weight column to the [Task](#) that different [Learners](#) may be using. In case initial weights are present, those are multiplied with new weights. Caution: Only fairness tasks are supported. Which means tasks need to have protected field. `tskcol_rolespta`.

PipeOpReweightingOversampling

Oversamples a [Task](#) for more balanced ratios in subgroups and protected groups. Can be used if a learner does not support weights. Caution: Only fairness tasks are supported. Which means tasks need to have protected field. `tskcol_rolespta`.

Construction

```
PipeOpReweighting*$new(id = "reweighing", param_vals = list())
```

- `id` (`character(1)`).
- `param_vals` (`list()`)

Input and Output Channels

Input and output channels are inherited from [PipeOpTaskPreproc](#). Instead of a [Task](#), a [TaskClassif](#) is used as input and output during training and prediction.

The output during training is the input [Task](#) with added weights column according to target class. The output during prediction is the unchanged input.

State

The `$state` is a named list with the `$state` elements inherited from [PipeOpTaskPreproc](#).

Parameters

- `alpha` (`numeric()`): A number between 0 (no debiasing) and 1 (full debiasing).

Internals

Introduces, or overwrites, the "weights" column in the [Task](#). However, the [Learner](#) method needs to respect weights for this to have an effect.

The newly introduced column is named `reweighing.WEIGHTS`; there will be a naming conflict if this column already exists and is *not* a weight column itself.

Fields

Only fields inherited from [PipeOpTaskPreproc/PipeOp](#).

Methods

Methods inherited from [PipeOpTaskPreproc/PipeOp](#).

Super classes

`mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpTaskPreproc -> PipeOpReweightingWeights`

Methods**Public methods:**

- [PipeOpReweightingWeights\\$new\(\)](#)
- [PipeOpReweightingWeights\\$clone\(\)](#)

Method `new()`: Creates a new instance of this `[R6][R6::R6Class][PipeOp]` R6 class.

Usage:

```
PipeOpReweightingWeights$new(id = "reweighing_wts", param_vals = list())
```

Arguments:

`id` character

The PipeOps identifier in the PipeOps library.

`param_vals` list

The parameter values to be set.

- `alpha`: controls the proportion between initial weight (1 if non existing) and reweighing weight. Defaults to 1. Here is how it works: $\text{new_weight} = (1 - \alpha) * 1 + \alpha * \text{reweighing_weight}$ $\text{final_weight} = \text{old_weight} * \text{new_weight}$

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpReweightingWeights$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Super classes

`mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpTaskPreproc -> PipeOpReweightingOversampling`

Methods

Public methods:

- [PipeOpReweighingOversampling\\$new\(\)](#)
- [PipeOpReweighingOversampling\\$clone\(\)](#)

Method `new()`:

Usage:

```
PipeOpReweighingOversampling$new(id = "reweighing_os", param_vals = list())
```

Arguments:

id ‘character’

The PipeOp’s id.

param_vals ‘list’

A list of parameter values.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpReweighingOversampling$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

References

Kamiran, Faisal, Calders, Toon (2012). “Data preprocessing techniques for classification without discrimination.” *Knowledge and Information Systems*, **33**(1), 1–33.

See Also

<https://mlr3book.mlr-org.com/list-pipeops.html>

Other PipeOps: [mlr_pipeops_equalized_odds](#), [mlr_pipeops_explicit_pta](#)

Examples

```
library(mlr3pipelines)

reweighing = po("reweighing_wts")
learner_po = po("learner", learner = lrn("classif.rpart"))

data = tsk("adult_train")
graph = reweighing %>>% learner_po
glrn = GraphLearner$new(graph)
glrn$train(data)
tem = glrn$predict(data)
tem$confusion
```

report_datasheet	<i>Create a Datasheet for Documenting a Dataset</i>
------------------	---

Description

Creates a new **rmarkdown** template with a skeleton questionnaire for dataset documentation. Uses the awesome markdown template created by Chris Garbin [from Github](#).

Usage

```
report_datasheet(filename = "datasheet.Rmd", edit = FALSE, build = FALSE)
```

Arguments

filename	(character(1)) File path or name for new file that should be created.
edit	(logical(1)) TRUE to edit the template immediately.
build	(logical(1)) Should the report be built after creation? Initialized to FALSE.

Value

Invisibly returns the path to the newly created file(s).

References

Gebu, Timnit, Morgenstern, Jamie, Vecchione, Briana, Vaughan, Wortman J, Wallach, Hanna, III D, Hal, Crawford, Kate (2018). "Datasheets for datasets." *arXiv preprint arXiv:1803.09010*.

See Also

Other fairness_reports: [report_fairness\(\)](#), [report_modelcard\(\)](#)

Examples

```
report_file = tempfile()
report_datasheet(report_file)
```

report_fairness *Create a Fairness Report*

Description

Creates a new **rmarkdown** template with a skeleton of reported metrics and visualizations. Uses the awesome markdown template created by Chris Garbin [from Github](#).

Usage

```
report_fairness(  
  filename = "fairness_report.Rmd",  
  objects,  
  edit = FALSE,  
  check_objects = FALSE,  
  build = FALSE  
)
```

Arguments

filename	(character(1)) File path or name for new file that should be created.
objects	(list()) A named list of objects required for the fairness report. Objects are saved as <name>.rds in the new folder created for the report. <ul style="list-style-type: none">task :: The Task a report should be created for.resample_result :: A mlr3::ResampleResult result to be analyzed.... :: any other objects passed on for the report.
edit	(logical(1)) TRUE to edit the template immediately.
check_objects	(logical(1)) Should items in objects be checked? If FALSE, no checks on object are performed.
build	(logical(1)) Should the report be built after creation? Initialized to FALSE.

Value

Invisibly returns the path to the newly created file(s).

See Also

Other fairness_reports: [report_datasheet\(\)](#), [report_modelcard\(\)](#)

Examples

```
report_file = tempfile()
task = tsk("compas")
learner = lrn("classif.rpart", predict_type = "prob")
rr = resample(task, learner, rsmpl("cv", folds = 3L))
report_fairness(report_file, list(task = task, resample_result = rr))
```

report_modelcard *Create a Modelcard*

Description

Creates a new **markdown** template with a skeleton questionnaire for a model card. Uses the awesome markdown template created by Chris Garbin [from Github](#).

Usage

```
report_modelcard(filename = "modelcard.Rmd", edit = FALSE, build = FALSE)
```

Arguments

filename	(character(1)) File path or name for new file that should be created.
edit	(logical(1)) TRUE to edit the template immediately.
build	(logical(1)) Should the report be built after creation? Initialized to FALSE.

Value

Invisibly returns the path to the newly created file(s).

References

Mitchell, Margaret, Wu, Simone, Zaldivar, Andrew, Barnes, Parker, Vasserman, Lucy, Hutchinson, Ben, Spitzer, Elena, Raji, Deborah I, Gebru, Timnit (2019). "Model cards for model reporting." In *Proceedings of the conference on fairness, accountability, and transparency*, 220–229.

See Also

Other fairness_reports: [report_datasheet\(\)](#), [report_fairness\(\)](#)

Examples

```
report_file = tempfile()
report_modelcard(report_file)
```

`task_summary`*Task summary for fairness report*

Description

Create the general task documentation in a dataframe for fairness report. The information includes

- Audit Date
- Task Name
- Number of observations
- Number of features
- Target Name
- Feature Names
- The Protected Attribute

Usage

```
task_summary(task)
```

Arguments

`task` [Task](#)

Value

`data.frame` containing the reported information

Examples

```
task_summary(tsk("adult_train"))
```

Index

- * **PipeOps**
 - mlr_pipeops_equalized_odds, 20
 - mlr_pipeops_explicit_pta, 22
 - mlr_pipeops_reweighing, 24
- * **datasets**
 - mlr_learners_fairness, 17
 - mlr_measures_fairness, 18
- * **data**
 - adult, 2
 - compas, 5
- * **fairness_reports**
 - report_datasheet, 27
 - report_fairness, 28
 - report_modelcard, 29

- adult, 2
- adult_test (adult), 2
- adult_train (adult), 2

- BenchmarkResult, 4, 6–8

- character, 8
- compare_metrics, 3
- Compas (compas), 5
- compas, 5, 5

- data.table(), 9
- dictionary, 11

- fairness_accuracy_tradeoff, 6
- fairness_prediction_density, 7
- fairness_tensor, 8

- groupdiff_absdiff, 12
- groupdiff_absdiff (groupdiff_tau), 9
- groupdiff_absdiff(), 11
- groupdiff_diff (groupdiff_tau), 9
- groupdiff_tau, 9
- groupdiff_tau(), 11
- groupwise_metrics, 10, 17

- Learner, 24, 25
- logical, 10, 16

- mean(), 13
- Measure, 4, 7
- MeasureFairness, 11, 13, 17, 18
- MeasureFairnessComposite, 11, 12, 13
- MeasureFairnessConstraint, 14
- MeasurePositiveProbability
 - (mlr_measures_positive_probability), 19
- MeasureSubgroup, 11, 16, 18
- mlr3::Measure, 10, 11, 13, 14, 16, 19
- mlr3::Measure(), 11, 16
- mlr3::ResampleResult, 28
- mlr3::Task(), 10
- mlr3pipelines::PipeOp, 21, 23, 25
- mlr3pipelines::PipeOpTaskPreproc, 23, 25
- mlr_learners_fairness, 17
- mlr_measures, 11
- mlr_measures_classif.ce, 11
- mlr_measures_classif.fpr, 11, 16
- mlr_measures_fairness, 18
- mlr_measures_positive_probability, 19
- mlr_pipeops_equalized_odds, 20, 23, 26
- mlr_pipeops_explicit_pta, 21, 22, 26
- mlr_pipeops_reweighing, 21, 23, 24
- msr(classif.acc), 7

- PipeOp, 20, 22–25
- PipeOpEOd (mlr_pipeops_equalized_odds), 20
- PipeOpExplicitPta
 - (mlr_pipeops_explicit_pta), 22
- PipeOpReweighingOversampling
 - (mlr_pipeops_reweighing), 24
- PipeOpReweighingWeights
 - (mlr_pipeops_reweighing), 24
- PipeOpTaskPreproc, 20, 22–25

PredictionClassif, [4](#), [6–9](#), [20](#)

R6, [11](#), [13](#), [14](#), [16](#)

R6: :R6Class, [5](#)

R6Class, [20](#), [22](#), [24](#)

report_datasheet, [27](#), [28](#), [29](#)

report_fairness, [27](#), [28](#), [29](#)

report_modelcard, [27](#), [28](#), [29](#)

ResampleResult, [4](#), [6–9](#)

Task, [6](#), [8](#), [10](#), [18](#), [20](#), [22](#), [24](#), [25](#), [28](#), [30](#)

task_summary, [30](#)

TaskClassif, [4](#), [5](#), [7–9](#), [20](#), [22](#), [24](#)