

Package ‘nakagami’

December 2, 2019

Type Package

Title Functions for the Nakagami Distribution

Version 1.0.0

Description Density, distribution function, quantile function and random generation for the Nakagami distribution of Nakagami (1960) <doi:10.1016/B978-0-08-009306-2.50005-4>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports assertthat

Suggests testthat, knitr, covr, rmarkdown

RoxygenNote 6.1.1

URL <https://github.com/JonasMoss/nakagami>

BugReports <https://github.com/JonasMoss/nakagami/issues>

NeedsCompilation no

Author Jonas Moss [aut, cre] (<<https://orcid.org/0000-0002-6876-6964>>)

Maintainer Jonas Moss <jonas.gjertsen@gmail.com>

Repository CRAN

Date/Publication 2019-12-02 15:40:09 UTC

R topics documented:

Nakagami	2
suppress_olw	3
Index	4

Description

Density, distribution function, quantile function and random generation for the Nakagami distribution with parameters shape and scale.

Usage

```
dnaka(x, shape, scale, log = FALSE)
```

```
pnaka(q, shape, scale, lower.tail = TRUE, log.p = FALSE)
```

```
qnaka(p, shape, scale, lower.tail = TRUE, log.p = FALSE)
```

```
rnaka(n, shape, scale)
```

Arguments

x, q	vector of quantiles.
shape	vector of shape parameters greater than 1/2.
scale	vector of positive scale parameters.
log, log.p	logical; if TRUE, probabilities p are given as log(p).
lower.tail	logical; if TRUE (default), probabilities are $P[X \leq x]$ otherwise, $P[X > x]$.
p	vector of probabilities.
n	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required.

Details

The Nakagami distribution with shape m and scale Ω has density

$$2m^m/\Gamma(m)\Omega^m x^{2m-1} e^{-m/\Omega x^2}$$

for $x \geq 0$, $m \geq 1/2$ and $\Omega > 0$.

If Y is [Gamma](#) distributed with $shape = m$ and $rate = m/\Omega$ then $X = \sqrt{Y}$ is Nakagami distributed with $shape = m$ and $scale = \Omega$.

Value

dnaka gives the density, pnaka gives the distribution function, qnaka gives the quantile function and rnaka generates random deviates.

The length of the result is determined by n for rnaka, and is the maximum of the lengths of the numerical arguments for the other functions.

The numerical arguments other than n are recycled to the length of the result.

References

Nakagami, N. 1960. "The M-Distribution, a General Formula of Intensity of Rapid Fading." In Statistical Methods in Radio Wave Propagation: Proceedings of a Symposium Held at the University of California, edited by William C. Hoffman, 3-36. Permagon Press.

See Also

The [Gamma](#) distribution is closed related to the Nakgami distribution.

suppress_olw

Suppress object length incompatibility warnings

Description

Suppress object length incompatibility warnings

Usage

suppress_olw(expr)

Arguments

expr expression to be evaluated.

Index

dnaka (Nakagami), 2

Gamma, 2, 3

Nakagami, 2

pnaka (Nakagami), 2

qnaka (Nakagami), 2

rnaka (Nakagami), 2

suppress_olw, 3