

Package 'rgeedim'

February 14, 2023

Type Package

Title Search, Composite, and Download 'Google Earth Engine' Imagery with the 'Python' Module 'geedim'

Version 0.2.1

Maintainer Andrew Brown <brown.andrew@gmail.com>

URL <https://humus.rocks/rgeedim/>, <https://github.com/brownag/rgeedim>,
<https://geedim.readthedocs.io/>

BugReports <https://github.com/brownag/rgeedim/issues>

Description Search, composite, and download 'Google Earth Engine' imagery with 'reticulate' bindings for the 'Python' module 'geedim' by Dugal Harris. Read the 'geedim' documentation here: <<https://geedim.readthedocs.io/>>.

Wrapper functions are provided to make it more convenient to use 'geedim' to download images larger than the 'Google Earth Engine' size limit <<https://developers.google.com/earth-engine/apidocs/ee-image-getdownloadurl>>.

By default the ``High Volume'' API endpoint <<https://developers.google.com/earth-engine/cloud/highvolume>> is used to download data and this URL can be customized during initialization of the package.

SystemRequirements Python (>= 3.6.0)

Config/reticulate list(packages = list(list(package =
``earthengine-api"), list(package = ``geedim")))

License Apache License (>= 2)

Language en-US

RoxygenNote 7.2.3

Imports utils, methods, reticulate, jsonlite

Suggests terra, raster, tinytest, knitr, rmarkdown

Depends R (>= 3.5)

Encoding UTF-8

VignetteBuilder knitr

NeedsCompilation no

Author Andrew Brown [aut, cre],
Dugal Harris [cph] ('geedim' 'Python' module)

Repository CRAN

Date/Publication 2023-02-14 14:30:02 UTC

R topics documented:

earthengine	2
gd_authenticate	3
gd_band_names	4
gd_band_properties	4
gd_bbox	5
gd_composite	6
gd_download	6
gd_enum_names	8
gd_export	10
gd_footprint	11
gd_get_asset	12
gd_image_from_id	13
gd_initialize	15
gd_mask_clouds	16
gd_projection	16
gd_properties	17
gd_region	18
gd_search	19
geedim	20
Index	21

earthengine	<i>Get Earth Engine Module(ee) Instance</i>
-------------	---

Description

Gets the ee module instance in use by geedim package in current session.

gd_ee_version() Gets the ee version using importlib.metadata.version()

Usage

```
earthengine()
```

```
gd_ee_version()
```

Value

character. Version Number.

gd_authenticate	<i>Authenticate with Google Earth Engine using gcloud, "Notebook Authenticator" or other method</i>
-----------------	---

Description

Calls `ee.Authenticate(...)` to authenticate with Earth Engine.

Usage

```
gd_authenticate(  
  authorization_code = NULL,  
  quiet = FALSE,  
  code_verifier = NULL,  
  auth_mode = NULL  
)
```

Arguments

authorization_code	Default: NULL
quiet	Suppress warnings, errors, messages? Default: FALSE
code_verifier	Optional code verifier for security Default: NULL
auth_mode	One of "notebook", "gcloud", "appdefault" or (default) NULL to guess based on the environment

Details

This method should be called once to set up a machine/project with a particular authentication method. The `auth_mode="notebook"` argument is very convenient for interactive R use and will take you to a web page where you can sign into your Google Account and get a token to paste into a console prompt.

Value

This function is primarily used for the side-effect of authentication with the 'Google Earth Engine' servers. Invisibly returns `try-error` on error.

Examples

```
## Not run:  
# opens web page to complete authentication/provide authorization code  
gd_authenticate(auth_mode = "notebook")  
  
## End(Not run)
```

gd_band_names *Get Names of Layers in an Earth Engine Image*

Description

Calls bandNames() method from ee.Image class.

Usage

```
gd_band_names(x)
```

Arguments

x a Google Earth Engine Image object, such as from gd_image_from_id()

Value

character. Vector of names of each layer in an image.

Examples

```
if (gd_is_initialized())  
  gd_band_names(gd_image_from_id("USGS/NED"))
```

gd_band_properties *Get Properties of Layers in an Earth Engine Image*

Description

Gets combined Earth Engine and STAC properties.

Usage

```
gd_band_properties(x)
```

Arguments

x a Google Earth Engine Image object, such as from gd_image_from_id()

Value

list. Each element is a list that corresponds to a layer in x, each with one or more elements for properties of that layer.

Examples

```
if (gd_is_initialized())
    gd_band_properties(gd_image_from_id("USGS/NED"))
```

gd_bbox

Prepare Bounding Box Region from X/Y Limits

Description

Create a bounding box polygon Python object for use with `gd_download()`. The coordinates of the bounding box are expressed in WGS84 decimal degrees ("OGC:CRS84").

Usage

```
gd_bbox(...)
```

Arguments

... Either a single terra `SpatExtent` object or arguments: `xmin/ymax/xmax/ymin`. If the four bounding arguments are not named they should be in order.

Details

Expecting total of 4 bounding box arguments, If arguments are unnamed they should be in the following order: "xmin", "ymax", "xmax", "ymin".

Value

a *list* object describing a GeoJSON bounding rectangular polygon suitable for use as regions argument to `gd_download()` or `gd_search()`

Examples

```
gd_bbox(
    xmin = 5.744140,
    ymax = 50.18162,
    xmax = 6.528252,
    ymin = 49.44781
)
```

gd_composite	<i>Composite an Image Collection</i>
--------------	--------------------------------------

Description

Create a composite image from elements of an image collection.

Usage

```
gd_composite(x, ...)
```

Arguments

x	an object inheriting from <code>geedim.collection.MaskedCollection</code> , such as from <code>gd_search()</code> or <code>gd_collection_from_list()</code>
...	additional arguments to <code>geedim.collection.MaskedCollection\$composite()</code>

Value

a composite `geedim.mask.MaskedImage` object

Examples

```
b <- terra::vect('POLYGON((-121.355 37.56,-121.355 37.555,
                        -121.35 37.555,-121.35 37.56,
                        -121.355 37.56))',
                crs = "OGC:CRS84")

if (gd_is_initialized())
  gd_composite(gd_search(gd_collection_from_name("USGS/3DEP/1m"),
                        region = gd_region(b)),
              resampling = "bilinear")
```

gd_download	<i>Download a Google Earth Engine Image</i>
-------------	---

Description

Download a Google Earth Engine Image

Usage

```
gd_download(
  x,
  filename = tempfile(fileext = ".tif"),
  region = NULL,
  composite = TRUE,
  overwrite = TRUE,
  silent = TRUE,
  ...
)
```

Arguments

<code>x</code> ,	ID or Name, or a reference to an object inheriting from <code>geedim.download.BaseImage</code> or <code>geedim.collection.MaskedCollection</code>
<code>filename</code>	path to output file, defaults to temporary GeoTIFF file path; if <code>composite=FALSE</code> then this path should be to a parent directory. File names will be calculated from the internal name of the image and the requested scale.
<code>region</code>	a GeoJSON-like list, or other R spatial object describing region of interest, see <code>gd_region()</code> and <code>gd_bbox()</code> for details. <code>NULL</code> region (default) will download the whole image.
<code>composite</code>	logical. Composite Image Collection into single image for download? Default: <code>TRUE</code>
<code>overwrite</code>	Overwrite existing file? Default: <code>TRUE</code>
<code>silent</code>	Silence errors? Default: <code>TRUE</code>
<code>...</code>	Additional arguments (e.g. <code>scale</code>) passed to <code>geedim.mask.MaskedImage\$download(...)</code> and, when <code>composite=TRUE</code> , <code>geedim.collection.MaskedCollection\$composite()</code>

Details

The `region` argument is *optional* for downloading images. When downloading a composite Image Collection, you must specify `region`, `scale` and `crs` arguments. When downloading an image collection as a set of GeoTIFF files (`composite=FALSE`), then `filename` is the destination directory, and `scale` must be specified. The default resampling method in `geedim` is `resampling="near"` (Nearest Neighbor). Other options for resampling include: `"average"`, `"bicubic"`, `"bilinear"`. See `gd_resampling_methods()`.

Value

Invisible path to downloaded image, or `try-error` on error

See Also

`gd_region()` `gd_bbox()`

Examples

```
r <- gd_bbox(  
  xmin = -121,  
  xmax = -120.5,  
  ymin = 38.5,  
  ymax = 39  
)  
  
if (gd_is_initialized()) {  
  x <- gd_image_from_id('CSP/ERGo/1_0/Global/SRTM_topoDiversity')  
  tf <- tempfile(fileext = ".tif")  
  
  # fast sample download at 10x aggregation (900m v.s. 90m)  
  img <- gd_download(x, filename = tf,  
                    region = r, scale = 900,  
                    overwrite = TRUE, silent = FALSE)  
  
  if (requireNamespace("terra")) {  
    library(terra)  
    f <- rast(img)  
    plot(f[[1]])  
    # inspect object  
    f  
  }  
  unlink(tf)  
}
```

gd_enum_names

geedim *Enums*

Description

geedim Enums

Usage

gd_enum_names()

gd_enum_elements(enum = gd_enum_names())

gd_resampling_methods()

gd_cloud_mask_methods()

gd_composite_methods()


```
gd_export_types()
```

Arguments

enum Enum name, one or more of: "CloudMaskMethod", "CompositeMethod", "ResamplingMethod"

Value

`gd_enum_names()`: character vector containing names of Enums

`gd_enum_elements()`: element values of an Enum

`gd_resampling_methods()`: character vector of resampling methods (Enum "ResamplingMethod")

`gd_cloud_mask_methods()`: character vector of cloud mask methods (Enum "CloudMaskMethod")

`gd_composite_methods()`: character vector of composite methods (Enum "CompositeMethod")

`gd_export_types()`: character vector of export types (Enum "ExportType")

Examples

```
if (gd_is_initialized())  
  gd_enum_names()
```

```
if (gd_is_initialized())  
  gd_enum_elements()
```

```
if (gd_is_initialized())  
  gd_resampling_methods()
```

```
if (gd_is_initialized())  
  gd_cloud_mask_methods()
```

```
if (gd_is_initialized())  
  gd_composite_methods()
```

```
if (gd_is_initialized())
```

```
gd_export_types()
```

gd_export	<i>Export image to Earth Engine Asset, Google Cloud Storage Bucket, or Google Drive</i>
-----------	---

Description

Exports an encapsulated image to the destination specified by type, folder and filename

Usage

```
gd_export(
  x,
  filename,
  type = "drive",
  folder = dirname(filename),
  region,
  wait = TRUE,
  ...
)
```

Arguments

x	An object that inherits from <code>geedim.download.BaseImage</code>
filename	Output filename. If type is "asset" and folder is not specified, filename should be a valid Earth Engine asset ID.
type	Export type. Defaults to "drive"; other options include "asset", and "cloud". See <code>gd_export_types()</code>
folder	Destination folder. Defaults to <code>dirname(filename)</code> .
region	Region e.g. from <code>gd_bbox()</code> or <code>gd_region()</code>
wait	Wait for completion? Default: TRUE
...	Additional arguments to <code>geedim.download.BaseImage.export()</code>

Details

See the [geedim.mask.MaskedImage.export\(\) documentation](#) for details on additional arguments. Requires 'geedim' >1.6.0.

Value

an `ee.batch.Task` object

Examples

```
## Not run:
if (gd_is_initialized()) {
  r <- gd_bbox(
    xmin = -120.6032,
    xmax = -120.5377,
    ymin = 38.0807,
    ymax = 38.1043
  )

  i <- gd_image_from_id('CSP/ERGo/1_0/US/CHILI')

  ## export to Google Drive (default `type="drive"`)
  # res <- gd_export(i, filename = "RGEEDIM_TEST.tif", scale = 100, region = r)

  ## export to `type="asset"`, then download by ID (stored in project assets)
  # res <- gd_export(
  #   i,
  #   "RGEEDIM_TEST",
  #   type = "asset",
  #   folder = "your-project-name",
  #   scale = 100,
  #   region = r
  # )
  # gd_download("projects/your-project-name/assets/RGEEDIM_TEST", filename = "test.tif")

  ## export to Google Cloud Bucket with `type="cloud"`,
  ##   where `folder` is the bucket path without `gs://`
  # res <- gd_export(i, filename = "RGEEDIM_TEST.tif", type = "cloud",
  #                 folder = "your-bucket-name", scale = 100, region = r)
}

## End(Not run)
```

gd_footprint

Get Footprint of Masked Image

Description

Gets GeoJSON-style list containing footprint of a `geedim.mask.MaskedImage` object

Usage

```
gd_footprint(x)
```

Arguments

x a `geedim.mask.MaskedImage` object

Value

list.

Examples

```
if (gd_is_initialized())
  gd_footprint(gd_image_from_id("USGS/NED"))
```

 gd_get_asset

Get, Update, or Delete an Earth Engine Asset by ID

Description

Get, Update, or Delete an Earth Engine Asset by ID

Usage

```
gd_get_asset(x, silent = FALSE)

gd_update_asset(
  x,
  asset,
  update = c("start_time", "end_time", "properties"),
  silent = FALSE
)

gd_delete_asset(x, silent = FALSE)
```

Arguments

x	Asset ID name
silent	Silence errors? Default: FALSE
asset	Used only for gd_update_asset(): a named list, with names representing elements of x to replace. Only "start_time", "end_time", and "properties" fields can be updated.
update	Used only for gd_update_asset(): A character vector of field names to update. Default: "start_time", and "end_time" to update timestamps; and "properties" to update all properties.

Value

try-error on error. gd_get_asset(): a named list containing information and properties of an Earth Engine asset

gd_update_asset(): This function is called for side-effects (updates the specified asset fields)

gd_delete_asset(): This function is called for side-effects (deletes the specified asset)

Examples

```
## Not run:
# get asset from project by ID
a <- gd_get_asset("projects/your-project-name/assets/YOUR_ASSET_ID")

## End(Not run)
## Not run:
# change description in `properties`
a$properties$description <- "foo"

# update asset
gd_update_asset("projects/your-project-name/assets/YOUR_ASSET_ID", a, "properties")

## End(Not run)
## Not run:
# remove an asset from project
gd_delete_asset("projects/your-project-name/assets/YOUR_ASSET_ID")

## End(Not run)
```

gd_image_from_id	<i>Reference Google Earth Engine Image or Image Collection by ID or Name</i>
------------------	--

Description

Create references to a Google Earth Engine Image or Image Collection based on IDs or names, or combine Images into Image Collections.

Usage

```
gd_image_from_id(x)

gd_collection_from_name(x)

gd_collection_from_list(x)

gd_asset_id(filename, folder = NULL)
```

Arguments

<code>x</code>	character. id of Image, name of Image Collection, or a vector of Image id to create a new Image Collection
<code>filename</code>	File or Asset Name
<code>folder</code>	Optional: Project Name

Value

`geedim.MaskedImage` or `geedim.MaskedCollection` object, or try-error on error

Examples

```

if (gd_is_initialized())
  gd_image_from_id('CSP/ERGo/1_0/Global/SRTM_topoDiversity')

if (gd_is_initialized())

  # Find 1m DEMs in arbitrary extent
  r <- gd_bbox(xmin = -121.4, xmax = -121.35, ymin = 37.55, ymax = 37.6)

  # collection of individual tiles of DEM
  x <- gd_collection_from_name("USGS/3DEP/1m")

  # search within region
  y <- gd_search(x, r)

  gd_properties(y)

if (gd_is_initialized())
  # Find 1m DEM in arbitrary extent
  r <- gd_bbox(xmin = -121.4, xmax = -121.35, ymin = 37.55, ymax = 37.6)

  # collection of individual tiles of DEM
  x <- gd_collection_from_name("USGS/3DEP/1m")

  # search within region
  y <- gd_search(x, r)

  # select images with fill > 0
  z <- subset(gd_properties(y), fill > 0)

  # create encapsulated images from IDs returned by search

```

```
l <- lapply(z$id, gd_image_from_id)

# create a new collection from the list of images
gd_collection_from_list(l)

if (gd_is_initialized())
  gd_asset_id("RGEEDIM_TEST", "your-project-name")
```

gd_initialize	<i>Initialize</i> geedim
---------------	--------------------------

Description

Calls `geedim Initialize()` method. This method should be called at the beginning of each session.

Usage

```
gd_initialize(
  private_key_file = NULL,
  opt_url = "https://earthengine-highvolume.googleapis.com",
  quiet = TRUE
)

gd_is_initialized()
```

Arguments

<code>private_key_file</code>	Optional: Path to JSON file containing client information and private key.
<code>opt_url</code>	Base URL for API requests; defaults to "High Volume": "https://earthengine-highvolume.googleapis.com"
<code>quiet</code>	Suppress error messages on load? Default: FALSE

Value

`gd_initialize()`: try-error (invisibly) on error.
`gd_is_initialized()`: logical. TRUE if initialized successfully.

See Also

`gd_authenticate()`

Examples

```
gd_initialize()
gd_is_initialized()
```

gd_mask_clouds	<i>Mask Clouds or Apply Fill Mask</i>
----------------	---------------------------------------

Description

Apply the cloud/shadow mask if supported, otherwise apply the fill mask.

Usage

```
gd_mask_clouds(x)
```

Arguments

x a `geedim.mask.MaskedImage`

Value

a `geedim.mask.MaskedImage`

gd_projection	<i>Get Projection Information from Google Earth Engine Asset</i>
---------------	--

Description

Get Projection Information from Google Earth Engine Asset

Usage

```
gd_projection(x)
```

Arguments

x character ID referencing asset, or an image object (subclass of `ee.image.Image` or `geedim.download.BaseImage`)

Value

`ee.Projection` object

Examples

```
if (gd_is_initialized())
  gd_projection(gd_image_from_id('CSP/ERGo/1_0/Global/SRTM_topoDiversity'))
```

gd_properties

Get Properties of an Image Collection

Description

Get Properties of an Image Collection

Usage

```
gd_properties(x)
```

Arguments

x geedim.collection.MaskedCollection object

Value

data.frame containing properties table from x; NULL if no properties table.

Examples

```
b <- terra::vect('POLYGON((-121.355 37.56,-121.355 37.555,
                        -121.35 37.555,-121.35 37.56,
                        -121.355 37.56))',
                crs = "OGC:CRS84")

if (gd_is_initialized()) {
  x <- gd_search(gd_collection_from_name("USGS/3DEP/1m"),
                region = gd_region(b))
  gd_properties(x)
}
```

gd_region	<i>Create GeoJSON Region from R Spatial Objects</i>
-----------	---

Description

Creates a suitable input for the region argument to `gd_download(<Image>)` or `gd_search()` for Image Collections.

Usage

```
gd_region(x)
```

Arguments

`x` either a WKT string (character), a terra `SpatRaster(Collection)/SpatVector(Collection)/SpatExtent`, an sf object, an sp `Spatial*` object or a raster `RasterLayer/RasterStack`.

Details

If `x` is an R spatial object, each vertex (possibly after converting object extent to vector) is used to create the GeoJSON object. Otherwise, the extent is determined and passed to `gd_bbox()`.

Value

list representing a GeoJSON extent

See Also

`gd_bbox()`

Examples

```
b <- terra::vect('POLYGON((-121.355 37.56,-121.355 37.555,
                        -121.35 37.555,-121.35 37.56,
                        -121.355 37.56))',
                crs = "OGC:CRS84")
gd_region(b)
```

gd_search

Search an Image Collection

Description

Search an Image Collection

Usage

```
gd_search(
  x,
  region,
  start_date = "2000-01-01",
  end_date = as.character(Sys.Date()),
  ...
)
```

Arguments

x	geedim.collection.MaskedCollection object
region	list / Python GeoJSON object describing region, e.g. as created by gd_bbox()
start_date	Default: '2020-01-01'
end_date	Default: Sys.Date()
...	additional arguments to geedim.MaskedCollection.search() e.g. cloudless_portion, fill_portion

Value

geedim.MaskedCollection object suitable for querying properties

Examples

```
b <- terra::vect('POLYGON((-121.355 37.56,-121.355 37.555,
                        -121.35 37.555,-121.35 37.56,
                        -121.355 37.56))',
                crs = "OGC:CRS84")
if (gd_is_initialized())
  gd_search(gd_collection_from_name("USGS/3DEP/1m"),
            region = gd_region(b))
```

geedim	Module(geedim) - <i>Get geedim Module Instance</i>
--------	--

Description

Gets the geedim module instance in use by the package in current **R**/reticulate session.

Usage

```
geedim()
```

```
gd_version()
```

Value

character. Version Number.

Index

earthengine, 2

gd_asset_id (gd_image_from_id), 13

gd_authenticate, 3

gd_band_names, 4

gd_band_properties, 4

gd_bbox, 5

gd_cloud_mask_methods (gd_enum_names), 8

gd_collection_from_list
 (gd_image_from_id), 13

gd_collection_from_name
 (gd_image_from_id), 13

gd_composite, 6

gd_composite_methods (gd_enum_names), 8

gd_delete_asset (gd_get_asset), 12

gd_download, 6

gd_ee_version (earthengine), 2

gd_enum_elements (gd_enum_names), 8

gd_enum_names, 8

gd_export, 10

gd_export_types (gd_enum_names), 8

gd_footprint, 11

gd_get_asset, 12

gd_image_from_id, 13

gd_initialize, 15

gd_is_initialized (gd_initialize), 15

gd_mask_clouds, 16

gd_projection, 16

gd_properties, 17

gd_region, 18

gd_resampling_methods (gd_enum_names), 8

gd_search, 19

gd_update_asset (gd_get_asset), 12

gd_version (geedim), 20

geedim, 20