

# Package ‘statsExpressions’

February 19, 2021

**Type** Package

**Title** Expressions and Dataframes with Statistical Details

**Version** 0.7.1

**Maintainer** Indrajeet Patil <patilindrajeet.science@gmail.com>

**Description** Statistical processing backend for 'ggstatsplot', this package creates expressions with details from statistical tests. It can additionally return dataframes with these results, which also make these functions a more pipe-friendly way to do statistical analysis. Currently, it supports only the most common types of statistical approaches and tests: parametric, nonparametric, robust, and Bayesian versions of t-test/ANOVA, correlation analyses, contingency table analysis, and meta-analysis.

**License** GPL-3 | file LICENSE

**URL** <https://indrajeetpatil.github.io/statsExpressions/>,  
<https://github.com/IndrajeetPatil/statsExpressions>

**BugReports** <https://github.com/IndrajeetPatil/statsExpressions/issues>

**Depends** R (>= 3.6.0)

**Imports** afex,  
BayesFactor,  
correlation (>= 0.6.0),  
dplyr,  
effectsize (>= 0.4.3),  
insight (>= 0.13.0),  
ipmisc (>= 6.0.0),  
parameters (>= 0.11.0),  
performance,  
rlang,  
stats,  
tidyr,  
WRS2 (>= 1.1-1)

**Suggests** ggplot2,  
knitr,  
metaBMA,  
metafor,  
metaplust,  
purrr,

```
rmarkdown,
spelling,
testthat,
utils
```

**VignetteBuilder** knitr

**Encoding** UTF-8

**Language** en-US

**LazyData** true

**Roxygen** list(markdown = TRUE, roclets = c("`rd", ``namespace", ``collate", ``pkgapi::api\_roclet"))

**RoxygenNote** 7.1.1.9001

**Config/testthat/edition** 3

**Config/testthat/parallel** true

## R topics documented:

|                                 |    |
|---------------------------------|----|
| bf_extractor . . . . .          | 2  |
| bugs_long . . . . .             | 3  |
| expr_contingency_tab . . . . .  | 4  |
| expr_corr_test . . . . .        | 6  |
| expr_meta_random . . . . .      | 8  |
| expr_oneway_anova . . . . .     | 10 |
| expr_template . . . . .         | 13 |
| expr_t_onesample . . . . .      | 15 |
| expr_t_twosample . . . . .      | 17 |
| iris_long . . . . .             | 21 |
| movies_long . . . . .           | 22 |
| movies_wide . . . . .           | 23 |
| tidy_model_effectsize . . . . . | 24 |
| tidy_model_parameters . . . . . | 24 |
| VR_dilemma . . . . .            | 25 |

**Index** **26**

---

|              |   |
|--------------|---|
| bf_extractor | <i>Extract Bayes Factors from BayesFactor model object.</i> |
|--------------|---|

---

### Description

Extract Bayes Factors from BayesFactor model object.

### Usage

```
bf_extractor(
  bf.object,
  conf.level = 0.95,
  k = 2L,
  top.text = NULL,
  output = "dataframe",
  ...
)
```

**Arguments**

|            |   |
|------------|---|
| bf.object  | An object from BayesFactor package.   |
| conf.level | Confidence/Credible Interval (CI) level. Default to 0.95 (95%).   |
| k          | Number of digits after decimal point (should be an integer) (Default: k = 2L).  |
| top.text   | Text to display on top of the Bayes Factor message. This is mostly relevant in the context of ggstatsplot functions.                |
| output     | If "expression", will return expression with statistical details, while "dataframe" will return a dataframe containing the results. |
| ...        | Additional arguments passed to <code>parameters::model_parameters.BFBayesFactor()</code> .  |

**Note**

*Important:* don't enter `1/bf.object` to extract results for null hypothesis; doing so will return wrong results.

**Examples**

```
# setup
library(statsExpressions)
set.seed(123)

# creating a `BayesFactor` object
bf_obj <-
  BayesFactor::anovaBF(
    formula = Sepal.Length ~ Species,
    data = iris,
    progress = FALSE
  )

# extracting Bayes Factors in a dataframe
bf_extractor(bf_obj)
```

---

 bugs\_long

*Tidy version of the "Bugs" dataset.*


---

**Description**

Tidy version of the "Bugs" dataset.

**Usage**

```
bugs_long
```

## Format

A data frame with 372 rows and 6 variables

- subject. Dummy identity number for each participant.
- gender. Participant's gender (Female, Male).
- region. Region of the world the participant was from.
- education. Level of education.
- condition. Condition of the experiment the participant gave rating for (**LDLF**: low frighteningness and low disgustingness; **LFHD**: low frighteningness and high disgustingness; **HFHD**: high frighteningness and low disgustingness; **HFHD**: high frighteningness and high disgustingness).
- desire. The desire to kill an arthropod was indicated on a scale from 0 to 10.

## Details

This data set, "Bugs", provides the extent to which men and women want to kill arthropods that vary in frighteningness (low, high) and disgustingness (low, high). Each participant rates their attitudes towards all anthropods. Subset of the data reported by Ryan et al. (2013).

## Source

<https://www.sciencedirect.com/science/article/pii/S0747563213000277>

## Examples

```
dim(bugs_long)
head(bugs_long)
dplyr::glimpse(bugs_long)
```

---

expr\_contingency\_tab *Expression and dataframe for contingency table analysis*

---

## Description

### Maturing

A dataframe containing results from for contingency table analysis or goodness of fit test.

For more details, see- [https://indrajeetpatil.github.io/statsExpressions/articles/stats\\_details.html](https://indrajeetpatil.github.io/statsExpressions/articles/stats_details.html)

## Usage

```
expr_contingency_tab(  
  data,  
  x,  
  y = NULL,  
  paired = FALSE,  
  type = "parametric",  
  counts = NULL,  
  ratio = NULL,
```

```

    k = 2L,
    conf.level = 0.95,
    sampling.plan = "indepMulti",
    fixed.margin = "rows",
    prior.concentration = 1,
    top.text = NULL,
    output = "expression",
    ...
  )

```

### Arguments

|                     |  |
|---------------------|--|
| data                | A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will <b>not</b> be accepted.  |
| x                   | The variable to use as the <b>rows</b> in the contingency table.   |
| y                   | The variable to use as the <b>columns</b> in the contingency table. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run for the x variable. Otherwise association test will be carried out.  |
| paired              | Logical indicating whether data came from a within-subjects or repeated measures design study (Default: FALSE). If TRUE, McNemar's test expression will be returned. If FALSE, Pearson's chi-square test will be returned.   |
| type                | A character specifying the type of statistical approach. Four possible options: <ul style="list-style-type: none"> <li>"parametric"</li> <li>"nonparametric"</li> <li>"robust"</li> <li>"bayes"</li> </ul> <p>Corresponding abbreviations are also accepted: "p" (for parametric), "np" (for nonparametric), "r" (for robust), or "bf" (for Bayesian).</p>                                     |
| counts              | A string naming a variable in data containing counts, or NULL if each row represents a single observation.   |
| ratio               | A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is NULL, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be <code>ratio = c(0.5, 0.5)</code> or if there are four levels this will be <code>ratio = c(0.25, 0.25, 0.25, 0.25)</code> , etc. |
| k                   | Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code> ).   |
| conf.level          | Confidence/Credible Interval (CI) level. Default to 0.95 (95%).  |
| sampling.plan       | Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see <code>?BayesFactor::contingencyTableBF()</code> .   |
| fixed.margin        | For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".   |
| prior.concentration | Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.  |
| top.text            | Text to display on top of the Bayes Factor message. This is mostly relevant in the context of <code>ggstatsplot</code> functions.  |

output            If "expression", will return expression with statistical details, while "dataframe" will return a dataframe containing the results.

...                Additional arguments (currently ignored).

### Examples

```
# for reproducibility
set.seed(123)
library(statsExpressions)

# ----- non-Bayesian -----

# association test
expr_contingency_tab(
  data = mtcars,
  x = am,
  y = cyl,
  paired = FALSE,
  output = "dataframe"
)

# goodness-of-fit test
expr_contingency_tab(
  data = as.data.frame(HairEyeColor),
  x = Eye,
  counts = Freq,
  ratio = c(0.2, 0.2, 0.3, 0.3)
)

# ----- Bayesian -----

# association test
expr_contingency_tab(
  data = mtcars,
  x = am,
  y = cyl,
  paired = FALSE,
  type = "bayes",
  output = "dataframe"
)

# goodness-of-fit test
expr_contingency_tab(
  data = as.data.frame(HairEyeColor),
  x = Eye,
  counts = Freq,
  ratio = c(0.2, 0.2, 0.3, 0.3),
  type = "bayes"
)
```

## Description

### Maturing

A dataframe containing results from correlation test with confidence intervals for the correlation coefficient estimate. Results are extracted via `correlation::correlation`.

## Usage

```
expr_corr_test(
  data,
  x,
  y,
  type = "parametric",
  k = 2L,
  conf.level = 0.95,
  tr = 0.2,
  bf.prior = 0.707,
  top.text = NULL,
  output = "expression",
  ...
)
```

## Arguments

|            |  |
|------------|--|
| data       | A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will <b>not</b> be accepted.  |
| x          | The column in data containing the explanatory variable to be plotted on the x-axis. Can be entered either as a character string (e.g., "x") or as a bare expression (e.g, x).  |
| y          | The column in data containing the response (outcome) variable to be plotted on the y-axis. Can be entered either as a character string (e.g., "y") or as a bare expression (e.g, y).   |
| type       | A character specifying the type of statistical approach. Four possible options: <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> <p>Corresponding abbreviations are also accepted: "p" (for parametric), "np" (for nonparametric), "r" (for robust), or "bf" (for Bayesian).</p> |
| k          | Number of digits after decimal point (should be an integer) (Default: k = 2L).   |
| conf.level | Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).  |
| tr         | Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of tr, which is by default set to 0.2. Lowering the value might help.  |
| bf.prior   | A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates.   |
| top.text   | Text to display on top of the Bayes Factor message. This is mostly relevant in the context of ggstatsplot functions.   |

output            If "expression", will return expression with statistical details, while "dataframe" will return a dataframe containing the results.

...                Additional arguments (currently ignored).

## References

For more details, see- [https://indrajeetpatil.github.io/statsExpressions/articles/stats\\_details.html](https://indrajeetpatil.github.io/statsExpressions/articles/stats_details.html)

## Examples

```
# for reproducibility
set.seed(123)
library(statsExpressions)

# without changing defaults
expr_corr_test(
  data = ggplot2::midwest,
  x = area,
  y = percblack
)

# changing defaults
expr_corr_test(
  data = ggplot2::midwest,
  x = area,
  y = percblack,
  type = "robust",
  output = "dataframe"
)
```

---

expr\_meta\_random

*Expression and dataframe for random-effects meta-analysis*

---

## Description

### Maturing

A dataframe containing results from random-effects meta-analysis.

For more details, see- [https://indrajeetpatil.github.io/statsExpressions/articles/stats\\_details.html](https://indrajeetpatil.github.io/statsExpressions/articles/stats_details.html)

## Usage

```
expr_meta_random(
  data,
  type = "parametric",
  random = "mixture",
  k = 2L,
  conf.level = 0.95,
  top.text = NULL,
  output = "expression",
  ...
)
```



**Arguments**

|            |   |
|------------|---|
| data       | A dataframe. It <b>must</b> contain columns named estimate (effect sizes or outcomes) and std.error (corresponding standard errors). These two columns will be used for yi and sei arguments in metafor::rma (for parametric analysis) or metaplust::metaplust (for robust analysis), and for y and SE arguments in metaBMA::meta_random (for Bayesian analysis). |
| type       | A character specifying the type of statistical approach. Four possible options: <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> Corresponding abbreviations are also accepted: "p" (for parametric), "np" (for nonparametric), "r" (for robust), or "bf" (for Bayesian).       |
| random     | The type of random effects distribution. One of "normal", "t-dist", "mixture", for standard normal, <i>t</i> -distribution or mixture of normals respectively.  |
| k          | Number of digits after decimal point (should be an integer) (Default: k = 2L).  |
| conf.level | Confidence/Credible Interval (CI) level. Default to 0.95 (95%).   |
| top.text   | Text to display on top of the Bayes Factor message. This is mostly relevant in the context of ggstatsplot functions.  |
| output     | If "expression", will return expression with statistical details, while "dataframe" will return a dataframe containing the results.   |
| ...        | Additional arguments passed to the respective meta-analysis function.   |

**Note**

**Important:** The function assumes that you have already downloaded the needed package (metafor, metaplust, or metaBMA) for meta-analysis.

**Examples**

```
# run examples only if the needed packages are available
if (all(unlist(lapply(
  c("metaplust", "metafor", "metaBMA"), # needed packages
  require,
  character.only = TRUE,
  quietly = TRUE,
  warn.conflicts = FALSE
)))) {
  # note that the `print` calls below are not necessary for you to write
  # they are in the documentation so that the website renders them

  # setup
  set.seed(123)
  library(statsExpressions)

  # renaming to what `statsExpressions` expects
  df <- dplyr::rename(mag, estimate = yi, std.error = sei)

  # ----- parametric -----
```

```

# creating expression
print(expr_meta_random(data = df, output = "dataframe"))

# ----- random -----

# creating expression
print(expr_meta_random(
  data = df,
  type = "random",
  random = "normal",
  output = "dataframe"
))

# ----- Bayes Factor -----

# making expression
expr_meta_random(
  data = df,
  type = "bayes",
  output = "dataframe",
  # additional arguments given to `metaBMA`
  iter = 5000,
  summarize = "integrate",
  control = list(adapt_delta = 0.99, max_treedepth = 15)
)
}

```

---

expr\_oneway\_anova

*Expression and dataframe for one-way ANOVA*


---

## Description

### Maturing

A dataframe containing results for one-way ANOVA.

For more details, see- [https://indrajeetpatil.github.io/statsExpressions/articles/stats\\_details.html](https://indrajeetpatil.github.io/statsExpressions/articles/stats_details.html)

## Usage

```

expr_oneway_anova(
  data,
  x,
  y,
  subject.id = NULL,
  type = "parametric",
  paired = FALSE,
  k = 2L,
  conf.level = 0.95,
  effsize.type = "omega",
  var.equal = FALSE,
  bf.prior = 0.707,
  tr = 0.2,

```

```

  nboot = 100,
  top.text = NULL,
  output = "expression",
  ...
)

```

## Arguments

|              |  |
|--------------|--|
| data         | A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will <b>not</b> be accepted.  |
| x            | The grouping variable from the dataframe data.   |
| y            | The response (a.k.a. outcome or dependent) variable from the dataframe data.   |
| subject.id   | In case of repeated measures design ( <code>paired = TRUE</code> , i.e.), this argument specifies the subject or repeated measures id. Note that if this argument is <code>NULL</code> (which is the default), the function assumes that the data has already been sorted by such an id by the user and creates an internal identifier. So if your data is <b>not</b> sorted and you leave this argument unspecified, the results can be inaccurate. |
| type         | A character specifying the type of statistical approach. Four possible options: <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> Corresponding abbreviations are also accepted: "p" (for parametric), "np" (for nonparametric), "r" (for robust), or "bf" (for Bayesian).  |
| paired       | Logical that decides whether the experimental design is repeated measures/within-subjects or between-subjects. The default is <code>FALSE</code> .   |
| k            | Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code> ).   |
| conf.level   | Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).  |
| effsize.type | Type of effect size needed for <i>parametric</i> tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).  |
| var.equal    | a logical variable indicating whether to treat the two variances as being equal. If <code>TRUE</code> then the pooled variance is used to estimate the variance otherwise the Welch (or Satterthwaite) approximation to the degrees of freedom is used.  |
| bf.prior     | A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates.   |
| tr           | Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of <code>tr</code> , which is by default set to 0.2. Lowering the value might help.  |
| nboot        | Number of bootstrap samples for computing confidence interval for the effect size (Default: 100).  |
| top.text     | Text to display on top of the Bayes Factor message. This is mostly relevant in the context of <code>ggstatsplot</code> functions.  |
| output       | If "expression", will return expression with statistical details, while "dataframe" will return a dataframe containing the results.  |
| ...          | Additional arguments (currently ignored).  |

**Note**

1. Please note that the function expects that the data is already sorted by subject/repeated measures ID.
2. To carry out Bayesian analysis for ANOVA designs, you will need to install the development version of BayesFactor (0.9.12-4.3). You can download it by running: `remotes::install_github("richarddmoo")`

**Examples**

```

# for reproducibility
set.seed(123)
library(statsExpressions)

# ----- parametric -----

# between-subjects
expr_oneway_anova(
  data = ggplot2::msleep,
  x = vore,
  y = sleep_rem
)

# within-subjects design
expr_oneway_anova(
  data = iris_long,
  x = condition,
  y = value,
  subject.id = id,
  paired = TRUE,
  output = "dataframe"
)

# ----- non-parametric -----

# between-subjects
expr_oneway_anova(
  data = ggplot2::msleep,
  x = vore,
  y = sleep_rem,
  type = "np"
)

# within-subjects design
expr_oneway_anova(
  data = iris_long,
  x = condition,
  y = value,
  subject.id = id,
  paired = TRUE,
  type = "np",
  output = "dataframe"
)

# ----- robust -----

# between-subjects

```

```

expr_oneway_anova(
  data = ggplot2::msleep,
  x = vore,
  y = sleep_rem,
  type = "r"
)

# within-subjects design
expr_oneway_anova(
  data = iris_long,
  x = condition,
  y = value,
  subject.id = id,
  paired = TRUE,
  type = "r",
  output = "dataframe"
)

# ----- Bayesian -----

# between-subjects
expr_oneway_anova(
  data = ggplot2::msleep,
  x = vore,
  y = sleep_rem,
  type = "bayes"
)

# within-subjects design
# needs `BayesFactor 0.9.12-4.3` or above
if (utils::packageVersion("BayesFactor") >= package_version("0.9.12-4.3")) {
  expr_oneway_anova(
    data = iris_long,
    x = condition,
    y = value,
    subject.id = id,
    paired = TRUE,
    type = "bayes",
    output = "dataframe"
  )
}

```

---

 expr\_template

*Template for expressions with statistical details*


---

## Description

### Questioning

Creates an expression from a dataframe containing statistical details. Ideally, this dataframe would come from having run `tidy_model_parameters` function on your model object.

This function is currently **not** stable and should not be used outside of this package context.

**Usage**

```

expr_template(
  data,
  no.parameters = 0L,
  bayesian = FALSE,
  statistic.text = NULL,
  effsize.text = NULL,
  top.text = NULL,
  prior.distribution = NULL,
  prior.type = NULL,
  n = NULL,
  n.text = NULL,
  paired = FALSE,
  conf.method = "HDI",
  k = 2L,
  k.df = 0L,
  k.df.error = 0L,
  ...
)

```

**Arguments**

|                    |   |
|--------------------|---|
| data               | A dataframe containing details from the statistical analysis and should contain some or all of the the following columns: <ul style="list-style-type: none"> <li>• <i>statistic</i>: the numeric value of a statistic.</li> <li>• <i>df.error</i>: the numeric value of a parameter being modeled (often degrees of freedom for the test); note that if <code>no.parameters = 0L</code> (e.g., for non-parametric tests), this column will be irrelevant.</li> <li>• <i>df</i> relevant only if the statistic in question has two degrees of freedom (e.g., anova).</li> <li>• <i>p.value</i> the two-sided <i>p</i>-value associated with the observed statistic.</li> <li>• <i>estimate</i>: estimated value of the effect size.</li> <li>• <i>conf.level</i>: width for the confidence intervals.</li> <li>• <i>conf.low</i>: lower bound for effect size estimate.</li> <li>• <i>conf.high</i>: upper bound for effect size estimate.</li> <li>• <i>bf10</i> Bayes Factor value (if <code>bayesian = TRUE</code>).</li> <li>• <i>method</i>: method describing the test carried out.</li> </ul> |
| no.parameters      | An integer that specifies that the number of parameters for the statistical test. Can be 0 for non-parametric tests, 1 for tests based on <i>t</i> -statistic or chi-squared statistic, 2 for tests based on <i>F</i> -statistic.   |
| bayesian           | Is this Bayesian analysis? Defaults to FALSE. The template is slightly different for Bayesian analysis.   |
| statistic.text     | A character that specifies the relevant test statistic. For example, for tests with <i>t</i> -statistic, <code>statistic.text = "t"</code> .  |
| effsize.text       | A character that specifies the relevant effect size.  |
| top.text           | Text to display on top of the Bayes Factor message. This is mostly relevant in the context of <code>ggstatsplot</code> functions.   |
| prior.distribution | A character that specifies the prior type.  |

|                  |   |
|------------------|---|
| prior.type       | The type of prior.  |
| n                | An integer specifying the sample size used for the test.  |
| n.text           | A character that specifies the design, which will determine what the n stands for. If NULL, defaults to <code>quote(italic("n")["pairs"])</code> if <code>paired = TRUE</code> , and to <code>quote(italic("n")["obs"])</code> if <code>paired = FALSE</code> . |
| paired           | Logical that decides whether the experimental design is repeated measures/within-subjects or between-subjects. The default is FALSE.  |
| conf.method      | The type of index used for Credible Interval. Can be "hdi" (default), "eti", or "si" (see <code>si()</code> , <code>hdi()</code> , <code>eti()</code> functions from <code>bayestestR</code> package).  |
| k                | Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code> ).  |
| k.df, k.df.error | Number of decimal places to display for the parameters (default: 0).  |
| ...              | Currently ignored.  |

## Examples

```
set.seed(123)

# creating a dataframe with stats results
stats_df <-
  cbind.data.frame(
    statistic = 5.494,
    df = 29.234,
    p.value = 0.00001,
    estimate = -1.980,
    conf.level = 0.95,
    conf.low = -2.873,
    conf.high = -1.088
  )

# expression for *t*-statistic with Cohen's *d* as effect size
# note that the plotmath expressions need to be quoted
statsExpressions::expr_template(
  no.parameters = 1L,
  data = stats_df,
  statistic.text = quote(italic("t")),
  effsize.text = quote(italic("d")),
  n = 32L,
  k = 3L,
  k.df = 3L
)
```

---

expr\_t\_onesample

*Expression and dataframe for one-sample t-test*

---

## Description

### Maturing

A dataframe containing results from a one-sample test. The exact test and the effect size details contained will depend on the `type` argument.

For more details, see- [https://indrajeetpatil.github.io/statsExpressions/articles/stats\\_details.html](https://indrajeetpatil.github.io/statsExpressions/articles/stats_details.html)

**Usage**

```

expr_t_onesample(
  data,
  x,
  type = "parametric",
  test.value = 0,
  k = 2L,
  conf.level = 0.95,
  tr = 0.2,
  bf.prior = 0.707,
  effsize.type = "g",
  nboot = 100L,
  top.text = NULL,
  output = "expression",
  ...
)

```

**Arguments**

|              |   |
|--------------|---|
| data         | A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will <b>not</b> be accepted.   |
| x            | A numeric variable from the dataframe data.   |
| type         | A character specifying the type of statistical approach. Four possible options: <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> Corresponding abbreviations are also accepted: "p" (for parametric), "np" (for nonparametric), "r" (for robust), or "bf" (for Bayesian). |
| test.value   | A number specifying the value of the null hypothesis (Default: 0).  |
| k            | Number of digits after decimal point (should be an integer) (Default: k = 2L).  |
| conf.level   | Confidence/Credible Interval (CI) level. Default to 0.95 (95%).   |
| tr           | Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of tr, which is by default set to 0.2. Lowering the value might help.   |
| bf.prior     | A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates.  |
| effsize.type | Type of effect size needed for <i>parametric</i> tests. The argument can be "d" (for Cohen's <i>d</i> ) or "g" (for Hedge's <i>g</i> ).   |
| nboot        | Number of bootstrap samples for computing confidence interval for the effect size (Default: 100).   |
| top.text     | Text to display on top of the Bayes Factor message. This is mostly relevant in the context of ggstatsplot functions.  |
| output       | If "expression", will return expression with statistical details, while "dataframe" will return a dataframe containing the results.   |
| ...          | Currently ignored.  |



**Examples**

```

# for reproducibility
set.seed(123)
library(statsExpressions)

# ----- parametric -----

expr_t_onesample(
  data = ggplot2::msleep,
  x = brainwt,
  test.value = 0.275,
  type = "parametric"
)

# ----- non-parametric -----

expr_t_onesample(
  data = ggplot2::msleep,
  x = brainwt,
  test.value = 0.275,
  type = "nonparametric"
)

# ----- robust -----

expr_t_onesample(
  data = ggplot2::msleep,
  x = brainwt,
  test.value = 0.275,
  type = "robust"
)

# ----- Bayesian -----

expr_t_onesample(
  data = ggplot2::msleep,
  x = brainwt,
  test.value = 0.275,
  type = "bayes",
  bf.prior = 0.8
)

```

---

 expr\_t\_twosample

*Expression and dataframe for two-sample t-test*


---

**Description****Maturing**

A dataframe containing details from results of a two-sample test and effect size plus confidence intervals.

For more details, see- [https://indrajeetpatil.github.io/statsExpressions/articles/stats\\_details.html](https://indrajeetpatil.github.io/statsExpressions/articles/stats_details.html)

**Usage**

```

expr_t_twosample(
  data,
  x,
  y,
  subject.id = NULL,
  type = "parametric",
  paired = FALSE,
  k = 2L,
  conf.level = 0.95,
  effsize.type = "g",
  var.equal = FALSE,
  bf.prior = 0.707,
  tr = 0.2,
  nboot = 100,
  top.text = NULL,
  output = "expression",
  ...
)

```

**Arguments**

|              |  |
|--------------|--|
| data         | A dataframe (or a tibble) from which variables specified are to be taken. A matrix or tables will <b>not</b> be accepted.  |
| x            | The grouping variable from the dataframe data.   |
| y            | The response (a.k.a. outcome or dependent) variable from the dataframe data.   |
| subject.id   | In case of repeated measures design (paired = TRUE, i.e.), this argument specifies the subject or repeated measures id. Note that if this argument is NULL (which is the default), the function assumes that the data has already been sorted by such an id by the user and creates an internal identifier. So if your data is <b>not</b> sorted and you leave this argument unspecified, the results can be inaccurate. |
| type         | A character specifying the type of statistical approach. Four possible options: <ul style="list-style-type: none"> <li>• "parametric"</li> <li>• "nonparametric"</li> <li>• "robust"</li> <li>• "bayes"</li> </ul> Corresponding abbreviations are also accepted: "p" (for parametric), "np" (for nonparametric), "r" (for robust), or "bf" (for Bayesian).  |
| paired       | Logical that decides whether the experimental design is repeated measures/within-subjects or between-subjects. The default is FALSE.   |
| k            | Number of digits after decimal point (should be an integer) (Default: k = 2L).   |
| conf.level   | Confidence/Credible Interval (CI) level. Default to 0.95 (95%).  |
| effsize.type | Type of effect size needed for <i>parametric</i> tests. The argument can be "d" (for Cohen's <i>d</i> ) or "g" (for Hedge's <i>g</i> ).  |
| var.equal    | a logical variable indicating whether to treat the two variances as being equal. If TRUE then the pooled variance is used to estimate the variance otherwise the Welch (or Satterthwaite) approximation to the degrees of freedom is used.   |

|          |   |
|----------|---|
| bf.prior | A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates.  |
| tr       | Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of tr, which is by default set to 0.2. Lowering the value might help. |
| nboot    | Number of bootstrap samples for computing confidence interval for the effect size (Default: 100).   |
| top.text | Text to display on top of the Bayes Factor message. This is mostly relevant in the context of ggstatsplot functions.  |
| output   | If "expression", will return expression with statistical details, while "dataframe" will return a dataframe containing the results.                                       |
| ...      | Currently ignored.  |

### Note

The `stats::wilcox.test` function does not follow the same convention as `stats::t.test`. The sign of the  $V$  test statistic will always be positive since it is **the sum of the positive signed ranks**. Therefore,  $V$  will vary in magnitude but not significance based solely on the order of the grouping variable. Consider manually reordering your factor levels if appropriate as shown in the second example below.

### Examples

```
# for reproducibility
set.seed(123)
library(statsExpressions)

# ----- parametric -----

# between-subjects design
expr_t_twosample(
  data = sleep,
  x = group,
  y = extra,
  type = "p"
)

# within-subjects design
expr_t_twosample(
  data = VR_dilemma,
  x = modality,
  y = score,
  paired = TRUE,
  subject.id = id,
  type = "p",
  output = "dataframe"
)

# ----- non-parametric -----

# between-subjects design
expr_t_twosample(
  data = sleep,
```

```

    x = group,
    y = extra,
    type = "np"
  )

  # within-subjects design
  expr_t_twosample(
    data = VR_dilemma,
    x = modality,
    y = score,
    paired = TRUE,
    subject.id = id,
    type = "np",
    output = "dataframe"
  )

  # ----- robust -----

  # between-subjects design
  expr_t_twosample(
    data = sleep,
    x = group,
    y = extra,
    type = "r"
  )

  # within-subjects design
  expr_t_twosample(
    data = VR_dilemma,
    x = modality,
    y = score,
    paired = TRUE,
    subject.id = id,
    type = "r",
    output = "dataframe"
  )

  #' # ----- Bayesian -----

  # between-subjects design
  expr_t_twosample(
    data = sleep,
    x = group,
    y = extra,
    type = "bayes"
  )

  # within-subjects design
  expr_t_twosample(
    data = VR_dilemma,
    x = modality,
    y = score,
    paired = TRUE,
    subject.id = id,
    type = "bayes",
    output = "dataframe"
  )

```

---

`iris_long`*Edgar Anderson's Iris Data in long format.*

---

### Description

Edgar Anderson's Iris Data in long format.

### Usage

```
iris_long
```

### Format

A data frame with 600 rows and 5 variables

- `id`. Dummy identity number for each flower (150 flowers in total).
- `Species`. The species are *Iris setosa*, *versicolor*, and *virginica*.
- `condition`. Factor giving a detailed description of the attribute (Four levels: "Petal.Length", "Petal.Width", "Sepal.Length", "Sepal.Width").
- `attribute`. What attribute is being measured ("Sepal" or "Petal").
- `measure`. What aspect of the attribute is being measured ("Length" or "Width").
- `value`. Value of the measurement.

### Details

This famous (Fisher's or Anderson's) iris data set gives the measurements in centimeters of the variables sepal length and width and petal length and width, respectively, for 50 flowers from each of 3 species of iris. The species are *Iris setosa*, *versicolor*, and *virginica*.

This is a modified dataset from `datasets` package.

### Examples

```
dim(iris_long)
head(iris_long)
dplyr::glimpse(iris_long)
```

---

`movies_long`*Movie information and user ratings from IMDB.com (long format).*

---

### Description

Movie information and user ratings from IMDB.com (long format).

### Usage

```
movies_long
```

### Format

A data frame with 1,579 rows and 8 variables

- `title`. Title of the movie.
- `year`. Year of release.
- `budget`. Total budget (if known) in US dollars
- `length`. Length in minutes.
- `rating`. Average IMDB user rating.
- `votes`. Number of IMDB users who rated this movie.
- `mpaa`. MPAA rating.
- `genre`. Different genres of movies (action, animation, comedy, drama, documentary, romance, short).

### Details

Modified dataset from `ggplot2movies` package.

The internet movie database, <https://imdb.com/>, is a website devoted to collecting movie data supplied by studios and fans. It claims to be the biggest movie database on the web and is run by amazon.

Movies were are identical to those selected for inclusion in `movies_wide` but this dataset has been constructed such that every movie appears in one and only one genre category.

### Source

<https://CRAN.R-project.org/package=ggplot2movies>

### Examples

```
dim(movies_long)
head(movies_long)
dplyr::glimpse(movies_long)
```

---

`movies_wide`*Movie information and user ratings from IMDB.com (wide format).*

---

**Description**

Movie information and user ratings from IMDB.com (wide format).

**Usage**

```
movies_wide
```

**Format**

A data frame with 1,579 rows and 13 variables

- `title`. Title of the movie.
- `year`. Year of release.
- `budget`. Total budget in millions of US dollars
- `length`. Length in minutes.
- `rating`. Average IMDB user rating.
- `votes`. Number of IMDB users who rated this movie.
- `mpaa`. MPAA rating.
- `action`, `animation`, `comedy`, `drama`, `documentary`, `romance`, `short`. Binary variables representing if movie was classified as belonging to that genre.
- `NumGenre`. The number of different genres a film was classified in an integer between one and four

**Details**

Modified dataset from `ggplot2movies` package.

The internet movie database, <https://imdb.com/>, is a website devoted to collecting movie data supplied by studios and fans. It claims to be the biggest movie database on the web and is run by amazon.

Movies were selected for inclusion if they had a known length and had been rated by at least one imdb user. Small categories such as documentaries and NC-17 movies were removed.

**Source**

<https://CRAN.R-project.org/package=ggplot2movies>

**Examples**

```
dim(movies_wide)
head(movies_wide)
dplyr::glimpse(movies_wide)
```

---

tidy\_model\_effectsize *Convert effectsize package output to tidyverse conventions*

---

**Description**

Convert effectsize package output to tidyverse conventions

**Usage**

```
tidy_model_effectsize(data)
```

**Arguments**

data                      Dataframe returned by effectsize functions.

**Examples**

```
df <- effectsize::cohens_d(sleep$extra, sleep$group)
tidy_model_effectsize(df)
```

---

tidy\_model\_parameters *Convert parameters package output to tidyverse conventions*

---

**Description**

Convert parameters package output to tidyverse conventions

**Usage**

```
tidy_model_parameters(model, ...)
```

**Arguments**

model                      Statistical Model.  
...                          Arguments passed to or from other methods. Non-documented arguments are digits, p\_digits and ci\_digits to set the number of digits for the output. See 'Examples' in [model\\_parameters.default](#).

**Examples**

```
model <- lm(mpg ~ wt + cyl, data = mtcars)
tidy_model_parameters(model)
```



---

`VR_dilemma`*Virtual reality moral dilemmas.*

---

**Description**

Virtual reality moral dilemmas.

**Usage**

```
VR_dilemma
```

**Format**

A data frame with 68 rows and 4 variables

- `id`. Dummy identity number for each participant.
- `order`. The order in which the participants completed the two sessions: "text\_first" (0) or "text\_second" (1).
- `modality`. Describes how the moral dilemmas were presented to the participants: either in text format ("text") or in Virtual Reality ("vr").
- `score`. Proportion of "utilitarian" decisions. In other words, of the 4 decisions, how many affirmative were responses. Range: 0 (all utilitarian) - 1 (none utilitarian).

**Details**

Dataset from a study where participants completed identical moral dilemmas in two different sessions held on separate days: in one session, they read text description of the scenario, while in another session they completed the same scenarios in Virtual Reality (videos: <https://www.youtube.com/watch?v=ebdU3HhhYs8>). The study investigated if there was a discrepancy between how people judged the same scenarios while reading them in text versus experiencing them in virtual reality.

**Source**

<https://psyarxiv.com/ry3ap/>

**Examples**

```
dim(VR_dilemma)
head(VR_dilemma)
dplyr::glimpse(VR_dilemma)
```

# Index

## \* datasets

- bugs\_long, 3
- iris\_long, 21
- movies\_long, 22
- movies\_wide, 23
- VR\_dilemma, 25

- bf\_extractor, 2
- bugs\_long, 3

- expr\_contingency\_tab, 4
- expr\_corr\_test, 6
- expr\_meta\_random, 8
- expr\_oneway\_anova, 10
- expr\_t\_onesample, 15
- expr\_t\_twosample, 17
- expr\_template, 13

- iris\_long, 21

- model\_parameters.default, 24
- movies\_long, 22
- movies\_wide, 23

- parameters::model\_parameters.BFBayesFactor(),  
3

- tidy\_model\_effectsize, 24
- tidy\_model\_parameters, 24

- VR\_dilemma, 25